

SENDING DATA FROM RASPBERRY-PI TO IBM WATSON

Date	19 NOVEMBER 2022
Team ID	PNT2022TMID38668
Project Title	GAS LEAKAGE MONITORING AND ALERTING SYSTEM FOR INDUSTRIES

AIM:

To send sensor data (or any dummy data) from Raspberry –Pi to IBM Watson .In our case it is DHT sensors Data.

REQUIREMENTS:

HARDWARE:

- RASPBERRY-PI (3B)(WITH ETHERNET CABLE OR WIFI CONNECTED)
- USB MOUSE
- USB KEYBOARD
- VGA TO HDMI CABLE
- A MONITOR
- RASPBERRY’S POWER SUPPLY
- DHT-11 Sensor
- Connecting Wires


SOFTWARE:

- IBM BLUEMIX ACCOUNT

STEPS TO BE FOLLOWED

Step-1: Create a device in IBM Watson:

- Firstly, login into your IBM-Bluemix account with your e-mail ID and Password.



IBM

Log in to IBM


IBMid [Forgot IBMId?](#)

☒ Remember me ⓘ


[Continue](#) →

Don't have an account? [Create an IBMId](#)


Need help? [Contact the IBMId help desk](#)



➤ Click on catalog on your dashboard screen, then under platform go IoT.



- Check all details and click on create.



Catalog /

Internet of Things Platform

This service is the hub of all things IBM IoT, it is where you can set up and manage your connected devices so that your apps can access their live and historical data.

Type
Service

Provider
IBM

Last updated
08/15/2022

Category
Internet of Things

Compliance
IAM-enabled

Location
Frankfurt
London
Dallas
Washington DC

Related links
[Docs](#)
[Terms](#)

Create

About

Select a location

Frankfurt (eu-de) ▾

Select a pricing plan

Displayed prices do not include tax. Monthly prices shown are for country or location: [United States](#)

Plan	Features	Pricing
Lite	<p>Includes up to 500 registered devices, and a maximum of 200 MB of each data metric</p> <ul style="list-style-type: none">Maximum of 500 registered devicesMaximum of 500 application bindingsMaximum of 200 MB of each of data exchanged, data analyzed and edge data analyzed <p>The Lite service plan for Internet of Things Platform includes up to 500 registered devices, and a maximum of 200 MB each of data exchanged, data analyzed, and edge data analyzed per month.</p>	Free

Summary

Internet of Things Platform **Free**

Location: Frankfurt

Plan: Lite

Service name: Internet of Things Platform-mr

Resource group: Default

☐ I have read and agree to the following license agreements: [Terms](#)

Create

Add to estimate

- click on Launch

Resource list /

Internet of Things Platform-tk


Active Add tags

Details Actions...

Manage

Plan

Connections



Let's get started with IBM Watson IoT Platform

Securely connect, control, and manage devices. Quickly build IoT applications that analyze data from the physical world.

Launch Docs

Ready for the next level?

IBM Watson IoT Platform Journey

✓

Lite

The Lite service plan provides a lightweight development environment to get you started with the connectivity capabilities of Watson IoT Platform.

- Free

○

Non-Production

The Non-Production service plan is a full-featured, fully-integrated offering that enables you to explore Watson IoT Platform to see how the service can fit into your IoT environment.

- Starts at \$500 per month

○

Production

The Production service is a fully managed SaaS offering that enables you to manage and analyze enterprise IoT data.

- Includes IBM Service & Support

- Dashboard of IBM Watson IoT platform,
- Click on Add device

Browse Devices

All Devices Diagnose

This table shows a summary of all devices that have been added. It can be filtered, organized, and searched on using different criteria. To get started, you can add devices by using the Add Device button, or by using API.

Search by Device ID

Device Simulator ☒

<input type="checkbox"/>	Device ID	Status	Device Type	Class ID	Date Added	Descriptive Location
> <input type="checkbox"/>	01234	Disconnected		Device	Nov 14, 2022 9:33 PM	
> <input type="checkbox"/>		Disconnected		Device	Nov 14, 2022 10:07 PM	

Items per page 50 | 1-2 of 2 items

1 of 1 page < 1 >

2 Simulations running

- After click on Add device this page will open

Add Device

Identity Device Information Security Summary

Select a device type for the device that you are adding and give the device a unique ID.

Device Type

Device ID

Cancel Next

Browse Devices

All Devices Diagnose

5 Simulations running

- Go to device type and fill the details.

Browse Action **Device Types** Interfaces

Add Type

Identity Device Information

Device types group devices that have similar characteristics, such as model number, firmware version, or location. Give the device type a unique name and a description that identifies characteristics that are shared by devices of this type.

Type Or

Name

The device type name is used to identify the device type uniquely and uses a restricted set of characters to make it suitable for API use.

Description

5 Simulations running

- Click on Finish

Browse Action **Device Types** Interfaces

Add Type


Identity Device Information

These attributes will be used as a template for new devices that are assigned this device type


Serial Number	<input type="text" value="Enter Serial Number"/>	Manufacturer	<input type="text" value="Enter Manufacturer"/>
Model	<input type="text" value="Enter Model"/>	Device Class	<input type="text" value="Enter Device Class"/>
Description	<input type="text" value="Enter Description"/>	Firmware Version	<input type="text" value="Enter Firmware Version"/>
Hardware Version	<input type="text" value="Enter Hardware Version"/>	Descriptive Location	<input type="text" value="Enter Descriptive Location"/>

2 Simulations running

- Click on Register Device.



- Choose the device and give device ID and then click on next.



➤ Click on Next

The screenshot shows the 'Add Device' form in the 'Device Information' step. The form is divided into two columns. The left column contains fields for 'Serial Number', 'Model', 'Description', and 'Hardware Version'. The right column contains fields for 'Manufacturer', 'Device Class', 'Firmware Version', and 'Descriptive Location'. Below the left column is an 'Add Metadata' button. At the bottom right of the form are 'Back' and 'Next' buttons. The 'Next' button is highlighted in blue. The 'Device Information' step is the active step in the progress bar, indicated by a blue circle. The 'Identity' step is completed, indicated by a checkmark. The 'Security' and 'Summary' steps are not yet started, indicated by empty circles. The 'Browse Devices' button is visible at the bottom left, and '5 Simulations running' is displayed at the bottom right.

Browse Action Device Types Interfaces

Add Device

Identity Device Information Security Summary

You can modify the default device information and enter more information about the device for identification purposes.

Serial Number

Model

Description

Hardware Version

Manufacturer

Device Class

Firmware Version

Descriptive Location

[Add Metadata](#)

[Back](#) [Next](#)

Browse Devices 5 Simulations running

➤ Click on Next

The screenshot shows the 'Add Device' form in the 'Security' step. The form is divided into two columns. The left column is titled 'Auto-generated authentication token (default)' and contains a text area for the token. The right column is titled 'Self-provided authentication token' and contains a text area for the token. Below the text areas are instructions for each option. At the bottom right of the form is a 'Next' button. The 'Security' step is the active step in the progress bar, indicated by a blue circle. The 'Identity' and 'Device Information' steps are completed, indicated by checkmarks. The 'Summary' step is not yet started, indicated by an empty circle. The 'Browse Devices' button is visible at the bottom left, and '5 Simulations running' is displayed at the bottom right.

Browse Action Device Types Interfaces

Add Device

Identity Device Information Security Summary

There are two options for selecting a device authentication token.

Auto-generated authentication token (default)

Allow the service to generate an authentication token for you. Tokens are 18 characters and contain a mix of alphanumeric characters and symbols. The token is returned to you at the end of the device registration process.

Self-provided authentication token

Provide your own authentication token for this device. The token must be between 8 and 36 characters and contain a mix of lowercase and uppercase letters, numbers, and symbols, which can include hyphens, underscores, and periods. Do not use repeated characters, dictionary words, user names, or other predefined sequences.

Authentication Token


Make a note of the generated token. Lost authentication tokens cannot be recovered. Tokens are encrypted before being stored.

Authentication token are encrypted before we store them.


[Next](#)

Browse Devices 5 Simulations running

➤ Click on Finish



➤ Device is created



STEP-2: INSTALLING NECESSARY PACKAGES ON YOUR PI:

- Now we are going to install necessary packages on your pi.
- Open your terminal in your pi and type the following commands
- `curl -LO https://github.com/ibm-messaging/iot-raspberrypi/releases/download/1.0.2.1/iot_1.0-2_armhf.deb`
- `sudo dpkg -i iot_1.0-2_armhf.deb`
- `service iot status`

Following are the images as to what appears on your pi's terminal when u type these commands

```
File Edit Tabs Help
pi@raspberrypi:~$ curl -LO https://github.com/ibm-messaging/iot-raspberrypi/releases/download/1.0.2.1/iot_1.0-2_armhf.deb
  % Total    % Received % Xferd  Average Speed   Time    Time     Time  Current
                                 Dload  Upload   Total   Spent    Left  Speed
100 164 0 164 0 0 157 0 --:--:-- 0:00:01 --:--:-- 157
100 609 0 609 0 0 457 0 --:--:-- 0:00:01 --:--:-- 457
100 110k 100 110k 0 0 20117 0 0:00:03 0:00:03 --:--:-- 48190
pi@raspberrypi:~$ sudo dpkg -i iot_1.0-2_armhf.deb
(Reading database ... 115606 files and directories currently installed.)
Preparing to unpack iot_1.0-2_armhf.deb ...
Unpacking iot (1.0-2) over (1.0-1) ...
Setting up iot (1.0-2) ...
Processing triggers for systemd (232-25+deb9u1) ...
pi@raspberrypi:~$ service iot status
* iot.service - LSB: iot service
   Loaded: loaded (/etc/init.d/iot; generated; vendor preset: enabled)
   Active: active (running) since Mon 2017-10-23 06:56:25 UTC; 17s ago
     Docs: man:systemd-sysv-generator(8)
    CGroup: /system.slice/iot.service
            └─2562 /opt/iot/iot /dev/null

Oct 23 06:56:24 raspberrypi systemd[1]: Starting LSB: Iot service...
Oct 23 06:56:24 raspberrypi iot[2557]: Starting the iot program
Oct 23 06:56:25 raspberrypi iot[2562]: **** Iot Raspberry Pi Sample has started ****
Oct 23 06:56:25 raspberrypi iot[2562]: Config file not found. Going to Quickstart mode
Oct 23 06:56:25 raspberrypi iot[2562]: Running in Quickstart mode
Oct 23 06:56:25 raspberrypi systemd[1]: Started LSB: Iot service.
```

- Then open your terminal and type `pip install ibmiotf`

```
File Edit Tabs Help
pi@raspberrypi:~$ pip install ibmiotf
Collecting ibmiotf
  Downloading ibmiotf-0.3.0.tar.gz (58kB)
    100% |#####| 61kB 510kB/s
Collecting dicttoxml==1.7.4 (from ibmiotf)
  Downloading dicttoxml-1.7.4.tar.gz
    100% |#####| 61kB 1.7MB/s
Collecting iso8601==0.1.10 (from ibmiotf)
  Downloading iso8601-0.1.12-py2.py3-none-any.whl
    100% |#####| 81kB 916kB/s
Collecting paho-mqtt==1.2 (from ibmiotf)
  Downloading paho-mqtt-1.3.1.tar.gz (80kB)
    100% |#####| 81kB 916kB/s
Collecting pytz==2014.7 (from ibmiotf)
  Using cached pytz-2017.2-py2.py3-none-any.whl
Collecting requests==2.5.0 (from ibmiotf)
  Downloading requests-2.18.4-py2.py3-none-any.whl (88kB)
    100% |#####| 92kB 1.0MB/s
Collecting requests-toolbelt==0.7.0 (from ibmiotf)
  Downloading requests-toolbelt-0.8.0-py2.py3-none-any.whl (54kB)
    100% |#####| 61kB 1.6MB/s
Collecting xmldict==0.10.2 (from ibmiotf)
  Downloading xmldict-0.11.0-py2.py3-none-any.whl
    100% |#####| 61kB 1.7MB/s
Collecting urllib3<1.23,>=1.21.1 (from requests==2.5.0->ibmiotf)
  Downloading urllib3-1.22-py2.py3-none-any.whl (132kB)
    100% |#####| 133kB 1.4MB/s
Collecting idna<2.7,>=2.5 (from requests==2.5.0->ibmiotf)
  Downloading idna-2.6-py2.py3-none-any.whl (56kB)
    100% |#####| 61kB 1.7MB/s
Collecting chardet<3.1.0,>=3.0.2 (from requests==2.5.0->ibmiotf)
  Downloading chardet-3.0.4-py2.py3-none-any.whl (133kB)
    100% |#####| 143kB 1.0MB/s
Collecting certifi==2017.4.17 (from requests==2.5.0->ibmiotf)
  Using cached certifi-2017.7.27.1-py2.py3-none-any.whl
Building wheels for collected packages: ibmiotf, dicttoxml, paho-mqtt
Running setup.py bdist_wheel for ibmiotf ... done
Stored in directory: /home/pi/.cache/pip/wheels/7e/f9/45/bbc33ad957e82f7b71ba0e316d65a83d9d735a0d12e0c0418
Running setup.py bdist_wheel for dicttoxml ... done
Stored in directory: /home/pi/.cache/pip/wheels/45/52/59/96910b33ec6a7b2ae66a13765401b50def5468024078e12c0e
Running setup.py bdist_wheel for paho-mqtt ... done
Stored in directory: /home/pi/.cache/pip/wheels/20/d8/0d/acdc8f289011b7be7de71deebef6642fb3be0313dfff0493
Successfully built ibmiotf dicttoxml paho-mqtt
Installing collected packages: dicttoxml, iso8601, paho-mqtt, pytz, urllib3, idna, chardet, certifi, requests, requests-toolbelt, xmldict, ibmiotf
Successfully installed certifi-2017.7.27.1 chardet-3.0.4 dicttoxml-1.7.4 ibmiotf-0.3.0 idna-2.6 iso8601-0.1.12 paho-mqtt-1.3.1 pytz-2017.2 requests-2.18.4 requests-toolbelt-0.8.0 urllib3-1.22 xmldict-0.11.0
pi@raspberrypi:~$
```

- I have sent DHT-11 Sensors data to ibm bluemix .To get the code u need to login into IOT GYAN.
- Then I get the image as follows in my pi's shell:

```

File Edit Shell Debug Options Window Help
Python 2.7.13 (default, Jan 19 2017, 14:48:08)
[GCC 6.3.0 20170124] on linux2
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: /home/pi/Downloads/dht11toibmiot.py =====
2017-10-23 07:10:37,768 ibmiotf.device.Client INFO Connected successfully: d:gegtl4:mydevice:mydevice
SensorData Invalid
Published Temperature = 28 C Humidity = 50 % to IBM Watson
SensorData Invalid
Published Temperature = 28 C Humidity = 50 % to IBM Watson
SensorData Invalid
Published Temperature = 28 C Humidity = 50 % to IBM Watson
SensorData Invalid
Published Temperature = 29 C Humidity = 50 % to IBM Watson
Published Temperature = 29 C Humidity = 50 % to IBM Watson

```

Step-3: checking your data sent on IBM Bluemix:

- After you have sent your sensors data you can check whether it is received at your iot platform Just look at the image below and if u see the same wifi kind of symbol on your created device then your data is being received.

Browse

Action

Device Types

Interfaces

Add Device

Browse Devices

All Devices

Diagnose

This table shows a summary of all devices that have been added. It can be filtered, organized, and searched on using different criteria. To get started, you can add devices by using the Add Device button, or by using API.

Q Search by Device ID

Device Simulator ☒

<input type="checkbox"/>	Device ID	Status	Device Type	Class ID	Date Added	Descriptive Location
> <input type="checkbox"/>	01234	Disconnected		Device	Nov 14, 2022 9:33 PM	
> <input type="checkbox"/>	ESP32_1	Connected	ESP32	Device	Nov 14, 2022 9:27 PM	


Items per page 50 | 1-2 of 2 items

1 of 1 page

< 1 >


5 Simulations running

- After double clicking on your created device you can see the received data as shown in image




Step-4: Creating boards and cards for visualization of data:

- In your Watson platform you have an option called board .Click on it and you get the following window on your screen




- Click on Create a new board to create a board .


The given below window appears give a name and description to your board as shown in the window below.




- Then click on Next you get the below window then again click on Submit




- Then double click on your boards name which you have created.




- Click on Add New Card



- Select the type of Graph u want accordingly and click next



- You get the below window, choose the Device and click on Next.



- Select the event, properly to be visualized on your graph and click next. In my case it is humidity

IBM Watson IoT Platform

temp

Card source data

1902

Card preview

Card information

Create Line chart Card

Connect data set

temp

Property
temperature

Name
temperature

Type
Number

Unit
%

Min
0

Max
100

+ Connect new data set

Back Submit

- Then select the size of the graph and color of the graph board you want and click next

Card source data

01234

Card preview

Card information

Create Line chart Card

Enter title and description of the card

Title
Line chart

Color scheme

A line chart to display time series information with historic and live data

Back Submit

➤ Here is the graph



➤ Repeat the process to get different graphs.



RESULT:

Hence, we were able to send data from our pi to IBM Watson and visualize it on a graph.