SOURCE CODE :

```
#include "DHTesp.h"
#include <cstdlib>
#include <time.h>
#include <WiFi.h>
#include <PubSubClient.h>

#define ORG "pfrrli"
#define DEVICE_TYPE "Rasp"
#define DEVICE_ID "12345"
#define TOKEN "12345678"
#define speed 0.034

char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/data/fmt/json";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;

WiFiClient wifiClient;
PubSubClient client(server, 1883, wifiClient);
float temperature  = 0;
int pH = 0;

String quality_status = "";
String temperture_status = "";



void setup() {
  Serial.begin(99900);


   wifiConnect();
   mqttConnect();
}

void loop() {

  srand(time(0));
```

```
  //initial variable
  int p;

  temperature = random(-20,40);
  pH = random(0,14);
  if(pH > 6.5 && pH < 8.5){
     p = 0;
  }
  else{
     p = 1;
  }

  //set a quality status

  switch (p) {
  case 0:
     quality_status = "Drinkable";
     break;
  case 1:
     quality_status = "Not Drinkable";
     break;
  }

 //Obivously the output.It is like json format 'cause it will help us for future sprints
  String payload = "{";
  payload+="\"pH level is \":";
  payload+=pH;
  payload+=",";
  payload+="\"Temperature of Water\":";
  payload+=(int)temperature;
  payload+=",";
  payload+="\"Alert\":\""+quality_status+"\"}";
  Serial.println(payload);


 if(client.publish(publishTopic, (char*) payload.c_str()))
 {
   Serial.println("Publish OK");
 }
 else{
   Serial.println("Publish failed");
 }
```

```
  delay(1000);


  if (!client.loop())
  {
    mqttConnect();
  }



}


void wifiConnect()
{
  Serial.print("Connecting to ");
  Serial.print("Wifi");
  WiFi.begin("Wokwi-GUEST", "", 6);
  while (WiFi.status() != WL_CONNECTED)
  {
    delay(500);
    Serial.print(".");
  }
  Serial.print("WiFi connected, IP address: ");
  Serial.println(WiFi.localIP());

}


void mqttConnect()
{
  if (!client.connected())
  {
    Serial.print("Reconnecting MQTT client to ");
    Serial.println(server);
    while (!client.connect(clientId, authMethod, token))
    {
      Serial.print(".");
      delay(500);
    }

    Serial.println();
  }
}
```

DIAGRAM.JSON:

```
{
  "version": 1,
  "author": "PNT2022TMID51903",
  "editor": "wokwi",
  "parts": [
    { "type": "wokwi-esp32-devkit-v1", "id": "esp", "top": -16.32, "left": -
0.82, "attrs": {} },
    {
      "type": "wokwi-dht22",
      "id": "dht1",
      "top": -30.22,
      "left": 165.89,
      "attrs": { "temperature": "59.3" }
    }
  ],
  "connections": [
    [ "esp:TX0", "$serialMonitor:RX", "", [] ],
    [ "esp:RX0", "$serialMonitor:TX", "", [] ],
    [ "dht1:SDA", "esp:D15", "green", [ "v0" ] ],
    [ "dht1:VCC", "esp:3V3", "red", [ "v0" ] ],
    [ "dht1:GND", "esp:GND.1", "black", [ "v0" ] ]
  ]
}
```