

## MODEL BUILDING

### Configuring The Learning Process

```
import keras

from keras.preprocessing.image import ImageDataGenerator

#Define the parameters/ arguments for ImageDataGenerator class

train_datagen= ImageDataGenerator (rescale=1./255,shear_range=0.2, rotation_range=180,
zoom_range=0.2, horizontal_flip=True)

test_datagen= ImageDataGenerator (rescale=1./255)

#Applying ImageDataGenerator functionality to trainset

x_train=train_datagen.flow_from_directory(r'C:\Users\dhine\Downloads\archive\Dataset\train
_set'target_size=(128,128),batch_size=32,class_mode='binary')

Found 436 images belonging to 2 classes.

#Applying ImageDataGenerator functionality to testset

x_test=test_datagen.flow_from_directory(r'C:\Users\dhine\Downloads\archive\Dataset\test_s
et'target_size=(128,128),batch_size=32,class_mode='binary')

Found 121 images belonging to 2 classes.

#import model building libraries

#To define Linear initialisation import Sequential

from keras.models import Sequential

#To add layers import Dense
```

```
from keras. layers import Dense
#To Create Convolution kernel import Convolution2D
from keras.layers import Convolution2D
#import Maxpooling layer
from keras. layers import Maxpooling2D
#import flatten layer
from keras. layers import Flatten
import warnings
warnings.filterwarnings('ignore')
#initializing the model
model=Sequential( )
#add convolution layer
model . add (convolution2D(32,(3,3), input_shape(128,128,3),activation='relu'))
#add maxpooling layer
model . add (Maxpooling2D (pool_size=(2,2)))
#add flatten layer
model . add (flatten( ))
#add hidden layer
model.add(Dense(150,activation='relu'))
#add output layer
model.add(Dense(1,activation='sigmoid'))
#configure the learning process
model.compile(loss='binary_crossentropy',optimizer="adam",metrics=["accuracy"])
```