# Project Development Phase Sprint-2

Date	7-November 2022
Team ID	PNT2022TMID35932
Project Name	Hazardous Area Monitoring for Industrial Plant powered by IoT
Maximum Marks	4 Marks

#### ESP32 Program for Temperature and Dummy Gas sensor simulated in Wokwi:

```
#include "DHT.h"// Library for dht22
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#define DHTPIN 15
                    // what pin we're connected to
#define DHTTYPE DHT22 // define type of sensor DHT 11
//GAS SENSOR MQ-02
#define GAS_SENSOR 2
*/
DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr of dht connected
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
//----credentials of IBM Accounts-----
#define ORG "bxddo9"//IBM ORGANITION ID
#define DEVICE TYPE "ESP32"//Device type mentioned in ibm watson IOT Platform
#define DEVICE_ID "Assign4"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "45625689713"
                              //Token
String data3;
float h, t;
int val;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and
format in which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT command type AND
COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the predefined client id by
passing parameter like server id, portand wificredential
const int DHT_PIN = 15;
void setup() {
  Serial.begin(115200);
```

```
Serial.println();
 wificonnect();
 mqttconnect();
}
void loop() {
 //val = analogRead(GAS_SENSOR);
 val = 0;
 h = dht.readHumidity();
 t = dht.readTemperature();
 Serial.print("temp:");
 Serial.println(t);
 Serial.print("Humid:");
 Serial.println(h);
 Serial.print("Gas Sensor:");
 Serial.println(val);
 PublishData(t, h, val);
 delay(1000);
 if (!client.loop()) {
   mqttconnect();
 }
 delay(5000);
/*....retrieving to Cloud......*/
void PublishData(float temp, float humid, int vol) {
 mqttconnect();//function call for connecting to ibm
     creating the String in in form JSon to update the data to ibm cloud
 */
 String payload = "{\"temp\":";
 payload += temp;
 payload += "," "\"Humid\":";
 payload += humid;
 payload += ",""\"Gas Sensor\":";
 payload += val;
 payload += "}";
  Serial.print("Sending payload: ");
  Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
   Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will
print publish ok in Serial monitor or else it will print publish failed
 } else {
   Serial.println("Publish failed");
 }
}
void mqttconnect() {
 if (!client.connected()) {
   Serial.print("Reconnecting client to ");
   Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
     Serial.print(".");
     delay(500);
   }
```


```
initManagedDevice();
     Serial.println();
  }
}
void wificonnect() //function defination for wificonnect
{
  Serial.println();
  Serial.print("Connecting to ");
  WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
  while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  }
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
}
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
    Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
    Serial.println("subscribe to cmd FAILED");
  }
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++) {</pre>
    //Serial.print((char)payload[i]);
    data3 += (char)payload[i];
  Serial.println("data: "+ data3);
 if(data3=="lighton")
Serial.println(data3);
  }
 else
Serial.println(data3);
data3="";
}
```

### **Wokwi Simulation Output:**

```
Connecting to ...
WiFi connected
IP address:
10.10.0.2
Reconnecting client to bxddo9.messaging.internetofthings.ibmcloud.com
iot-2/cmd/command/fmt/String
subscribe to cmd OK

temp:14.90
Humid:40.00
Gas Sensor:0
Sending payload: {"temp":14.90,"Humid":40.00,"Gas Sensor":0}
Publish ok
temp:14.90
```

## **Wokwi Circuit Diagram:**



### IBM Watson Dashboard view:

