Assignment 4

Assignment date	06 November 2022
Student name	Arun D
Student roll no	711719104011
Team ID	PNT2022TMID31586

Question 1:

Pull an image from docker hub and run it on docker playground.

Solution 1:

docker pull uifd/ui-for-docker

docker run -d -p 9000:9000 --privileged -v /var/run/docker.sock:/var/run/docker.sock uifd/ui-for-docker



Docker playground:



Docker UI:



Question 2:

Create a docker file for the job portal app or hello world app and deploy it in docker desktop app.

Solution 2:

DockerFile

Dockerfile - Notepad

File Edit Format View Help

```
FROM python:3.8
WORKDIR /app
ADD . /app
COPY requirements.txt /app
RUN python3 -m pip install -r requirements.txt
EXPOSE 5000
CMD ["python","app.py"]
```

Bulid Docker image



Deploy it on Docker hub



Tested it using Docker playground



Question 3:

Create an IBM container registry and deploy helloworld app or job portal app.

Solution 3:

My image link: au.icr.io/hello-world-app/hello-world




C:\Windows\System32\cmd.exe - docker run -p 5000:5000 au.icr.io/hello-world-app/hello-world
E:\Study materials\Sem 7\IBM\Exercise\Assignment4>docker tag hello-world au.icr.io/hello-world-app/hello-world
E:\Study materials\Sem 7\IBM\Exercise\Assignment4>docker push au.icr.io/hello-world-app/hello-world
Using default tag: latest
The push refers to repository [au.icr.io/hello-world-app/hello-world]
492bcd5cc069: Pushed
006e0938fc5e: Pushed
4bb20ce8724f: Pushed
402dea3c8533: Pushed
f5d161bba139: Pushed
1569e0d95ce6: Pushed
d9e08da15d0c: Pushed
6b183c62e3d7: Mounted from hello-world-app/helloworldapp
882fd36bfd35: Mounted from hello-world-app/helloworldapp
d1dec9917839: Mounted from hello-world-app/helloworldapp
d38adf39e1dd: Mounted from hello-world-app/helloworldapp
4ed121b04368: Mounted from hello-world-app/helloworldapp
d9d07d703dd5: Mounted from hello-world-app/helloworldapp
latest: digest: sha256:0036fe1456627bba779e865ba4793212e8332e6835b48c6b5814784adb70c46f size: 3049
E:\Study materials\Sem 7\IBM\Exercise\Assignment4>ibmcloud cr image-list
Listing images...
Repository Tag Digest Namespace Created Size Security status
au.icr.io/hello-world-app/hello-world latest 0036fe145662 hello-world-app 12 minutes ago 356 MB -
OK
E:\Study materials\Sem 7\IBM\Exercise\Assignment4>docker run -p 5000:5000 au.icr.io/hello-world-app/hello-world
* Serving Flask app 'app'
* Debug mode: off
WARNING: This is a development server. Do not use it in a production deployment. Use a production WSGI server instead.
* Running on all addresses (0.0.0.0)
* Running on http://127.0.0.1:5000
* Running on http://172.17.0.2:5000
Press CTRL+C to quit
172.17.0.1 - - [03/Nov/2022 19:35:58] "GET / HTTP/1.1" 200 -


Container Registry
Quick start
Namespaces 1
Repositories 1
Images 1
Trash 1
Settings
Repositories
Location
Sydney
Search
Create
Name
Image count
Namespace
Last updated
hello-world
au.icr.io/hello-world-app/hello-world
1
hello-world-app
15 minutes ago
Items per page: 25
1–1 of 1 item
1 of 1 page

Question 4:

Create a kubernetes cluster in IBM cloud and deploy helloworld image or jobportal image and also expose the same app to run in nodeport.

Solution 4:

https://raw.githubusercontent.com/itsmona14/IBM-Assignment-cloud/main/deployment.yaml

```
apiVersion: v1
kind: Service
metadata:
   name: hello-world-deployment
spec:
   ports:
   - port: 5000
     targetPort: 5000
   selector:
     app: hello-world
---
apiVersion: apps/v1
kind: Deployment
metadata:
   name: hello-world-deployment
spec:
   replicas: 1
   selector:
     matchLabels:
       app: hello-world
   template:
     metadata:
       labels:
         app: hello-world
     spec:
       containers:
       - name: hello-world
         image: au.icr.io/hello-world-app/hello-world
         imagePullPolicy: Always
         ports:
         - containerPort: 5000
```




kubernetes
default
Search
Workloads > Deployments
Workloads
Cron Jobs
Daemon Sets
Deployments
Jobs
Pods
Replica Sets
Replication Controllers
Stateful Sets
Service
Ingresses
Ingress Classes
Services
Config and Storage
Config Maps
CPU Usage
CPU (cores)
0.01
0
Memory Usage
Memory (bytes)
20 Mi
0 Mi
Deployments
Name
Images
Labels
Pods
Created
hello-world-deployment
Show all
-
1 / 1
24 minutes ago


kubernetes
default
Search
Workloads > Pods > hello-world-deployment-6c75b9c898-p4ntv > Logs
Workloads
Cron Jobs
Daemon Sets
Deployments
Jobs
Pods
Replica Sets
Replication Controllers
Stateful Sets
Service
Ingresses
Ingress Classes
Services
Config and Storage
Logs from hello-world in hello-world-dep...
* Serving Flask app 'app'
* Debug mode: off
WARNING: This is a development server. Do not use it in a production deployment. Use a production WSGI server instead.
* Running on all addresses (0.0.0.0)
* Running on http://127.0.0.1:5000
* Running on http://172.30.82.142:5000
Press CTRL+C to quit
Logs from Nov 4, 2022 to Nov 4, 2022 UTC