

# Gas Leakage Monitoring and Alerting System

## Literature Survey – 1

### Summary:

The author has observed gas leakage and LPG levels where gas leakage occurs automatically. The authors suggests that gas leakage is performed by various gas sensors. Whose author has worked on gas leaks and mentions that we can take care if a found using a sensor and gas booking can be done automatically when a small amount of gas is taken closed

RFID tag microcontroller, pressure sensors and buzzers are used to monitor gas. Through this paper important parameters are used to find the level of gas in the container. The good purpose of this project is to get notification of gas leak to user when gas leakage is started.

Arduino was originally created as a tool for fast sampling and activities for students with no knowledge for electronics. This paper uses a microcontroller, buzzer and a gas sensor to detect gas leakage system. When a gas leak is detected by a gas sensor ,the microcontroller turn on the buzzer in critical condition. The author suggest that this message or instruction may be displayed using an LCD display for LPG monitoring.

The proposed system detects LPG leaks and alerts customers. The alarm starts when the system notice and increases in LPG leakage concentration by sending an alarm and sending a message to specific mobile phone. The device assures safety and prevents explosions. A microcontroller based system based on gas sensor(MQ6) has been developed in proposed system to detect LPG leakage . The unit is also integrated with an alarm unit to detect signal a leak