Project: Real-Time Communication system powered by Al for specially abled

```
In [1]:
from keras.models import Sequential
from keras.layers import Dense
from keras.layers import Convolution2D
from keras.layers import MaxPooling2D
from keras.layers import Dropout
from keras.layers import Flatten
from tensorflow.keras.preprocessing.image import ImageDataGenerator
In [2]:
import numpy as np
import matplotlib.pyplot as plt #to view graph in colab itself
import IPython.display as display
from PIL import Image
import pathlib
In [14]:
import tensorflow as tf
import os
In [3]:
from google.colab import drive
drive.mount('/content/drive')
Mounted at /content/drive
In [ ]:
| unzip '/content/drive/MyDrive/Classroom/conversation engine for deaf and dumb.zip'
In [7]:
train datagen=ImageDataGenerator(rescale=1./255, shear range=0.2, zoom range=0.2, horizontal
flip=True)
In [8]:
test datagen=ImageDataGenerator(rescale=1./255)
In [9]:
x train=train_datagen.flow_from_directory('/content/Dataset/training_set',target_size=(64
,64),batch size=200,
                                           class mode='categorical',color mode="grayscale"
")
Found 15750 images belonging to 9 classes.
In [10]:
x test=test datagen.flow from directory('/content/Dataset/test set',target size=(64,64),
batch size=200,
                                           class mode='categorical', color mode="grayscale"
")
```

Found 2250 images belonging to 9 classes.

Add Layers

```
In [15]:
model=Sequential()
```

Add The Convolution Layer

```
In [16]:
```

```
model.add(Convolution2D(32,(3,3),input_shape=(64,64,1),activation='relu'))
```

Add Pooling Layer

```
In [17]:
```

```
model.add(MaxPooling2D(pool_size=(2,2)))
```

Add The Flatten Layer

```
In [18]:
```

```
model.add(Flatten())
```

Adding The Dense Layers

```
In [19]:
```

```
#1st hidden layer
model.add(Dense(units=512,activation='relu'))
#2nd hidden layer
model.add(Dense(units=261,activation='relu'))
```

```
In [20]:
```

```
model.add(Dense(units=9,activation='softmax'))
```

Compile The Model

```
In [21]:
```

```
model.compile(loss='categorical_crossentropy',optimizer='adam',metrics=['accuracy'])
```

Fit The Model

```
In [22]:
```

```
\label{lem:condition} $$ model.fit\_generator(x\_train, steps\_per\_epoch=len(x\_train), epochs=10, validation\_data=x\_test, validation\_steps=len(x\_test)) $$
```

/usr/local/lib/python3.7/dist-packages/ipykernel_launcher.py:1: UserWarning: `Model.fit_g enerator` is deprecated and will be removed in a future version. Please use `Model.fit`, which supports generators.

"""Entry point for launching an IPython kernel.

```
Epoch 5/10
val_loss: 0.3130 - val_accuracy: 0.9778
Epoch 6/10
val_loss: 0.3312 - val_accuracy: 0.9769
Epoch 7/10
val_loss: 0.3252 - val_accuracy: 0.9769
Epoch 8/10
79/79 [============= ] - 100s 1s/step - loss: 0.0051 - accuracy: 0.9985 -
val loss: 0.3386 - val_accuracy: 0.9751
Epoch 9/10
val loss: 0.3241 - val accuracy: 0.9764
Epoch 10/10
val loss: 0.3893 - val accuracy: 0.9751
Out[22]:
```

Save The Model

```
In [23]:
```

```
model.save('aslpng2.h5')
```

Import The Packages And Load The Saved Model

<keras.callbacks.History at 0x7faea88e3f50>

In [24]:

```
from tensorflow.keras.models import load_model
import numpy as np
import cv2
from tensorflow.keras.preprocessing import image
```

In [25]:

```
model=load_model('aslpng2.h5')
```

In [29]:

```
img=image.load_img('/content/Dataset/test_set/C/15.png',target_size=(200,300))
img
```

Out[29]:

