


TEAM ID: PNT2022TMID17645

## PROJECT NAME: DemandEst - AI powered Food Demand Forecaster

### Team Leader



The screenshot displays a Jupyter Notebook interface with the following content:

### Reading And Merging .Csv Files

**In [104]:**

```
body = client_ebb884ca98d444a5ae59a6874ea685aa.get_object(Bucket='fooddemandforecatsing-donotdelete-pr-cdss9tfwyg4lgb',Key='meal_
# add missing __iter__ method, so pandas accepts body as file-like object
if not hasattr(body, "__iter__"): body.__iter__ = types.MethodType( __iter__, body )

meal_info = pd.read_csv(body)
```

**In [105]:** meal\_info.head()

**Out[105]:**

	meal_id	category	cuisine
0	1885	Beverages	Thai
1	1993	Beverages	Thai
2	2539	Beverages	Thai
3	1248	Beverages	Indian
4	2631	Beverages	Indian

**In [106]:**

```
body = client_ebb884ca98d444a5ae59a6874ea685aa.get_object(Bucket='fooddemandforecatsing-donotdelete-pr-cdss9tfwyg4lgb',Key='fulf
# add missing __iter__ method, so pandas accepts body as file-like object
if not hasattr(body, "__iter__"): body.__iter__ = types.MethodType( __iter__, body )

fulfilment_center_info = pd.read_csv(body)
```

**In [107]:** fulfilment\_center\_info.head()

**Out[107]:**

	center_id	city_code	region_code	center_type	op_area
0	11	679	56	TYPE_A	3.7
1	13	590	56	TYPE_B	6.7
2	124	590	56	TYPE_C	4.0
3	66	648	34	TYPE_A	4.1
4	94	632	34	TYPE_C	3.6

Merging train.csv and meal\_info.csv dataset by using common key id:

We notice that meal\_id column in train.csv is similar to meal\_id in meal\_info.csv dataset. Let us merge these two datasets, train.csv and meal\_info.csv using common key meal\_id and name the table as trainfinal.

**In [108]:** trainfinal = pd.merge(train, meal\_info, on="meal\_id", how="outer")

Merging trainfinal.csv and fulfilment\_center\_info.csv dataset by using common key id:

We notice that center\_id column in trainfinal.csv is similar to center\_id in fulfilment\_center\_info.csv dataset. Let us merge these two datasets, trainfinal.csv and fulfilment\_center\_info.csv using common key center\_id and store it back in trainfinal. Display the first five rows of trainfinal using head().

**In [109]:** trainfinal = pd.merge(trainfinal, fulfilment\_center\_info, on="center\_id", how="outer")

Merging train.csv and meal\_info.csv dataset by using common key id:

We notice that meal\_id column in train.csv is similar to meal\_id in meal\_info.csv dataset. Let us merge these two datasets, train.csv and meal\_info.csv using common key meal\_id and name the table as trainfinal.

```
In [108]: trainfinal = pd.merge(train, meal_info, on="meal_id", how="outer")
```

Merging trainfinal.csv and fulfilment\_center\_info.csv dataset by using common key id:

We notice that center\_id column in trainfinal.csv is similar to center\_id in fulfilment\_center\_info.csv dataset. Let us merge these two datasets, trainfinal.csv and fulfilment\_center\_info.csv using common key center\_id and store it back in trainfinal. Display the first five rows of trainfinal using head().

```
In [109]: trainfinal = pd.merge(trainfinal, fulfilment_center_info, on="center_id", how="outer")
trainfinal.head()
```

```
Out[109]:
```

	id	week	center_id	meal_id	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders	category	cuisine	city_code	regio
0	1379560	1	55	1885	136.83	152.29	0	0	177	Beverages	Thai	647	
1	1018704	2	55	1885	135.83	152.29	0	0	323	Beverages	Thai	647	
2	1196273	3	55	1885	132.92	133.92	0	0	96	Beverages	Thai	647	
3	1116527	4	55	1885	135.86	134.86	0	0	163	Beverages	Thai	647	
4	1343872	5	55	1885	146.50	147.50	0	0	215	Beverages	Thai	647	

## Team Member 1

### Reading And Merging .Csv Files

```
In [104]: body = client_ebb884ca98d444a5ae59a6874ea685aa.get_object(Bucket='fooddemandforecatsing-donotdelete-pr-cdss9tfwyg4lgb',Key='meal_info.csv')
# add missing __iter__ method, so pandas accepts body as file-like object
if not hasattr(body, "__iter__"): body.__iter__ = types.MethodType( __iter__, body )

meal_info = pd.read_csv(body)
```

```
In [105]: meal_info.head()
```

```
Out[105]:
```

	meal_id	category	cuisine
0	1885	Beverages	Thai
1	1993	Beverages	Thai
2	2539	Beverages	Thai
3	1248	Beverages	Indian
4	2631	Beverages	Indian

```
In [106]: body = client_ebb884ca98d444a5ae59a6874ea685aa.get_object(Bucket='fooddemandforecatsing-donotdelete-pr-cdss9tfwyg4lgb',Key='fulfilment_center_info.csv')
# add missing __iter__ method, so pandas accepts body as file-like object
if not hasattr(body, "__iter__"): body.__iter__ = types.MethodType( __iter__, body )

fulfilment_center_info = pd.read_csv(body)
```

IBM Home Page - Select or create a notebook Code - Jupyter Notebook

localhost:8891/notebooks/Downloads/SBSPS-Challenge-8325-Food-Demand-Forecasting-for-Food-Delivery-Company-using-IBM-Cloud-main/SBSPS-Challenge-...

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

```
fulfilment_center_info = pd.read_csv(body)
```

In [107]: `fulfilment_center_info.head()`

Out[107]:

	center_id	city_code	region_code	center_type	op_area
0	11	679	56	TYPE_A	3.7
1	13	590	56	TYPE_B	6.7
2	124	590	56	TYPE_C	4.0
3	66	648	34	TYPE_A	4.1
4	94	632	34	TYPE_C	3.6

Merging train.csv and meal\_info.csv dataset by using common key id:

We notice that meal\_id column in train.csv is similar to meal\_id in meal\_info.csv dataset. Let us merge these two datasets, train.csv and meal\_info.csv using common key meal\_id and name the table as trainfinal.

In [108]: `trainfinal = pd.merge(train, meal_info, on="meal_id", how="outer")`

Merging trainfinal.csv and fulfilment\_center\_info.csv dataset by using common key id:

We notice that center\_id column in trainfinal.csv is similar to center\_id in fulfilment\_center\_info.csv dataset. Let us merge these two datasets, trainfinal.csv and fulfilment\_center\_info.csv using common key center\_id and store it back in trainfinal. Display the first five rows of trainfinal using head().

In [109]: `trainfinal = pd.merge(trainfinal, fulfilment_center_info, on="center_id", how="outer")`

IBM Home Page - Select or create a notebook Code - Jupyter Notebook

localhost:8891/notebooks/Downloads/SBSPS-Challenge-8325-Food-Demand-Forecasting-for-Food-Delivery-Company-using-IBM-Cloud-main/SBSPS-Challenge-...

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

3	66	648	34	TYPE_A	4.1
4	94	632	34	TYPE_C	3.6

Merging train.csv and meal\_info.csv dataset by using common key id:

We notice that meal\_id column in train.csv is similar to meal\_id in meal\_info.csv dataset. Let us merge these two datasets, train.csv and meal\_info.csv using common key meal\_id and name the table as trainfinal.

In [108]: `trainfinal = pd.merge(train, meal_info, on="meal_id", how="outer")`

Merging trainfinal.csv and fulfilment\_center\_info.csv dataset by using common key id:

We notice that center\_id column in trainfinal.csv is similar to center\_id in fulfilment\_center\_info.csv dataset. Let us merge these two datasets, trainfinal.csv and fulfilment\_center\_info.csv using common key center\_id and store it back in trainfinal. Display the first five rows of trainfinal using head().

In [109]: `trainfinal = pd.merge(trainfinal, fulfilment_center_info, on="center_id", how="outer")`  
`trainfinal.head()`

Out[109]:

	id	week	center_id	meal_id	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders	category	cuisine	city_code	region
0	1379560	1	55	1885	136.83	152.29	0	0	177	Beverages	Thai	647	
1	1018704	2	55	1885	135.83	152.29	0	0	323	Beverages	Thai	647	
2	1196273	3	55	1885	132.92	133.92	0	0	96	Beverages	Thai	647	
3	1116527	4	55	1885	135.86	134.86	0	0	163	Beverages	Thai	647	
4	1343872	5	55	1885	146.50	147.50	0	0	215	Beverages	Thai	647	

## Team Member 2

The screenshot shows a Jupyter Notebook interface with the title "Reading And Merging .Csv Files". The notebook is running on a local host (localhost:8891) and is connected to a Python 3 (ipykernel) environment. The code in the notebook is as follows:

```
In [104]: body = client_ebb884ca98d444a5ae59a6874ea685aa.get_object(Bucket='fooddemandforecating-donotdelete-pr-cdss9tfwyg4lgb',Key='meal_info.csv')
# add missing __iter__ method, so pandas accepts body as file-like object
if not hasattr(body, "__iter__"): body.__iter__ = types.MethodType( __iter__, body )

meal_info = pd.read_csv(body)

In [105]: meal_info.head()

Out[105]:
```

	meal_id	category	cuisine
0	1885	Beverages	Thai
1	1993	Beverages	Thai
2	2539	Beverages	Thai
3	1248	Beverages	Indian
4	2631	Beverages	Indian

```
In [106]: body = client_ebb884ca98d444a5ae59a6874ea685aa.get_object(Bucket='fooddemandforecating-donotdelete-pr-cdss9tfwyg4lgb',Key='fulfilment_center_info.csv')
# add missing __iter__ method, so pandas accepts body as file-like object
if not hasattr(body, "__iter__"): body.__iter__ = types.MethodType( __iter__, body )

fulfilment_center_info = pd.read_csv(body)
```

The screenshot shows a Jupyter Notebook interface with the title "Merging train.csv and meal\_info.csv dataset by using common key id:". The notebook is running on a local host (localhost:8891) and is connected to a Python 3 (ipykernel) environment. The code in the notebook is as follows:

```
fulfilment_center_info = pd.read_csv(body)

In [107]: fulfilment_center_info.head()

Out[107]:
```

	center_id	city_code	region_code	center_type	op_area
0	11	679	56	TYPE_A	3.7
1	13	590	56	TYPE_B	6.7
2	124	590	56	TYPE_C	4.0
3	66	648	34	TYPE_A	4.1
4	94	632	34	TYPE_C	3.6

Merging train.csv and meal\_info.csv dataset by using common key id:

We notice that meal\_id column in train.csv is similar to meal\_id in meal\_info.csv dataset. Let us merge these two datasets, train.csv and meal\_info.csv using common key meal\_id and name the table as trainfinal.

```
In [108]: trainfinal = pd.merge(train, meal_info, on="meal_id", how="outer")
```

Merging trainfinal.csv and fulfilment\_center\_info.csv dataset by using common key id:

We notice that center\_id column in trainfinal.csv is similar to center\_id in fulfilment\_center\_info.csv dataset. Let us merge these two datasets, trainfinal.csv and fulfilment\_center\_info.csv using common key center\_id and store it back in trainfinal. Display the first five rows of trainfinal using head().

```
In [109]: trainfinal = pd.merge(trainfinal,fulfilment_center_info, on="center_id", how="outer")
```

Merging train.csv and meal\_info.csv dataset by using common key id:

We notice that meal\_id column in train.csv is similar to meal\_id in meal\_info.csv dataset. Let us merge these two datasets, train.csv and meal\_info.csv using common key meal\_id and name the table as trainfinal.

```
In [108]: trainfinal = pd.merge(train, meal_info, on="meal_id", how="outer")
```

Merging trainfinal.csv and fulfilment\_center\_info.csv dataset by using common key id:

We notice that center\_id column in trainfinal.csv is similar to center\_id in fulfilment\_center\_info.csv dataset. Let us merge these two datasets, trainfinal.csv and fulfilment\_center\_info.csv using common key center\_id and store it back in trainfinal. Display the first five rows of trainfinal using head().

```
In [109]: trainfinal = pd.merge(trainfinal, fulfilment_center_info, on="center_id", how="outer")
trainfinal.head()
```

```
Out[109]:
```

	id	week	center_id	meal_id	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders	category	cuisine	city_code	regio
0	1379560	1	55	1885	136.83	152.29	0	0	177	Beverages	Thai	647	
1	1018704	2	55	1885	135.83	152.29	0	0	323	Beverages	Thai	647	
2	1196273	3	55	1885	132.92	133.92	0	0	96	Beverages	Thai	647	
3	1116527	4	55	1885	135.86	134.86	0	0	163	Beverages	Thai	647	
4	1343872	5	55	1885	146.50	147.50	0	0	215	Beverages	Thai	647	

## Team Member 3

### Reading And Merging .Csv Files

```
In [104]: body = client_ebb884ca98d444a5ae59a6874ea685aa.get_object(Bucket='fooddemandforecatsing-donotdelete-pr-cdss9tfwyg4lgb',Key='meal_info.csv')
# add missing __iter__ method, so pandas accepts body as file-like object
if not hasattr(body, "__iter__"): body.__iter__ = types.MethodType( __iter__, body )

meal_info = pd.read_csv(body)
```

```
In [105]: meal_info.head()
```

```
Out[105]:
```

	meal_id	category	cuisine
0	1885	Beverages	Thai
1	1993	Beverages	Thai
2	2539	Beverages	Thai
3	1248	Beverages	Indian
4	2631	Beverages	Indian

```
In [106]: body = client_ebb884ca98d444a5ae59a6874ea685aa.get_object(Bucket='fooddemandforecatsing-donotdelete-pr-cdss9tfwyg4lgb',Key='fulfilment_center_info.csv')
# add missing __iter__ method, so pandas accepts body as file-like object
if not hasattr(body, "__iter__"): body.__iter__ = types.MethodType( __iter__, body )

fulfilment_center_info = pd.read_csv(body)
```

IBM | Home Page - Select or create a notebook | Code - Jupyter Notebook

localhost:8891/notebooks/Downloads/SBSPS-Challenge-8325-Food-Demand-Forecasting-for-Food-Delivery-Company-using-IBM-Cloud-main/SBSPS-Challenge-...

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (pykernel)

```
fulfilment_center_info = pd.read_csv(body)
```

In [107]: `fulfilment_center_info.head()`

Out[107]:

	center_id	city_code	region_code	center_type	op_area
0	11	679	56	TYPE_A	3.7
1	13	590	56	TYPE_B	6.7
2	124	590	56	TYPE_C	4.0
3	66	648	34	TYPE_A	4.1
4	94	632	34	TYPE_C	3.6

Merging train.csv and meal\_info.csv dataset by using common key id:

We notice that meal\_id column in train.csv is similar to meal\_id in meal\_info.csv dataset. Let us merge these two datasets, train.csv and meal\_info.csv using common key meal\_id and name the table as trainfinal.

In [108]: `trainfinal = pd.merge(train, meal_info, on="meal_id", how="outer")`

Merging trainfinal.csv and fulfilment\_center\_info.csv dataset by using common key id:

We notice that center\_id column in trainfinal.csv is similar to center\_id in fulfilment\_center\_info.csv dataset. Let us merge these two datasets, trainfinal.csv and fulfilment\_center\_info.csv using common key center\_id and store it back in trainfinal. Display the first five rows of trainfinal using head().

In [109]: `trainfinal = pd.merge(trainfinal, fulfilment_center_info, on="center_id", how="outer")`

IBM | Home Page - Select or create a notebook | Code - Jupyter Notebook

localhost:8891/notebooks/Downloads/SBSPS-Challenge-8325-Food-Demand-Forecasting-for-Food-Delivery-Company-using-IBM-Cloud-main/SBSPS-Challenge-...

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (pykernel)

```
3 66 648 34 TYPE_A 4.1
4 94 632 34 TYPE_C 3.6
```

Merging train.csv and meal\_info.csv dataset by using common key id:

We notice that meal\_id column in train.csv is similar to meal\_id in meal\_info.csv dataset. Let us merge these two datasets, train.csv and meal\_info.csv using common key meal\_id and name the table as trainfinal.

In [108]: `trainfinal = pd.merge(train, meal_info, on="meal_id", how="outer")`

Merging trainfinal.csv and fulfilment\_center\_info.csv dataset by using common key id:

We notice that center\_id column in trainfinal.csv is similar to center\_id in fulfilment\_center\_info.csv dataset. Let us merge these two datasets, trainfinal.csv and fulfilment\_center\_info.csv using common key center\_id and store it back in trainfinal. Display the first five rows of trainfinal using head().

In [109]: `trainfinal = pd.merge(trainfinal, fulfilment_center_info, on="center_id", how="outer")`  
`trainfinal.head()`

Out[109]:

	id	week	center_id	meal_id	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders	category	cuisine	city_code	region_code
0	1379560	1	55	1885	136.83	152.29	0	0	177	Beverages	Thai	647	
1	1018704	2	55	1885	135.83	152.29	0	0	323	Beverages	Thai	647	
2	1196273	3	55	1885	132.92	133.92	0	0	96	Beverages	Thai	647	
3	1116527	4	55	1885	135.86	134.86	0	0	163	Beverages	Thai	647	
4	1343872	5	55	1885	146.50	147.50	0	0	215	Beverages	Thai	647	