Assignment – 4

Assignment Date	15 October 2022
Student Name	SASIKUMAR.S
Student Roll Number	820319205032
Maximum Marks	2 Marks

Importing Model building libraries

```
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn import preprocessing
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras_preprocessing import sequence
from keras.utils import to_categorical
from keras.models import load model
```

Importing NLTK libraries

```
import csv
import tensorflow as tf
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from tensorflow.keras.preprocessing.text import Tokenizer
from tensorflow.keras.preprocessing.sequence import pad_sequences
import nltk
nltk.download('stopwords')
from nltk.corpus import stopwords
STOPWORDS = set(stopwords.words('english'))

[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data] Unzipping corpora/stopwords.zip.
```

Reading dataset and preprocessing

```
from google.colab import drive
drive.mount('/content/gdrive')
```

Mounted at /content/gdrive

```
Df=
pd.read_csv('/content/gdrive/MyDrive/spam.csv',delimiter=',',encoding='latin-
1')
df.head()
OUTPUT:
    ν1
                                                        v2 Unnamed: 2
0
   ham Go until jurong point, crazy.. Available only ...
                                                                 NaN
                            Ok lar... Joking wif u oni...
1
                                                                  NaN
   spam Free entry in 2 a wkly comp to win FA Cup fina...
                                                                  NaN
   ham U dun say so early hor... U c already then say...
3
                                                                  NaN
   ham Nah I don't think he goes to usf, he lives aro...
                                                                  NaN
 Unnamed: 3 Unnamed: 4
0
        NaN
                   NaN
1
        NaN
                   NaN
2
        NaN
                   NaN
3
        NaN
                   NaN
4
        NaN
                    NaN
from google.colab import drive
drive.mount('/content/gdrive')
df.drop(['Unnamed: 2','Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
df.info()
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
    Column Non-Null Count Dtype
    -----
0
    v1
             5572 non-null
                            object
1
            5572 non-null
                            object
    v2
dtypes: object(2)
memory usage: 87.2+ KB
df.groupby(['v1']).size()
v1
ham
       4825
spam
        747
dtype: int64
#Label Encoding Required Column
X = df.v2
Y = df.v1
```

```
le = preprocessing.LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)

# Test and train data split
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
# Tokenisation function
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = sequence.pad_sequences(sequences,maxlen=max_len)
```

Create Model

Add layers (LSTM ,Dense-(HiddenLayers),Ouput)

```
#LSTM model
inputs = Input(name='InputLayer',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FullyConnectedLayer1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='OutputLayer')(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

OUTPUT:

Model: "model"

Layer (type)	Output Shape	Param #
InputLayer (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 64)	29440
FullyConnectedLayer1 (Dense	e (None, 256)	16640

```
activation (Activation)
                     (None, 256)
                                         0
dropout (Dropout)
                     (None, 256)
                                         0
                     (None, 1)
OutputLayer (Dense)
                                         257
activation 1 (Activation)
                     (None, 1)
                                         0
______
Total params: 96,337
```

Trainable params: 96,337 Non-trainable params: 0

model.fit(sequences matrix,Y train,batch size=128,epochs=25,validation split= 0.2)

OUTPUT:

```
Epoch 1/25
30/30 [============ ] - 11s 274ms/step - loss: 0.3376 -
accuracy: 0.8659 - val loss: 0.1359 - val accuracy: 0.9789
Epoch 2/25
accuracy: 0.9762 - val loss: 0.0471 - val accuracy: 0.9863
Epoch 3/25
accuracy: 0.9863 - val_loss: 0.0401 - val_accuracy: 0.9863
Epoch 4/25
accuracy: 0.9886 - val loss: 0.0431 - val accuracy: 0.9884
Epoch 5/25
accuracy: 0.9923 - val loss: 0.0563 - val accuracy: 0.9863
Epoch 6/25
30/30 [============= ] - 10s 333ms/step - loss: 0.0176 -
accuracy: 0.9947 - val_loss: 0.1245 - val_accuracy: 0.9789
Epoch 7/25
accuracy: 0.9952 - val_loss: 0.0629 - val_accuracy: 0.9863
Epoch 8/25
accuracy: 0.9960 - val loss: 0.0646 - val accuracy: 0.9852
accuracy: 0.9968 - val_loss: 0.0945 - val_accuracy: 0.9842
Epoch 10/25
```

```
accuracy: 0.9982 - val loss: 0.0975 - val accuracy: 0.9842
Epoch 11/25
accuracy: 0.9992 - val loss: 0.1190 - val accuracy: 0.9863
Epoch 12/25
30/30 [=========== - - 8s 256ms/step - loss: 0.0041 -
accuracy: 0.9987 - val loss: 0.1252 - val accuracy: 0.9852
Epoch 13/25
accuracy: 0.9984 - val loss: 0.1310 - val accuracy: 0.9852
Epoch 14/25
accuracy: 0.9992 - val loss: 0.1534 - val accuracy: 0.9842
Epoch 15/25
accuracy: 0.9987 - val loss: 0.1294 - val accuracy: 0.9842
Epoch 16/25
accuracy: 0.9997 - val_loss: 0.1495 - val_accuracy: 0.9852
Epoch 17/25
accuracy: 0.9997 - val loss: 0.1561 - val accuracy: 0.9873
Epoch 18/25
accuracy: 0.9995 - val loss: 0.1704 - val accuracy: 0.9842
Epoch 19/25
accuracy: 0.9992 - val loss: 0.1624 - val accuracy: 0.9863
Epoch 20/25
accuracy: 0.9997 - val_loss: 0.1580 - val_accuracy: 0.9863
Epoch 21/25
accuracy: 0.9997 - val loss: 0.1654 - val accuracy: 0.9852
Epoch 22/25
accuracy: 0.9995 - val_loss: 0.1918 - val_accuracy: 0.9863
Epoch 23/25
accuracy: 0.9997 - val_loss: 0.2004 - val_accuracy: 0.9852
Epoch 24/25
accuracy: 0.9997 - val loss: 0.1895 - val accuracy: 0.9831
Epoch 25/25
accuracy: 0.9997 - val_loss: 0.1820 - val_accuracy: 0.9852
<keras.callbacks.History at 0x7ff68a3bcf10>
```

```
model.save("AI Spam Identifier")
WARNING:absl:Function `_wrapped_model` contains input name(s) InputLayer with
unsupported characters which will be renamed to inputlayer in the SavedModel.
WARNING:absl:Found untraced functions such as lstm_cell_layer_call_fn,
1stm cell layer call and return conditional losses while saving (showing 2 of
2). These functions will not be directly callable after loading.
test sequences = tok.texts to sequences(X test)
test sequences matrix = sequence.pad sequences(test sequences, maxlen=max len)
accuracy = model.evaluate(test sequences matrix,Y test)
print('Accuracy: {:0.3f}'.format(accuracy[1]))
27/27 [============== ] - 1s 21ms/step - loss: 0.1908 -
accuracy: 0.9833
Accuracy: 0.983
y_pred = model.predict(test_sequences_matrix)
print(y pred[25:40].round(3))
OUTPUT:
27/27 [======== ] - 1s 22ms/step
[[1.
[1.
 [0.
 [0.
 [1.
 [1.
 [0.
 [0.
 [0.
 [0.
 [0.
 [1.
 [0.001]
 [0.
[0.
      11
print(Y_test[25:40])
OUTPUT:
[[1]
[1]
[0]
[0]
[1]
[1]
 [0]
[0]
```

[0] [0] [0] [1] [0] [0] [0]]