ASSIGNMENT 4

Team ID:PNT2022TMID52302

Project Name: Gas Leakage monitoring & Alerting system for Industries

Submitted by **ATUL JOSHI F** (963519106013)

QUESTION:

Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events.

Upload document with wokwi share link and images of IBM cloud

Solution Code:

```
#include<WiFi.h>
#include<PubSubClient.h>
voidcallback(char* subscribetopic, byte* payload, unsignedintpayloadLength);
#define ORG "pjny99"//IBM ORGANITION ID
#define DEVICE TYPE "UltrasonicSensor"
#define DEVICE_ID "01151122"
#define TOKEN "LRGUi+TSM?4HjrNAfo"//Token
String data3;
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
charpublishTopic[] = "iot-2/evt/Data/fmt/json";
charsubscribetopic[] = "iot-2/cmd/test/fmt/String";
charauthMethod[] = "use-token-auth";
char token[] = TOKEN;
charclientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClientwifiClient;
PubSubClientclient(server, 1883, callback ,wifiClient);
constinttrigPin = 5;
constintechoPin = 18;
#define SOUND SPEED 0.034
long duration;
float distance;
voidsetup()
 {
   Serial.begin(115200);
    pinMode(trigPin, OUTPUT);
```

```
pinMode(echoPin, INPUT);
    wificonnect();
    mqttconnect();
    }
voidloop()
 {
    digitalWrite(trigPin, LOW);
    delayMicroseconds(2);
    digitalWrite(trigPin, HIGH);
    delayMicroseconds(10);
    digitalWrite(trigPin, LOW);
    duration = pulseIn(echoPin, HIGH);
    distance = duration * SOUND_SPEED/2;
    Serial.print("Distance (cm): ");
    Serial.println(distance);
    if(distance<100) {</pre>
      Serial.println("ALERT!!");
      delay(1000);
      PublishData(distance);
      delay(1000);
      if (!client.loop()) {
        mqttconnect();
      }
    delay(1000);
voidPublishData(floatdist)
{
  mqttconnect();
  String payload = "{\"Distance\":";
  payload += dist;
  payload += ",\"ALERT!!\":""\"Distance less than 100cms\"";
  payload += "}";
  Serial.print("Sending payload: ");
  Serial.println(payload);
  if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish ok");
    } else {
    Serial.println("Publish failed");
    }
voidmqttconnect()
  if (!client.connected()) {
    Serial.print("Reconnecting client to ");
```

```
Serial.println(server);
    while (!!!client.connect(clientId, authMethod, token)) {
      Serial.print("."); delay(500);
      }
    initManagedDevice();
    Serial.println();
    }
  }
voidwificonnect()
  Serial.println();
  Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);
 while (WiFi.status() != WL CONNECTED) {
    delay(500); Serial.print(".");
    }
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
  }
voidinitManagedDevice()
  if (client.subscribe(subscribetopic)) {
    Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
    } else {
    Serial.println("subscribe to cmd FAILED");
  }
voidcallback(char* subscribetopic, byte* payload, unsignedintpayloadLength)
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
  for (inti = 0; i<payloadLength; i++) {</pre>
    Serial.print((char)payload[i]);
    data3 += (char)payload[i];
  Serial.println("data: "+ data3);
  data3="";
}
```

OUTPUT:



