EMERGING METHODS FOR EARLY DETECTION OF FOREST FIRES

MODEL BUILDING

SAVE THE MODEL

Date	17 November 2022
Team ID	PNT2022TMID52343
Project Name	Emerging Methods for Early Detection of Forest Fires

Importing The ImageDataGenerator Library

import keras

from keras.preprocessing.image import ImageDataGenerator

Define the parameters/arguments for ImageDataGenerator class

train_datagen=ImageDataGenerator(rescale=1./255,shear_range=0.2,rot ati on_range=180,zoom_range=0.2, horizontal_flip=True) test_datagen=ImageDataGenerator(rescale=1./255)

Applying ImageDataGenerator functionality to trainset

x_train=train_datagen.flow_from_directory(r'/content/drive/MyDriv e/ Dataset/train_set',target_size=(128,128),batch_size=32, class_mode='binary')

Found 436 images belonging to 2 classes.

Applying ImageDataGenerator functionality to testset

x_test=test_datagen.flow_from_directory(r'/content/drive/MyDrive / Dataset/test_set',target_size=(128,128),batch_size=32, class_mode='binary')

Found 121 images belonging to 2 classes.

Import model building libraries

```
#To define Linear initialisation import Sequential
from keras.models import Sequential
#To add layers import Dense
from keras.layers import Dense
#To create Convolution kernel import Convolution2D
from keras.layers import Convolution2D
#import Maxpooling layer
from keras.layers import MaxPooling2D
#import flatten layer
from keras.layers import Flatten
import warnings
warnings.filterwarnings('ignore')
```

Initializing the model

```
model=Sequential()

Add CNN Layer

model.add(Convolution2D(32,
(3,3),input_shape=(128,128,3),activation='relu'))

#add maxpooling layer

model.add(MaxPooling2D(pool_size=(2,2)))

#add flatten layer

model.add(Flatten())

Add Hidden Layer

#add hidden layer
```

model.add(Dense(150,activation='relu'))

```
#add output layer
model.add(Dense(1,activation='sigmoid')
Configure the learning process
model.compile(loss='binary crossentropy',optimizer="adam",metrics=[
"ac curacy"])
Train the model
model.fit generator(x train, steps per epoch=14, epochs=10, validation
da ta=x test, validation steps=4)
Epoch 1/10
14/14 [======] - 97s 7s/step - loss:
1.3060 -
accuracy: 0.7775 - val loss: 0.5513 - val accuracy: 0.8512
Epoch 2/10
14/14 [======] - 26s 2s/step - loss:
0.3178 -
accuracy: 0.8807 - val loss: 0.1299 - val accuracy: 0.9421
Epoch 3/10
14/14 [======] - 26s 2s/step - loss:
0.2226 -
accuracy: 0.9106 - val loss: 0.1311 - val accuracy: 0.9421
Epoch 4/10
14/14 [======] - 31s 2s/step - loss:
0.1836 -
accuracy: 0.9174 - val loss: 0.1129 - val accuracy: 0.9339
Epoch 5/10
14/14 [======] - 30s 2s/step - loss:
0.1675 -
accuracy: 0.9243 - val loss: 0.0925 - val_accuracy: 0.9669
Epoch 6/10
14/14 [=======] - 26s 2s/step - loss:
0 1884 -
```

```
accuracy: 0.9289 - val loss: 0.1287 - val accuracy: 0.9339
Epoch 7/10
14/14 [======] - 28s 2s/step - loss:
0.1724 -
accuracy: 0.9335 - val loss: 0.0926 - val accuracy: 0.9752
Epoch 8/10
14/14 [=======] - 26s 2s/step - loss:
0.1510 -
accuracy: 0.9404 - val loss: 0.0757 - val accuracy: 0.9752
Epoch 9/10
2s/step - loss:0.173
14/14
                                0.9835 Epoch 10/10
=====] - 26s accuracy: 0.9174 - <sup>2</sup>
val loss: 0.0537 - val accuracy:
2s/step - loss:0.154
14/14
=====] - 26s accuracy: 0.9312 -
val loss: 0.0573 - val accuracy:
0.9835 < keras.callbacks. History at
0x7f05d66a9c90>
Save The Model
model.save("forest1.h5")
```

6-