Assignment -1

Team ID: PNT2022TMID52309

Team Member : Anusha R

Objective:

Build a smart home in Tinkercad with 2 sensors, a Led, buzzer

Code:

```
#include <Servo.h>


int output1Value = 0;
int sen1Value = 0;
int sen2Value = 0;
int constgas_sensor = A1;
int const LDR = A0;
int limit = 400;


long readUltrasonicDistance(int triggerPin, int echoPin)
{
pinMode(triggerPin, OUTPUT);  // Clear the trigger
digitalWrite(triggerPin, LOW);
delayMicroseconds(2);
// Sets the trigger pin to HIGH state for 10 microseconds
digitalWrite(triggerPin, HIGH);
delayMicroseconds(10);
digitalWrite(triggerPin, LOW);
pinMode(echoPin, INPUT);
  // Reads the echo pin, and returns the sound wave travel time in microseconds
  return pulseIn(echoPin, HIGH);
```

```
}

Servo servo_7;

void setup()
{
Serial.begin(9600);
pinMode(A0, INPUT);
pinMode(A1,INPUT);
pinMode(13, OUTPUT);
  servo_7.attach(7, 500, 2500);

pinMode(8,OUTPUT);
pinMode(9, INPUT);
pinMode(10, OUTPUT);
pinMode(4, OUTPUT);
pinMode(3, OUTPUT);

}

void loop()
{

    //------light intensity control------//
//-------------------------------------------------------------
   int val1 = analogRead(LDR);
  if (val1 > 500)
    {
    digitalWrite(13, LOW);
Serial.print("Bulb ON = ");
```

```
Serial.print(val1);
    }
  else
    {
    digitalWrite(13, HIGH);
Serial.print("Bulb OFF = ");
Serial.print(val1);
    }

//-------------------------------------------------------------
       //------ light & fan control --------//
//-------------------------------------------------------------
  sen2Value = digitalRead(9);
  if (sen2Value == 0)
    {
    digitalWrite(10, LOW);
    digitalWrite(4, HIGH);
    digitalWrite(3, LOW);
Serial.print("     || NO Motion Detected    " );
    }

  if (sen2Value == 1)
    {
    digitalWrite(10, HIGH);
delay(5000);
    digitalWrite(4, LOW);
    digitalWrite(3, HIGH);
Serial.print("        || Motion Detected!      " );
    }
```

```
//-------------------------------------------------------------
      // ------- Gas Sensor --------//
//-------------------------------------------------------------
int val = analogRead(gas_sensor);
Serial.print("|| Gas Sensor Value = ");
Serial.print(val);
//val = map(val, 300, 750, 0, 100);
  if (val> limit)
    {
    tone(8, 650);
    }
    delay(300);
    noTone(8);

 //-------------------------------------------------------------
     //-------  servo motor  ---------//
 //-------------------------------------------------------------
  sen1Value = 0.01723 * readUltrasonicDistance(6, 6);

  if (sen1Value < 100)
    {
    servo_7.write(90);
Serial.print("       || Door Open!  ; Distance = ");
Serial.print(sen1Value);
Serial.print("\n");

    }
  else
    {
```

```
    servo_7.write(0);
Serial.print("       || Door Closed! ; Distance =  ");
Serial.print(sen1Value);
Serial.print("\n");
  }
delay(10);
}
```