Assignment-IV

Fertilizer recommendation system for disease prediction

Date	26 October 2022
Student name	Aarthi K
Student roll no	814719106002
Maximum marks	2 marks

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from tensorflow.keras.models import Model
from tensorflow.keras.layers import LSTM, Activation, Dense, Dropout, Input,
Embedding
from tensorflow.keras.optimizers import RMSprop
from tensorflow.keras.preprocessing.text import Tokenizer
from tensorflow.keras.preprocessing import sequence
from tensorflow.keras.utils import to_categorical
from tensorflow.keras.callbacks import EarlyStopping
%matplotlib inline
import csv
with open('/spam.csv', 'r') as csvfile:
  reader = csv.reader(csvfile)
df = pd.read_csv(r'/spam.csv',encoding='latin-1')
df.head()
    v1
                                                         v2 Unnamed: 2 \
0
       Go until jurong point, crazy.. Available only ...
    ham
                                                                  NaN
                             Ok lar... Joking wif u oni...
1
    ham
                                                                  NaN
2 spam Free entry in 2 a wkly comp to win FA Cup fina...
                                                                  NaN
3
    ham U dun say so early hor... U c already then say...
                                                                   NaN
    ham Nah I don't think he goes to usf, he lives aro...
                                                                  NaN
  Unnamed: 3 Unnamed: 4
        NaN
                    NaN
         NaN
                    NaN
```


```
2
         NaN
                    NaN
3
         NaN
                    NaN
         NaN
                    NaN
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
df.info()
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
    Column Non-Null Count Dtype
 0
     v1
             5572 non-null
                             object
 1
    v2
             5572 non-null
                             object
dtypes: object(2)
memory usage: 87.2+ KB
```

sns.countplot(df.v1)

/usr/local/lib/python3.7/dist-packages/seaborn/_decorators.py:43: FutureWarning: Pass the following variable as a keyword arg: x. From version 0.12, the only valid positional argument will be `data`, and passing other arguments without an explicit keyword will result in an error or misinterpretation.

FutureWarning

<matplotlib.axes._subplots.AxesSubplot at 0x7f5197dac250>



```
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit transform(Y)
Y = Y.reshape(-1,1)
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.20)
max\_words = 1000
max len = 150
tok = Tokenizer(num words=max words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = sequence.pad_sequences(sequences,maxlen=max_len)
def RNN():
    inputs = Input(name='inputs',shape=[max len])
    layer = Embedding(max_words,50,input_length=max_len)(inputs)
    layer = LSTM(128)(layer)
    layer = Dense(256,name='FC1')(layer)
    layer = Activation('relu')(layer)
    layer = Dropout(0.5)(layer)
    layer = Dense(1,name='out_layer')(layer)
    layer = Activation('tanh')(layer)
    model = Model(inputs=inputs,outputs=layer)
    return model
model = RNN()
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accura
cy','mse','mae'])
```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 128)	91648
FC1 (Dense)	(None, 256)	33024
activation (Activation)	(None, 256)	0
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257

```
activation 1 (Activation) (None, 1)
                                                    0
Total params: 174,929
Trainable params: 174,929
Non-trainable params: 0
model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,
validation split=0.2, callbacks=[EarlyStopping(monitor='val loss', min delta=0.
0001)])
Epoch 1/10
28/28 [=========== ] - 17s 486ms/step - loss: 0.2960 -
accuracy: 0.8819 - mse: 0.0821 - mae: 0.1563 - val loss: 0.1341 -
val_accuracy: 0.9675 - val_mse: 0.0344 - val_mae: 0.1237
Epoch 2/10
28/28 [============== ] - 13s 462ms/step - loss: 0.1149 -
accuracy: 0.9764 - mse: 0.0381 - mae: 0.1538 - val loss: 0.1321 -
val accuracy: 0.9798 - val mse: 0.0437 - val mae: 0.1695
<keras.callbacks.History at 0x7f5193192590>
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = sequence.pad_sequences(test_sequences,maxlen=max_len)
accr = model.evaluate(test sequences matrix,Y test)
35/35 [============ ] - 3s 78ms/step - loss: 0.1590 -
accuracy: 0.9812 - mse: 0.0451 - mae: 0.1733
print('Test set\n Loss: {:0.3f}\n Accuracy:
{:0.3f}'.format(accr[0],accr[1]))
Test set
 Loss: 0.159
 Accuracy: 0.981
model.save("./assign4model.h5")
from tensorflow.keras.models import load model
m2 = load model("./assign4model.h5")
m2.evaluate(test_sequences_matrix,Y_test)
35/35 [============ ] - 3s 68ms/step - loss: 0.1590 -
accuracy: 0.9812 - mse: 0.0451 - mae: 0.1733
[0.1589982509613037,
0.9811659455299377,
```

- 0.04506031796336174,
- 0.17333826422691345]