
IBM - NALLAIYA THIRAN PROJECT ASSIGNMENT-1 : SMART HOME

K.MOHAMED NOUFHAL ABBAS

2019503534

CIRCUIT DIAGRAM:



SOURCE CODE:

```
// C++ code


//
int t=2;
int e=3;
void setup()
{
    Serial.begin(9600);
```

```
pinMode(t,OUTPUT);
 pinMode(e,INPUT);
 pinMode(12,OUTPUT);
}
void loop()
{
 //ultrasonic sensor
 digitalWrite(t,LOW);
 digitalWrite(t,HIGH);
 delayMicroseconds(10);
 digitalWrite(t,LOW);
 float dur=pulseIn(e,HIGH);
 float dis=(dur*0.0343)/2;
 Serial.print("Distance is: ");
 Serial.println(dis);
  //LED ON
 if(dis>=60)//(in terms of centimeter)
  digitalWrite(8,HIGH);
  digitalWrite(7,HIGH);
 //Buzzer For ultrasonic Sensor
 if(dis>=60)
 for(int i=0; i<=5; i=i+1)
 tone(12,i);
 delay(1000);
```

```
noTone(12);
delay(1000);
 //Temperate Sensor
double a= analogRead(A0);
double t=(((a/1024)*5)-0.5)*100;
Serial.print("Temp Value: ");
Serial.println(t);
delay(1000);
//LED ON
if(t>=20)//(in terms of celsius)
 digitalWrite(8,HIGH);
 digitalWrite(7,HIGH);
//Buzzer for Temperature Sensor
if(t>=20)
for(int i=0; i<=5; i=i+1)
tone(12,i);
delay(1000);
noTone(12);
delay(1000);
//LED OFF
```

```
if(t<20)
{
    digitalWrite(8,LOW);
    digitalWrite(7,LOW);
}</pre>
```

OUTPUT (SERIAL MONITOR):



TINKERCAD LINK:

https://www.tinkercad.com/things/2zhpSa6w0em-terrific-jaban-jaagub/editel?sharecode=ooLJV6X_pehlyNOeMcca_noP1N8VxNZ2gezrcMH8bv
U