

EARLY DETECTION OF FOREST FIRE USING DEEP LEARNING

MODEL BUILDING

INITIALIZING THE MODEL

| | |
|--------------|--|
| Team ID | PNT2022TMID38456 |
| Project Name | Project-Early detection of forest fire using deep learning |

INITIALILIZING THE MODEL:

keras has 2 ways to define a neural network:

- Sequential
- Function API

The Sequential class is used to define linear initializations of network layers which then, collectively, constitute a model. In our example below, we will use the Sequential constructor to create a model, which will then have layers added to it using the add () method.

Now, will initialize our model.

Untitled8.ipynb - Colaboratory

▾ Importing Keras libraries

```
import keras
```

▾ Importing ImageDataGenerator from Keras

```
from keras.preprocessing.image import ImageDataGenerator
```

▾ Importing Keras libraries

```
[1] import keras
```

▾ Importing ImageDataGenerator from Keras

```
[13] from matplotlib import pyplot as plt
      from keras.preprocessing.image import ImageDataGenerator
```


▾ Defining the Parameters

```
train_datagen=ImageDataGenerator(rescale=1./255, shear_range=0.2, rotation_range=180, zoom_range=0.2, horizontal_flip=True)
test_datagen=ImageDataGenerator(rescale=1./255)
```

```
<keras.preprocessing.image.ImageDataGenerator at 0x7fb7448ac110>
```

APPLYING ImageDataGenerator to train dataset:

plyflow_from_directory ()methodfor Train folder.



The screenshot shows a Jupyter Notebook with two cells. The first cell, titled 'Defining the Parameters', contains code to create ImageDataGenerator objects for training and testing. The second cell, titled 'Applying ImageDataGenerator functionality to train dataset', contains code to mount Google Drive and use the flow_from_directory method to load training data.

```
[11] train_datagen=ImageDataGenerator(rescale=1./255, shear_range=0.2, rotation_range=180, zoom_range=0.2, horizontal_flip=True)
test_datagen=ImageDataGenerator(rescale=1./255)

<keras.preprocessing.image.ImageDataGenerator at 0x7fb7448ac110>
```

```
[10] from google.colab import drive
drive.mount('/content/drive')


Drive already mounted at /content/drive; to attempt to forcibly remount, call drive.mount("/content/drive", force_remount=True).
```

```
[17] x_train=train_datagen.flow_from_directory('/content/drive/MyDrive/IBM PROJECT/dataset/DATA SET/archive/Dataset/Dataset/train_set',target_size=(128,128),batch_size=32,class_mode='binary')

Found 436 images belonging to 2 classes.
```

APPLYING ImageDataGenerator to test dataset:

Applying the flow_from_directory () methodfortest folder.



The screenshot shows a Jupyter Notebook with one cell titled 'Applying ImageDataGenerator functionality to test dataset'. It contains code to use the flow_from_directory method to load testing data from Google Drive.

```
x_test=test_datagen.flow_from_directory('/content/drive/MyDrive/IBM PROJECT/dataset/DATA SET/archive/Dataset/Dataset/test_set',target_size=(128,128),batch_size=32,class_mode='binary')

Found 121 images belonging to 2 classes.
```

IMPORTING MODEL BUILDING LIBRARIES:

Main code - Colaboratory

▾ Importing Model Building Libraries

```
#to define the linear Initialisation import sequential
from keras.models import Sequential
#to add layers import Dense
from keras.layers import Dense
#to create Convolutional kernel import convolution2D
from keras.layers import Convolution2D
#import Maxpooling layer
from keras.layers import MaxPooling2D
#import flatten layer
from keras.layers import Flatten
import warnings
warnings.filterwarnings('ignore')
```

INITIALIZING THE MODEL:

▼ Initializing the model

```
model=Sequential()
```