

PROJECT DESIGN PHASE 1

PROPOSED SOLUTION:

DATE	1 OCT 2022
TEAM ID	PNT2022TMID47272
TITLE	IoT Based Safety Gadget For Child Safety Monitoring & Notification
TEAM LEAD	MAHESH K S
TEAM MEMBERS	SRIDHAR G KALAIMUKILAN S ENIYAVAN M
MAXIMUM MARKS	2

Solution:

A. Safety Gadget

It consists of inbuilt Wi-Fi, GSM, GPS and Bluetooth modules. The link it one board is similar to the Arduino board and it is termed as all-in-one prototyping board for safety and IoT devices. The link it one is a robust development board for the hardware and also used for industrial applications. Different components such as temperature sensor, heartbeat sensor, panic button, contact switch are connected to the link it ONE board along with built in GSM, GPS modules. Safety gadget consists of BEACON and BLE packet is transmitted through it, this packet is

received by binding gadget which has BLE receiver module, the packet usually contains information such as identification number, signal strength etc. Temperature is one of the most commonly measured variables. For measuring body temperature of the child DS18B20 temperature sensor is used. The heartbeat sensor is used in the proposed system for measuring the pulse rate. There is a heartbeat/pulse sensor which is combined to simple optical heart rate sensor with amplification and nullification circuitry making it is fast and easy to get reliable pulse reading. The GSM/GPRS block is activated with a SIM card on the board. They mainly differ based on bandwidth and RF carrier frequency. GSM network consists of mobile station, base station subsystem network and operation subsystem. The GPS module is provided for identifying the location of the child. GPS module receives the signals from satellites. The latitude and longitude of the location can be identified by the GPS module. The device sends the monitored parameters data such as temperature and pulse rate to cloud. If any abnormalities occurs in temperature or pulse rate readings, a SMS and call triggers to the parent/caretaker mobile phone immediately and also updated to the mobile app only for the registries mobile no. We can use mobile application, cloud and database as the back end of storing and retrieving information and also a device for monitoring. Fig. 1. Block diagram of smart gadget

B. BLE Listener device

Figure 2 shows the BLE Listener device is the device which is used to satisfy this feature along with safety gadget and parental phone. This gadget is also used to monitor safety gadget within a

bounded area using wireless technology as follows, this feature of binding gadget is designed to work independently without phone network signal/internet so that safety gadget can even be under monitoring when it reaches remote areas where communication signals is not reachable like forest. Safety gadget consists of BEACON and BLE packet is transmitted through it, this packet is received by binding gadget which has BLE (Bluetooth Low Energy) receiver module, the packet usually contains information such as identification number, signal strength etc. Whenever the packet is received it checks for all the above information in the receiver device. As the distance between safety gadget and binding gadget increases, the signal strength decreases. Once the safety gadget is moving out of threshold distance from the binding gadget then an alert is provided on binding gadget which will be used by parent/guardian.