Student's Name	Princy S
Registration Number	960519104058
Assignment Number	04

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
```

▼ READ DATASET AND PRE PROCESSING

Y = Y.reshape(-1,1)

```
df = pd.read_csv('/content/spam.csv',delimiter=',',encoding='latin-1')
df.head()
```

v	1		v2	Unnamed: 2	Unnamed:	Unnamed:
0 har	m Go	until jurong point, cra	azy Available only	NaN	NaN	NaN
1 har	m	Ok lar	. Joking wif u oni	NaN	NaN	NaN
2 spar	m Fre	Free entry in 2 a wkly comp to win FA Cup fina		NaN	NaN	NaN
-	U	dun sav so earlv hor	U c alreadv then		** **	
info()		: 2', 'Unnamed:	3', 'Unnamed: 4	l'],axis=1,	inplace=Tru	e)
info() <class co<="" data="" rangeir="" td=""><td>'panda dex: 5 olumns olumn</td><td>as.core.frame.Da 572 entries, 0 (total 2 column Non-Null Count</td><td>taFrame'> to 5571 as): Dtype</td><td>l'],axis=1,</td><td>inplace=Tru</td><td>e)</td></class>	'panda dex: 5 olumns olumn	as.core.frame.Da 572 entries, 0 (total 2 column Non-Null Count	taFrame'> to 5571 as): Dtype	l'],axis=1,	inplace=Tru	e)
info() <class #="" 0="" 1="" co="" data="" dtypes:<="" rangeir="" td="" v1="" v2=""><td>'pandandex: 5</td><td>s.core.frame.Da 572 entries, 0 (total 2 column Non-Null Count </td><td>taFrame'> to 5571 s): Dtype object</td><td>i'],axis=1,</td><td>inplace=Tru</td><td>e)</td></class>	'pandandex: 5	s.core.frame.Da 572 entries, 0 (total 2 column Non-Null Count 	taFrame'> to 5571 s): Dtype object	i'],axis=1,	inplace=Tru	e)
info() <class #="" 0="" 1="" co="" data="" dtypes:<="" rangeir="" td="" v1="" v2=""><td>'pandandex: 5</td><td>s.core.frame.Da 572 entries, 0 (total 2 column Non-Null Count </td><td>taFrame'> to 5571 s): Dtype object</td><td>i'],axis=1,</td><td>inplace=Tru</td><td>e)</td></class>	'pandandex: 5	s.core.frame.Da 572 entries, 0 (total 2 column Non-Null Count 	taFrame'> to 5571 s): Dtype object	i'],axis=1,	inplace=Tru	e)
class RangeIr Data cc # Cc 0 vl 1 v2 dtypes: memory	'pandandex: 5	s.core.frame.Da 572 entries, 0 (total 2 column Non-Null Count 	taFrame'> to 5571 s): Dtype object	i'],axis=1,	inplace=Tru	e)
info() <class #="" 0="" 1="" co="" data="" dtypes:="" memory<="" rangeir="" td="" v2="" vl=""><td>'pandadex: 5 blumns blumns blumn 'e c object usage:</td><td>s.core.frame.Da 572 entries, 0 (total 2 column Non-Null Count </td><td>taFrame'> to 5571 s): Dtype object</td><td>i'],axis=1,</td><td>inplace=Tru</td><td>e)</td></class>	'pandadex: 5 blumns blumns blumn 'e c object usage:	s.core.frame.Da 572 entries, 0 (total 2 column Non-Null Count 	taFrame'> to 5571 s): Dtype object	i'],axis=1,	inplace=Tru	e)

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)

max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

Create Model and Add Layers (LSTM, Dense-(Hidden Layers), Output)

```
inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)
model.summary()
```

Model: "model"

Layer (type)	Output Shape	Param #	
inputs (InputLayer)	[(None, 150)]	0	
embedding (Embedding)	(None, 150, 50)	50000	
lstm (LSTM)	(None, 64)	29440	
FC1 (Dense)	(None, 256)	16640	
activation (Activation)	(None, 256)	0	
dropout (Dropout)	(None, 256)	0	
out_layer (Dense)	(None, 1)	257	
activation_1 (Activation)	(None, 1)	0	

Total params: 96,337
Trainable params: 96,337
Non-trainable params: 0

Compile the Model

Train and Fit the Model

```
Epoch 1/10
Epoch 2/10
30/30 [=========== ] - 9s 301ms/step - loss: 0.0934 - accur-
Epoch 3/10
30/30 [============= ] - 10s 327ms/step - loss: 0.0395 - accu:
Epoch 4/10
30/30 [============ ] - 9s 317ms/step - loss: 0.0311 - accur-
Epoch 5/10
30/30 [===========] - 9s 294ms/step - loss: 0.0213 - accur-
Epoch 6/10
30/30 [============] - 9s 305ms/step - loss: 0.0167 - accur-
Epoch 7/10
30/30 [============= ] - 9s 316ms/step - loss: 0.0115 - accur-
Epoch 8/10
30/30 [============ ] - 9s 286ms/step - loss: 0.0081 - accur-
Epoch 9/10
30/30 [============] - 9s 310ms/step - loss: 0.0065 - accur-
Epoch 10/10
30/30 [===========] - 10s 346ms/step - loss: 0.0064 - accu:
<keras.callbacks.History at 0x7f03f70fe810>
```

- Save The Model

```
model.save('sms_classifier.h5')
```

Preprocessing the Test Dataset

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = pad_sequences(test_sequences,maxlen=max_len)
```

Testing the Model

print('Test set\n Loss: {:0.3f}\n Accuracy: {:0.3f}'.format(accr[0],accr[1]))

Test set Loss: 0.135 Accuracy: 0.982