

## Assignment -4

Team ID: PNT2022TMID34298

Date: 1 November 2022

### 1) Download the Dataset

In [4]:

```
from google.colab import drive
drive.mount('/content/gdrive')
```

Mounted at /content/gdrive

In [5]:

```
df = pd.read_csv('/content/gdrive/MyDrive/spam.csv', delimiter=',', encoding='latin-1')
df.head()
```

Out[5]:

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy.. Available only ...	NaN	NaN	NaN
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro...	NaN	NaN	NaN

### 2) Import required library

In [16]:

```
import pandas as pd
import tensorflow as tf
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
%matplotlib inline
```

### 3) Read dataset and do pre-processing

In [6]:

```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
 #   Column  Non-Null Count  Dtype
---  -
 0    v1      5572 non-null    object
 1    v2      5572 non-null    object
dtypes: object(2)
memory usage: 87.2+ KB
```

In [7]:


```
sns.countplot(df.v1)
plt.xlabel('Label')
plt.title('Number of ham and spam messages')
```

/usr/local/lib/python3.7/dist-packages/seaborn/\_decorators.py:43: FutureWarning: Pass the following variable as a keyword arg: x. From version 0.12, the only valid positional argument will be `data`, and passing other arguments without an explicit keyword will result in an error or misinterpretation.

FutureWarning

Out[7]:

Text(0.5, 1.0, 'Number of ham and spam messages')



#### 4) Create Model

In [8]:

```
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

In [9]:

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

In [17]:

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = tf.keras.utils.pad_sequences(sequences,maxlen=max_len)
```

## 5) Add Layers (LSTM, Dense-(Hidden Layers), Output)

In [18]:

```
def RNN():
    inputs = Input(name='inputs',shape=[max_len])
    layer = Embedding(max_words,50,input_length=max_len)(inputs)
    layer = LSTM(64)(layer)
    layer = Dense(256,name='FC1')(layer)
    layer = Activation('relu')(layer)
    layer = Dropout(0.5)(layer)
    layer = Dense(1,name='out_layer')(layer)
    layer = Activation('sigmoid')(layer)
    model = Model(inputs=inputs,outputs=layer)
    return model
```

## 6) Compile the Model

In [19]:

```
model = RNN()
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation (Activation)	(None, 256)	0
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
activation_1 (Activation)	(None, 1)	0

=====  
Total params: 96,337  
Trainable params: 96,337  
Non-trainable params: 0  
=====

## 7) Fit the Model

In [20]:

```
model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,
          validation_split=0.2,callbacks=[EarlyStopping(monitor='val_loss',min_delta=0.0001)])
```

Epoch 1/10  
30/30 [=====] - 12s 305ms/step - loss: 0.3157 - accuracy: 0.8762 - val\_loss: 0.1607 - val\_accuracy: 0.9747  
Epoch 2/10  
30/30 [=====] - 9s 285ms/step - loss: 0.0761 - accuracy: 0.9813 - val\_loss: 0.0772 - val\_accuracy: 0.9778

Out[20]:

<keras.callbacks.History at 0x7f853b80bd10>

## 8) Save and Test The Model

In [22]:

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = tf.keras.utils.pad_sequences(test_sequences,maxlen=max_len)
```

In [23]:

```
accr = model.evaluate(test_sequences_matrix,Y_test)
```

```
27/27 [=====] - 1s 39ms/step - loss: 0.0361 - accuracy: 0.9916
```

In [24]:

```
print('Test set\n Loss: {:.3f}\n Accuracy: {:.3f}'.format(accr[0],accr[1]))
```

```
Test set
Loss: 0.036
Accuracy: 0.992
```