```
"cells": [
 "cell type": "markdown",
 "metadata": {},
 "source": [
  "## Assignment 4 Solution"
},
 "cell type": "markdown",
 "metadata": {},
 "source": [
  "### Import necessary libraries"
 1
},
 "cell type": "code",
 "execution count": 2,
 "metadata": {},
 "outputs": [],
  "source": [
  "import pandas as pd\n",
   "import numpy as np\n",
  "from sklearn.model selection import train test split\n",
  "from sklearn.preprocessing import LabelEncoder\n",
  "from tensorflow.keras.models import Sequential\n",
   "from tensorflow.keras.layers import LSTM, Dense, Dropout, Embedding\n",
   "from tensorflow.keras.optimizers import RMSprop\n",
   "from tensorflow.keras.preprocessing.text import Tokenizer\n",
   "from tensorflow.keras.preprocessing import sequence"
},
 "cell type": "markdown",
 "metadata": {},
 "source": [
  "### Data Pre-Processing"
 ]
},
 "cell type": "code",
 "execution count": 3,
  "metadata": {},
  "outputs": [
    "data": {
     "text/html": [
      <div>\n",
      "<style scoped>\n",
           .dataframe tbody tr th:only-of-type {\n",
              vertical-align: middle; \n",
      "
           }\n",
      "\n",
           .dataframe tbody tr th {\n",
              vertical-align: top; \n",
           } \n",
```

```
"\n",
   .dataframe thead th \{\n'',
      text-align: right; \n",
   }\n",
"</style>\n",
"\n",
 <thead>\n",
   \n",
**
    \n",
**
    v1\n",
**
    v2\n",
"
    Unnamed: 2\n",
"
    Unnamed: 3\n",
**
    Unnamed: 4\n",
**
  \n",
 </thead>\n",
 \n",
**
  \n",
**
    0\n",
**
    ham\n",
"
    Go until jurong point, crazy.. Available only ...\n",
"
    NaN\n",
"
    NaN\n"
"
    NaN\n",
"
   \n",
**
   \n",
**
    1\n",
11
    ham\n",
**
    Ok lar... Joking wif u oni...
**
    NaN\n",
**
    NaN\n",
**
    NaN\n",
"
   \n",
**
   \n",
11
    2\n",
"
    spam\n",
    Free entry in 2 a wkly comp to win FA Cup fina...\n",
**
    NaN\n",
**
    NaN\n",
**
    NaN\n",
"
   \n",
**
   \n",
"
    3\n",
    ham\n",
"
    U dun say so early hor... U c already then say...\n",
**
    NaN\n",
    NaN\n",
**
    NaN\n",
"
   \n",
**
   \n",
    4\n",
"
    ham\n",
**
    Nah I don't think he goes to usf, he lives aro...\n",
    NaN\n",
"
   NaN\n",
**
   NaN\n",
   \n",
```

```
" \n",
      "\n",
      "</div>"
     ],
      "text/plain": [
                                                              v2 Unnamed: 2
            v1
\\\n",
                Go until jurong point, crazy.. Available only ...
                                                                        NaN
\n",
      "1
           ham
                                    Ok lar... Joking wif u oni...
                                                                        NaN
\n",
      "2
          spam
               Free entry in 2 a wkly comp to win FA Cup fina...
                                                                        NaN
\n'',
      "3
           ham U dun say so early hor... U c already then say...
                                                                        NaN
n",
      '' 4
           ham Nah I don't think he goes to usf, he lives aro...
                                                                        NaN
\n",
      "\n",
      " Unnamed: 3 Unnamed: 4 \n",
      "0
                          NaN \n",
                NaN
      "1
                NaN
                           NaN \n",
      "2
                           NaN \n",
                NaN
      "3
                           NaN \n",
                NaN
                          NaN "
      '' 4
                NaN
     ]
    "execution count": 3,
     "metadata": {},
     "output_type": "execute result"
   }
  ],
   "source": [
   "df = pd.read csv('spam.csv', delimiter=',', encoding='latin-1')\n",
   "df.head()"
  ]
 },
  "cell type": "code",
  "execution count": 4,
   "metadata": {},
   "outputs": [
    "name": "stdout",
     "output type": "stream",
     "text": [
     "<class 'pandas.core.frame.DataFrame'>\n",
     "RangeIndex: 5572 entries, 0 to 5571\n",
     "Data columns (total 2 columns):\n",
     " # Column Non-Null Count Dtype \n",
     "--- \n",
     " 0 v1
                   5572 non-null object\n",
     " 1 v2
                   5572 non-null object\n",
     "dtypes: object(2)\n",
     "memory usage: 87.2+ KB\n"
    1
   }
   ],
```

```
"source": [
    "df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'], axis=1,
inplace=True) \n",
    "df.info()"
   ]
 },
  {
   "cell type": "code",
   "execution count": 5,
   "metadata": {},
   "outputs": [],
   "source": [
   "X = df.v2\n",
    "Y = df.v1\n",
    "encoder = LabelEncoder()\n",
    "Y = encoder.fit transform(Y)\n",
    "Y = Y.reshape(-1,1)"
   ]
 },
   "cell type": "code",
   "execution count": 6,
   "metadata": {},
   "outputs": [],
   "source": [
   "X train, X test, y train, y test = train test split(X, Y,
test size=0.2)"
  ]
 },
  "cell type": "code",
   "execution_count": 7,
   "metadata": {},
   "outputs": [],
   "source": [
    "tokenizer = Tokenizer(num words=2000, lower=True)\n",
    "tokenizer.fit on texts(X \overline{\text{train}})\n",
    "sequences = tokenizer.texts to sequences(X train)\n",
    "X train = sequence.pad sequences(sequences, maxlen=200)"
 },
  "cell type": "markdown",
   "metadata": {},
   "source": [
   "### Create model"
 },
  "cell type": "code",
   "execution count": 8,
   "metadata": {},
   "outputs": [],
   "source": [
   "model = Sequential()"
   1
 },
```

```
"cell type": "markdown",
 "metadata": {},
 "source": [
 "### Add layers"
},
"cell type": "code",
 "execution count": 9,
"metadata": {},
 "outputs": [],
"source": [
 "model.add(Embedding(2000, 50, input length=200))\n",
 "model.add(LSTM(64))\n",
 "model.add(Dense(256, activation=\"relu\"))\n",
 "model.add(Dropout(0.5))\n",
 "model.add(Dense(1,activation=\"sigmoid\"))"
]
},
"cell type": "code",
 "execution count": 10,
 "metadata": {},
 "outputs": [
  "name": "stdout",
  "output type": "stream",
  "text": [
   "Model: \"sequential\"\n",
                                                                 \n",
   " Layer (type)
                               Output Shape
                                                       Param #
                                                                 \n",
   "-----\n",
   " embedding (Embedding)
                               (None, 200, 50)
                                                       100000
                                                                 \n",
   " lstm (LSTM)
                               (None, 64)
                                                       29440
                                                                 \n",
                                                                 \n'',
   " dense (Dense)
                               (None, 256)
                                                       16640
                                                                 \n'',
                                                                 \n",
   " dropout (Dropout)
                               (None, 256)
                                                                 \n'',
                                                                 \n",
   " dense_1 (Dense)
                                                       257
                                                                \n",
                               (None, 1)
                                                                 \n",
   "-----\n",
   "Total params: 146,337\n",
   "Trainable params: 146,337\n",
   "Non-trainable params: 0\n",
                                                                 \n"
 }
],
 "source": [
 "model.summary()"
1
},
"cell type": "markdown",
```

```
"metadata": {},
  "source": [
   "### Compile the model"
  ]
 },
  "cell type": "code",
  "execution count": 11,
  "metadata": {},
  "outputs": [],
  "source": [
   "model.compile(loss='binary crossentropy', optimizer=RMSprop(),
metrics=['accuracy'])"
 },
  "cell type": "markdown",
  "metadata": {},
  "source": [
  "### Fit the model"
  1
 },
  "cell type": "code",
  "execution count": 12,
  "metadata": {},
  "outputs": [
    "name": "stdout",
    "output type": "stream",
    "text": [
     "Epoch 1/10\n",
     "28/28 [============= ] - 4s 49ms/step - loss: 0.3426 -
accuracy: 0.8738 - val loss: 0.1774 - val accuracy: 0.9585\n",
     "Epoch 2/10\n",
     "28/28 [=============== ] - 1s 27ms/step - loss: 0.1026 -
accuracy: 0.9745 - val loss: 0.0607 - val accuracy: 0.9809\n",
     "Epoch 3/10\n",
     "28/28 [=============== ] - 1s 27ms/step - loss: 0.0417 -
accuracy: 0.9882 - val loss: 0.0606 - val accuracy: 0.9832\n",
     "Epoch 4/10\n",
     "28/28 [============= ] - 1s 27ms/step - loss: 0.0253 -
accuracy: 0.9927 - val loss: 0.0579 - val accuracy: 0.9843\n",
     "Epoch 5/10\n",
     accuracy: 0.9947 - val loss: 0.0744 - val accuracy: 0.9865\n",
     "Epoch 6/10\n",
     "28/28 [==============] - 1s 28ms/step - loss: 0.0131 -
accuracy: 0.9961 - val loss: 0.0762 - val accuracy: 0.9865\n",
     "Epoch 7/10\n",
     "28/28 [=============== ] - 1s 26ms/step - loss: 0.0085 -
accuracy: 0.9969 - val loss: 0.1080 - val accuracy: 0.9854\n",
     "Epoch 8/10\n",
     accuracy: 0.9978 - val loss: 0.0998 - val accuracy: 0.9809\n",
     "Epoch 9/10\n",
```

```
"28/28 [============== ] - 1s 26ms/step - loss: 0.0053 -
accuracy: 0.9978 - val loss: 0.1187 - val accuracy: 0.9843\n",
      "Epoch 10/10\n",
      "28/28 [=============== ] - 1s 26ms/step - loss: 0.0031 -
accuracy: 0.9994 - val loss: 0.1409 - val accuracy: 0.9843\n"
    },
     "data": {
      "text/plain": [
      "<keras.callbacks.History at 0x1ecbb7a4ee0>"
     },
     "execution count": 12,
     "metadata": {},
     "output type": "execute result"
   ],
   "source": [
   "model.fit(X train, y train, batch size=128, epochs=10,
validation split=0.2)"
   ]
  },
   "cell type": "markdown",
   "metadata": {},
   "source": [
   "### Save the model"
  ]
  },
   "cell type": "code",
   "execution count": 13,
  "metadata": {},
   "outputs": [],
   "source": [
   "model.save(\"model.h5\")"
  1
  },
  "cell type": "markdown",
   "metadata": {},
   "source": [
    "### Test the model"
   ]
  },
   "cell type": "code",
   "execution count": 14,
   "metadata": {},
   "outputs": [],
   "source": [
   "test sequences = tokenizer.texts to sequences(X test)\n",
   "X test = sequence.pad sequences(test sequences, maxlen=200)"
  1
  },
  {
```

```
"cell type": "code",
   "execution count": 15,
   "metadata": {},
   "outputs": [
    "name": "stdout",
     "output type": "stream",
     "text": [
     "35/35 [============= ] - 0s 12ms/step - loss: 0.0825 -
accuracy: 0.9839\n"
    ]
    }
  ],
   "source": [
   "acc = model.evaluate(X test, y test)"
  },
   "cell type": "code",
   "execution count": 16,
   "metadata": {},
   "outputs": [],
   "source": [
   "def predict (message): \n",
        txt = tokenizer.texts to sequences(message) \n",
        txt = sequence.pad sequences(txt, maxlen=200) \n",
        preds = model.predict(txt) \n",
        if preds > 0.5:\n",
    **
            print(\"Spam\")\n",
        else:\n",
            print(\"Not Spam\")"
   ]
  },
   "cell type": "code",
   "execution count": 19,
   "metadata": {},
   "outputs": [
    "name": "stdout",
     "output type": "stream",
     "text": [
     "1/1 [======== ] - 0s 28ms/step\n",
      "Not Spam\n"
    ]
   }
   ],
   "source": [
    "predict([\"Sorry, I'll call after the meeting.\"])"
   ]
  },
   "cell type": "code",
   "execution count": 20,
   "metadata": {},
   "outputs": [
    {
```

```
"name": "stdout",
     "output type": "stream",
     "text": [
     "1/1 [======== ] - 0s 25ms/step\n",
     "Spam\n"
   }
  ],
  "source": [
   "predict([\"Congratulations!!! You won $50,000. Send message LUCKY100 to
XXXXXXXXX to recieve your prize.\"])"
 }
],
"metadata": {
 "kernelspec": {
  "display name": "Python 3.10.7 ('venv': venv)",
  "language": "python",
  "name": "python3"
 },
 "language info": {
  "codemirror mode": {
   "name": "ipython",
   "version": 3
  "file extension": ".py",
  "mimetype": "text/x-python",
  "name": "python",
  "nbconvert exporter": "python",
  "pygments lexer": "ipython3",
  "version": "3.10.7"
 } ,
 "orig nbformat": 4,
 "vscode": {
  "interpreter": {
   "hash":
"642c4c79e4b143d0da89805c64dad1e5ef21fdea6c19e5430701ee75c9149d19"
 }
"nbformat": 4,
"nbformat minor": 2
}
```