Delivery of Sprint-2

DATE	10 November 2022
TEAM ID	PNT2022TMID43558
PROJECT NAME	SMART WASTE MANAGEMENT FOR METROPOLITAN CITIES

Code for Data Transfer from Sensors

	#include <wifi.h> #include <pubsubclier #include="" 20,="" 4);<="" <liquidcrysta="" lcd(0x27,="" th=""><th></th><th>idCrystal_I2C</th><th>// library for wifi // library for MQTT</th><th></th></pubsubclier></wifi.h>		idCrystal_I2C	// library for wifi // library for MQTT	
	// cre	edentials of IE	BM Accounts	-	
	#define ORG "ktymlx" #define DEVICE_TYPE #define DEVICE_ID "09 #define TOKEN "Kame	"new" 9876"		// IBM organisation id // Device type mentioned in ibm watson iot platform // Device ID mentioned in ibm watson iot platform // Token	
//	, cu:	stomise abov	e values		
char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // server name char publishTopic[] = "iot-2/evt/data/fmt/json"; topic[] = "iot-2/cmd/led/fmt/String"; // cmd Represent type and command is test format of strings char authMethod[] = "useto auth"; // authentication method char token[] = TOKEN;					
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;			E_TYPE ":" DEVICE_ID;	//Client id	
	//				
WiFiClient wifiClient; PubSubClient client(server, 1883, wifiClient);			rifiClient);	// creating instance for wificlient	
	#define ECHO_PIN 12 #define TRIG_PIN 13 t dist;	float			
	void setup() { Serial.begin(115200); pinMode(LED_BUILTIN pinMode(TRIG_PIN, pinMode(ECHO_PIN, II //pir pin pinMode(4, IN	NPUT);	ОИТРИТ); ОИТРИТ);		
	//ledpins pinMode(23, OUTPUT); pinMode(2, OUTPUT); pinMode(4 OUTPUT); pinMode(15 OUTPUT);	4 <i>,</i>			

```
lcd.init(); lcd.backlight(); lcd.setCursor(1,
0); lcd.print(""); wifiConnect();
mqttConnect();
float readcmCM()
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2); digitalWrite(TRIG_PIN,
HIGH); delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW); int duration =
pulseIn(ECHO_PIN, HIGH); return
duration * 0.034 / 2;
void loop()
lcd.clear();
publishData(); delay(500);
if (!client.loop())
  {
   mqttConnect();
                                                                          // function call to connect to IBM
  }
                                    _____-retrieving to cloud
void wifiConnect()
Serial.print("Connecting to ");
Serial.print("Wifi");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED)
  {
   delay(500);
   Serial.print(".");
  }
Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
}
void mqttConnect()
{
  if (!client.connected())
   {
    Serial.print("Reconnecting MQTT client to ");
    Serial.println(server);
     (!client.connect(clientId, authMethod, token))
     {
      Serial.print("."); delay(500);
    initManagedDevice(); Serial.println();
void initManagedDevice()
  if (client.subscribe(topic))
   {
    Serial.println("IBM subscribe to cmd OK");
```

```
else
       Serial.println("subscribe to cmd FAILED");
   void publishData()
   float cm = readcmCM();
    if(digitalRead(34))
                                                                        //PIR motion detection
     Serial.println("Motion
     Detected");
                     Serial.println("Lid
     Opened"); digitalWrite(15, HIGH);
   else
     digitalWrite(15, LOW);
   if(digitalRead(34)== true)
    if(cm <= 100)
                                                                      //Bin level detection
     digitalWrite(2, HIGH);
     Serial.println("High Alert!!!,Trash bin is about to be full");
     Serial.println("Lid Closed"); lcd.print("Full! Don't use"); delay(2000);
        lcd.clear();
                               digitalWrite(4,
                                                     LOW);
     digitalWrite(23, LOW);
  else if(cm > 150 && cm < 250)
     digitalWrite(4, HIGH);
     Serial.println("Warning!!,Trash is about to cross 50% of bin level"); digitalWrite(2,
     digitalWrite(23, LOW);
  else if(cm > 250 && cm <=400)
     digitalWrite(23, HIGH); Serial.println("Bin is
     available"); digitalWrite(2,LOW);
     digitalWrite(4, LOW);
     delay(10000); Serial.println("Lid Closed");
   else
    Serial.println("No motion detected");
   if(cm <= 100)
   digitalWrite(21,HIGH);
  String payload = "{\"High Alert!!\":\"";
   payload += cm; payload
   += "left\" }";
  Serial.print("\n");
  Serial.print("Sending payload: ");
  Serial.println(payload); if (client.publish(publishTopic, (char*) payload.c_str())) // if data is uploaded to cloud successfully,prints publish
ok or prints publish failed
  Serial.println("Publish OK");
```

```
}
if(cm <= 250)
digitalWrite(22,HIGH);
String payload = "{\"Warning!!\":\"";
payload += dist; payload += "left\" }";
\textbf{Serial}.print("\n");
(char*) payload.c_str()))
Serial.println("Publish OK");
}
else
Serial.println("Publish FAILED");
}
}
float\ inches = (cm / 2.54); \ //print\ on\ LCD\ lcd.setCursor(0,0);\ lcd.print("Inches");\ lcd.setCursor(4,0);
lcd.setCursor(12,0); lcd.print("cm"); lcd.setCursor(1,1); lcd.print(inches, 1); lcd.setCursor(11,1);
lcd.print(cm, 1); lcd.setCursor(14,1); delay(1000); lcd.clear();
}
```

Connection Diagram

