ARUNAI ENGINEERING COLEGE

Department of Computer Science and Engineering

Smart Farmer-IOT Enabled Smart Farming Application

SPRINT DELIVERY – 2

TITLE	Smart Farmer-IOT Enabled Smart Farming Application
DOMAIN NAME	INTERNET OF THINGS
TEAM ID	PNT2022TMID29459
LEADER NAME	PRIYADHARSHINI A
TEAM MEMBER NAME	SANTHANALAKSHMI S KIRUBAVATHI S JASEEMABEGUM G
MENTOR NAME	SHOBA G

Building Project

Connecting IoT Simulator to IBM Watson IoT Platform


- Open link provided in below image
- ➤ Give the credentials of your device in IBM Watson
- ➤ PlatformClick on connect

My credentials given to simulator are:

api: a-ck2tf0-yutwjanphx

Device type: 1234

Token: MaZKMomT_thHLD54ml




You can see the received data in graphs by creating cards in Boards tab


> You will receive the simulator data in cloud

- > You can see the received data in Recent Events under your device
- ➤ Data received in this format(json)


```
{
  "d": {
  "name": "abcd",
  "temperature": 17,
  "humidity": 76,
  "Moisture ": 25
  }
}
```




Configuration of Node-Red to collect IBM cloud data




- ➤ The node IBM IoT App In is added to Node-Red workflow. Then the appropriatedevice credentials obtained earlier are entered into the node to connect and fetch device telemetry to Node-Red.
- Once it is connected Node-Red receives data from the device Display the data using debug node for verification
- ➤ Connect function node and write the Java script code to get each reading separately.
- ➤ The Java script code for the function node is: msg.payload=msg.payload.d.temperature return msg;
- Finally connect Gauge nodes from dashboard to see the data in UI



> Data received from the cloud in Node-Red console



Nodes connected in following manner to get each reading separately



This is the Java script code I written for the function node to get Temperature separately.

Configuration of Node-Red to collect data from OpenWeather

The Node-Red also receive data from the OpenWeather API by HTTP GET request. An inject trigger is added to perform HTTP request for every certain interval. HTTP request node is configured with URL we saved before in section 4.4 The data we receive from OpenWeather after request is in below JSON

```
format: {"coord": {"lon": 79.85, "lat": 14.13}, "weather": [{"id": 803, "main": "Clouds", "description": "brokenclouds", "icon": "04n"}], "base": "stations", "main": {"temp": 30759, "feels_like": 305.5, "temp_min": 307.59, "temp_max": 307.59, "pressure": 1002, "humidity": 35, "sea_level": 1002, "grnd_level": 1000}, "wind": {"speed": 6.23, "deg": 170}, "clouds": {"all": 68}, "dt": 1589991979, "sys": {"country": "IN", "sunrise": 158993355
```

3"sunset":1589979720},"timezone":19800,"id":1270791,"name":"Gūdūr","cod":20 0}

In order to parse the JSON string we use Java script functions and get each parameters

var temperature = msg.payload.main.temp; temperature = temperature-273.15;

return

{payload : temperature.toFixed(2)};

In the above Java script code we take temperature parameter into a new variable and convert it from kelvin to Celsius

Then we add Gauge and text nodes to represent data visually in UI

