

In [1]:

```
import keras
from keras.preprocessing.image import ImageDataGenerator
```

In [2]:

```
#Define the parameters/arguments for ImageDataGenerator class
train_datagen=ImageDataGenerator(rescale=1./255,shear_range=0.2,rotation_range=180,zoom_range=0.2,horizontal_flip=True)

test_datagen=ImageDataGenerator(rescale=1./255)
```

In [4]:

```
#Applying ImageDataGenerator functionality to trainset
x_train=train_datagen.flow_from_directory('/content/drive/MyDrive/Dataset/Dataset/train_set',target_size=(128,128),batch_size=32,class_mode='binary')
```

Found 436 images belonging to 2 classes.

In [5]:

```
#Applying ImageDataGenerator functionality to testset
x_test=test_datagen.flow_from_directory('/content/drive/MyDrive/Dataset/Dataset/test_set',target_size=(128,128),batch_size=32,class_mode='binary')
```

Found 121 images belonging to 2 classes.

In [6]:

```
#import model building libraries

#To define Linear initialisation import Sequential
from keras.models import Sequential
#To add layers import Dense
from keras.layers import Dense
#To create Convolution kernel import Convolution2D
from keras.layers import Convolution2D
#import Maxpooling layer
from keras.layers import MaxPooling2D
#import flatten layer
from keras.layers import Flatten
import warnings
warnings.filterwarnings('ignore')
```

In [7]:

```
#initializing the model
model=Sequential()
```

In [8]:

```
#add convolutional layer
model.add(Convolution2D(32,(3,3),input_shape=(128,128,3),activation='relu'))
#add maxpooling layer
model.add(MaxPooling2D(pool_size=(2,2)))
#add flatten layer
model.add(Flatten())
```

In [10]:

```
#add hidden layer
model.add(Dense(150,activation='relu'))
#add output layer
model.add(Dense(1,activation='sigmoid'))
```

In [11]:

```
In [11]:
```

```
#configure the learning process
```

```
model.compile(loss='binary_crossentropy', optimizer="adam", metrics=["accuracy"])
```

```
In [ ]:
```