

ASSIGNMENT 4

Name	L. Archana
Topic	Smart Solutions for Railways
Team id	PNT2022TMID38248

Write code and connections in wokwi for ultrasonic sensor

Whenever distance is less than 100cms send “alert” to ibm cloud and display in device recent events upload wokwi share images

```
#include <WiFi.h>
#include <PubSubClient.h>
void callback(char* subscribetopic,byte* payload, unsigned int payloadLength);
#define ORG "7wdz6s"
#define DEVICE_TYPE "iot"
#define DEVICE_ID "200148"
#define TOKEN "73973263"
String data3;

char server[]= ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[]="iot-2/evt/distance/fmt/json";
char subscribeTopic[]="iot-2/cmd/test/fmt/String";
char authMethod[]="use-token-auth";
char token[]=TOKEN;
char clientID[]="d:ORG:DEVICE_TYPE:DEVICE_ID;

WiFiClient wifiClient;
PubSubClient client(server,1883,callback,wifiClient);

#define ECHO_PIN 2
#define TRIG_PIN 4
#define led 5

void setup() {
  // put your setup code here, to run once:
  Serial.begin(115200);
  pinMode(led, OUTPUT);
  pinMode(TRIG_PIN, OUTPUT);
```

```

    pinMode(ECHO_PIN, INPUT);
    wificonnect();
    mqttconnect();
}
float readDistanceCM() {
    digitalWrite(TRIG_PIN, LOW);
    delayMicroseconds(2);
    digitalWrite(TRIG_PIN, HIGH);
    delayMicroseconds(10);
    digitalWrite(TRIG_PIN, LOW);
    int duration=random(1,200);
    //Serial.println(duration);
    //duration = pulseIn(ECHO_PIN, HIGH);
    return duration ;
    //Serial.println(duration);
}

void loop() {
    float distance = readDistanceCM();
    //Serial.println(distance);

    bool isNearby = distance < 100;
    digitalWrite(led, isNearby);

    Serial.print("Measured distance: ");
    Serial.println(distance);
    if(distance<100){
        PublishData2(distance);

    }else{
        PublishData1(distance);

    }
    //PublishData(distance);
    delay(1000);
    if(!client.loop()){
        mqttconnect();
    }

    //delay(2000);
}
void PublishData1(float dist){
    mqttconnect();
    String payload= "{\"distance\":\"";
    payload += dist;
    payload+="}";
}

```

```

Serial.print("Sending payload:");
Serial.println(payload);

if(client.publish(publishTopic,(char*)payload.c_str())){
    Serial.println("publish ok");
} else{
    Serial.println("publish failed");
}
}

void PublishData2(float dist){
    mqttconnect();
    String payload= "{\"ALERT\":";
    payload += dist;
    payload+="}";

    Serial.print("Sending payload:");
    Serial.println(payload);

    if(client.publish(publishTopic,(char*)payload.c_str())){
        Serial.println("publish ok");
    } else{
        Serial.println("publish failed");
    }
}

void mqttconnect(){
    if(!client.connected()){
        Serial.print("Reconnecting to ");
        Serial.println(server);
        while(!!!client.connect(clientID, authMethod, token)){
            Serial.print(".");
            delay(500);
        }
        initManagedDevice();
        Serial.println();
    }
}

void wificonnect(){
    Serial.println();
    Serial.print("Connecting to");

    WiFi.begin("Wokwi-GUEST","",6);
    while(WiFi.status() != WL_CONNECTED){
        delay(500);
        Serial.print(".");
    }
    Serial.println("");
    Serial.println("WIFI CONNECTED");
}

```

```

    Serial.println("IP address:");
    Serial.println(WiFi.localIP());
}

void initManagedDevice(){
    if(client.subscribe(subscribeTopic)){
        Serial.println((subscribeTopic));
        Serial.println("subscribe to cmd ok");
    }else{
        Serial.println("subscribe to cmd failed");
    }
}

void callback(char* subscribeTopic, byte* payload, unsigned int payloadLength){
    Serial.print("callback invoked for topic:");
    Serial.println(subscribeTopic);
    for(int i=0; i<payloadLength; i++){
        data3 += (char)payload[i];
    }
    Serial.println("data:"+ data3);
    if(data3=="lighton"){
        Serial.println(data3);
        digitalWrite(led,HIGH);
    }else{
        Serial.println(data3);
        digitalWrite(led,LOW);
    }
    data3="";
}

```

Link:

<https://wokwi.com/projects/347292100667114066>

NORMAL CASE:

The screenshot shows the Wokwi IoT simulation interface. The left pane displays the sketch code, and the right pane shows the simulation results.

```
1 #include <WiFi.h>
2 #include <PubSubClient.h>
3 void callback(char* topic, byte* payload, unsigned int payloadLength) {
4   #define ORG "7wdz6s"
5   #define DEVICE_TYPE "iot"
6   #define DEVICE_ID "200148"
7   #define TOKEN "73973263"
8   String data;
9
10  char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
11  char publishTopic[] = "iot-2/evt/distance/fmt/json";
12  char subscribeTopic[] = "iot-2/cmd/test/fmt/String";
13  char authMethod[] = "use-token-auth";
14  char token[] = TOKEN;
15  char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
16
17  WiFiClient wifiClient;
18  PubSubClient client(server, 1883, callback, wifiClient);
19
20  #define ECHO_PIN 2
21  #define TRIG_PIN 4
22  #define led 5
23
24  void setup() {
25    // put your setup code here, to run once:
26    Serial.begin(115200);
27    pinMode(led, OUTPUT);
```

Simulation results:

```
publish ok
Measured distance: 189.00
Sending payload:{"distance":189.00}
publish ok
Measured distance: 4.00
Sending payload:{"ALERT":4.00}
publish ok
```

ALTER CASE:

The screenshot shows the Wokwi IoT simulation interface. The left pane displays the sketch code, and the right pane shows the simulation results.

```
1 #include <WiFi.h>
2 #include <PubSubClient.h>
3 void callback(char* topic, byte* payload, unsigned int payloadLength) {
4   #define ORG "7wdz6s"
5   #define DEVICE_TYPE "iot"
6   #define DEVICE_ID "200148"
7   #define TOKEN "73973263"
8   String data;
9
10  char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
11  char publishTopic[] = "iot-2/evt/distance/fmt/json";
12  char subscribeTopic[] = "iot-2/cmd/test/fmt/String";
13  char authMethod[] = "use-token-auth";
14  char token[] = TOKEN;
15  char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
16
17  WiFiClient wifiClient;
18  PubSubClient client(server, 1883, callback, wifiClient);
19
20  #define ECHO_PIN 2
21  #define TRIG_PIN 4
22  #define led 5
23
24  void setup() {
25    // put your setup code here, to run once:
26    Serial.begin(115200);
27    pinMode(led, OUTPUT);
```

Simulation results:

```
publish ok
Measured distance: 169.00
Sending payload:{"distance":169.00}
publish ok
Measured distance: 144.00
Sending payload:{"distance":144.00}
publish ok
```

IBM CLOUD

The screenshot displays the IBM Watson IoT Platform dashboard in a web browser. The URL is <https://7wdz6s.internetofthings.ibmcloud.com/dashboard/devices/browse>. The user is logged in as **archana.leganathan76@gmail.com** with ID **7wdz6s**. The dashboard shows a list of devices, with one device selected and its details expanded.

Device Details:

Device ID	Status	Device Type	Class ID	Date Added
200148	Disconnected	iot	Device	Nov 1, 2022 9:55 PM

Recent Events:

The recent events listed show the live stream of data that is coming and going from this device.

Event	Value	Format	Last Received
distance	{"ALERT":43}	json	a few seconds ago
distance	{"distance":166}	json	a few seconds ago
distance	{"distance":178}	json	a few seconds ago
distance	{"ALERT":47}	json	a few seconds ago
distance	{"distance":106}	json	a few seconds ago

