## **ASSIGNMENT-4**

**TEAM ID** 

PNT2022TMID25739

Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events. Upload document with wokwi share link and images of IBM cloud.

## PROGRAM:

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#include "DHT.h"// Library for dht11
#define DHTPIN 15 // what pin we're connected to
#define DHTTYPE DHT22 // define type of sensor DHT 11
#define BUZZER PIN 2
int BUZZER CHANNEL = 0;
DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr of
dht connected
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//----credentials of IBM Accounts-----
#define ORG "fqeyos"//IBM ORGANITION ID
#define DEVICE TYPE "praveen107devicetype"//Device type mentioned in ibm
watson IOT Platform
#define DEVICE ID "meds108"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "p__P14YR0cP-CSHEkN"
                                     //Token
String data3;
float h, t;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
event perform and format in which data to be send
```

```
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT
command type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE TYPE ":" DEVICE ID;//client id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the
predefined client id by passing parameter like server id, portand
wificredential
void setup()// configureing the ESP32
 Serial.begin(115200);
 dht.begin();
 pinMode(BUZZER_PIN,OUTPUT);
 ledcAttachPin(BUZZER_PIN, BUZZER_CHANNEL);
 delay(10);
 Serial.println();
 wificonnect();
 mqttconnect();
}
void loop()// Recursive Function
{
 h = dht.readHumidity();
 t = dht.readTemperature();
 Serial.print("temperature:");
 Serial.println(t);
 Serial.print("Humidity:");
 Serial.println(h);
 PublishData(t, h);
 delay(1000);
 if (!client.loop()) {
   mqttconnect();
 }
}
/*....retrieving to
Cloud.....*/
void PublishData(float temp, float humid) {
  mqttconnect();//function call for connecting to ibm
  /*
```

```
creating the String in in form JSon to update the data to ibm cloud
  */
  String payload = "{\"Temperature\":";
  payload += temp;
  payload += "," "\"Humidity\":";
  payload += humid;
  payload += "}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish ok");// if it sucessfully upload data on the cloud
then it will print publish ok in Serial monitor or else it will print publish
failed
 } else {
   Serial.println("Publish failed");
 }
void mqttconnect() {
 if (!client.connected()) {
    Serial.print("Reconnecting client to ");
    Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
     Serial.print(".");
     delay(500);
    }
     initManagedDevice();
     Serial.println();
 }
}
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
the connection
 while (WiFi.status() != WL_CONNECTED) {
   delay(500);
   Serial.print(".");
  }
 Serial.println("");
  Serial.println("WiFi connected");
```

```
Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
}
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
    Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
  }
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++) {</pre>
   //Serial.print((char)payload[i]);
   data3 += (char)payload[i];
  }
  Serial.println("data: "+ data3);
  if(data3=="lighton")
Serial.println(data3);
digitalWrite(BUZZER_PIN,HIGH);
ledcWriteNote(BUZZER_CHANNEL, (note_t)NOTE_D, 8);
  }
  else
  {
Serial.println(data3);
digitalWrite(BUZZER_PIN,LOW);
ledcWriteNote(BUZZER_CHANNEL, (note_t)NOTE_D, 0);
  }
data3="";
}
```

OUTPUT:

