

IBM-Nallaiya Thiran Project

Assignment – 3

Abinesh V
2019503001

Q) Write python code for blinking LED and Traffic Light for Raspberry pi.

- **LED Light :**

Source Code:

```
import RPi.GPIO as GPIO # RPi.GPIO can be referred as GPIO from now
import time
ledPin = 22 # pin22
def setup():
    GPIO.setmode(GPIO.BOARD) # GPIO Numbering of Pins
    GPIO.setup(ledPin, GPIO.OUT) # Set ledPin as output
    GPIO.output(ledPin, GPIO.LOW) # Set ledPin to LOW to turn Off the
LED
def loop():
    while True:
        print 'LED on'
        GPIO.output(ledPin, GPIO.HIGH) # LED On
        time.sleep(1.0) # wait 1 sec
        print 'LED off'
        GPIO.output(ledPin, GPIO.LOW) # LED Off
        time.sleep(1.0) # wait 1 sec
def endprogram():
    GPIO.output(ledPin, GPIO.LOW) # LED Off
    GPIO.cleanup() # Release resources
if __name__ == '__main__': # Program starts from here
    setup()
    try:
        loop()
```

```
except KeyboardInterrupt: # When 'Ctrl+C' is pressed, the destroy()
will be executed.
    endprogram()
```

- **Traffic Lights**

Source Code:

```
import RPi.GPIO as GPIO
import time
import signal
import sys
GPIO.setmode(GPIO.BCM)
GPIO.setup(9, GPIO.OUT)
GPIO.setup(10, GPIO.OUT)
GPIO.setup(11, GPIO.OUT)
def allLightsOff(signal, frame):
    GPIO.output(9, False)
    GPIO.output(10, False)
    GPIO.output(11, False)
    GPIO.cleanup()
    sys.exit(0)
signal.signal(signal.SIGINT, allLightsOff)
while True:
    # Red
    GPIO.output(9, True)
    time.sleep(3)
    # Red and amber
    GPIO.output(10, True)
    time.sleep(1)
    # Green
    GPIO.output(9, False)
    GPIO.output(10, False)
```

```
GPIO.output(11, True)
time.sleep(5)
# Amber
GPIO.output(11, False)
GPIO.output(10, True)
time.sleep(2)
# Amber off (red comes on at top of loop)
GPIO.output(10, False)
```