Project Design Phase-II Solution Requirements (Functional & Non-functional)

| Date | 12 October 2022 |
|---------------|--|
| Team ID | PNT2022TMID00923 |
| Project Name | Signs with smart connectivity for better road safety |
| Maximum Marks | 4 Marks |

Functional Requirements:

Following are the functional requirements of the proposed solution.

| FR No. | Functional Requirement (Epic) | Sub Requirement (Story / Sub-Task) |
|--------|-------------------------------|---|
| FR-1 | USER REGISTRATION | Through google forms |
| | | Through mail |
| | | Through linkedin |
| | | Through facebook |
| FR-2 | USER CONFIRMATION | Through verification mails |
| | | Through OTP |
| FR-3 | USER APPROVAL | Through mails |
| | | Through phone calls |
| | | Through SMS |
| FR-4 | USER TRANSACTION | Through net banking |
| | | Through UPI |
| FR-5 | TESTING | Testing through components |
| | | Testing through API and UI |
| FR-6 | END RESULT | End result through product features |
| | | By using the technology |

Non-functional Requirements:

Following are the non-functional requirements of the proposed solution.

| FR No. | Non-Functional Requirement | Description |
|--------|----------------------------|---|
| NFR-1 | Usability | Situations never remain the same. Therefore there must be a constant check of the conditions prevailing and accordingly there must be changes made in these boards. Sign boards with caution or alerts must be placed well in advance so that the drivers could be more alert with the journey. The text content must be available in different languages to help the drivers. Boards must be large and clear for better visibility. |

| NFR-2 | Security | Sign boards should be bright coloured so that it catches the drivers' sight. The illustrations or the symbols used in the boards must be easily understandable. The security system should be strong enough that no one can modify it other than the authority. No one should be able to enter into |
|-------|--------------|--|
| | | the network to change, delete or manage the intimations or messages delivered through the sign boards. |
| NFR-3 | Reliability | There should not be any miscommunications or confusions regarding the messages displayed. Maximum accuracy must be ensured. All the information displayed must be checked periodically and updated if any changes are needed for error-free intimation. |
| NFR-4 | Performance | The efficiency and the accuracy of the information hence calculated should be maximum. It should be ensured that minimum amount of energy, time and cost is required for the operation. |
| NFR-5 | Availability | These should be available anytime and everywhere that is 24/7. Sign boards should be located in places which has direct view from the road. It should not present amidst bushes, trees, building etc It should be properly monitored that no sign boards are damaged, repaired or malfunctioning at any time. The sign boards should be made available only in places where they are required the most. Frequent availability of boards may lead to confusion and mistakes. |
| NFR-6 | Scalability | It should be easy to scale according to the requirement. It should be in such a way that the network at any time of period should be ready to be expanded and implemented on a wider scale. |