# Assignment - 4

NAME :- Sruthi Gnana Priya D
ROLL.No:- 110719106033

OBJECTIVES:-
Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events.

LINK :- sketch.ino - Wokwi Arduino and ESP32 Simulator

CIRCUIT:-

CODE:-

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#define TRIG_PIN 13
#define ECHO_PIN 12

void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
```

```cpp
//-------credentials of IBM Accounts------

#define ORG "hg0hll"//IBM ORGANITION ID
#define DEVICE_TYPE "123"//Device type mentioned in ibm watson IOT Platform
#define DEVICE_ID "abcd"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "12345678"     //Token

//-------- Customise the above values --------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and format in
which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd  REPRESENT command type AND
COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id

//----------------------------------------
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient);  //calling the predefined client id by passing
parameter like server id,portand wificredential

void setup()// configureing the ESP32
{
 Serial.begin(115200);
 pinMode(TRIG_PIN, OUTPUT);
 digitalWrite(TRIG_PIN, LOW);
 pinMode(ECHO_PIN, INPUT);
 delay(10);
 Serial.println();
 wificonnect();
 mqttconnect();
}

void loop()// Recursive Function
{
```

```arduino
  digitalWrite(TRIG_PIN, HIGH);
  delayMicroseconds(10);
  digitalWrite(TRIG_PIN, LOW);
  float duration_us = pulseIn(ECHO_PIN, HIGH);
  float distance = 0.017 * duration_us;

  if(distance<100)
  {
    PublishData(distance,"ALERT");
  }else{
    PublishData(distance,"SAFE");
  }

  delay(1000);
  if (!client.loop()) {
    mqttconnect();
  }
}

/*...................................retrieving to Cloud.............................*/

void PublishData(float d,char s[]) {
  mqttconnect();//function call for connecting to ibm
  /*
    creating the String in in form JSon to update the data to ibm cloud
  */
  String payload = "{\"Distance\":";
  payload+=d;
  payload+=",";
  payload+="\"MESSAGE\":";
  payload+="\"";
  payload+=s;
  payload+="\"";
  payload+="}";

  Serial.print("Sending payload: ");
```

```arduino
    Serial.println(payload);

  if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will print publish ok
in Serial monitor or else it will print publish failed
  } else {
    Serial.println("Publish failed");
  }
}
void mqttconnect() {
  if (!client.connected()) {
    Serial.print("Reconnecting client to ");
    Serial.println(server);
    while (!!!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
      delay(500);
    }
    initManagedDevice();
    Serial.println();
  }
}
void wificonnect() //function defination for wificonnect
{
  Serial.println();
  Serial.print("Connecting to ");
  WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
  while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  }
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
}
void initManagedDevice() {
```

```cpp
if (client.subscribe(subscribetopic)) {

  Serial.println((subscribetopic));

  Serial.println("subscribe to cmd OK");

} else {

  Serial.println("subscribe to cmd FAILED");

}

}

void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)

{


}
```

OUTPUT:-