

**INTERNETOFTHINGS**

**GAS LEAKAGE**

**MONITORINGANDALERTINGSYSTEMFOR  
INDUSTRIES**

IBMProject–TeamID:PNT2022TMID13124

**TeamLeader**

Swathi - 717817F140

**TeamMembers**

Suvetha	717819F249
Dharshana	717819F209
Santhiya	717819F243

**BACHELOROFTECHNOLOGY**

**in**

**INFORMATION TECHNOLOGY**

**KARPAGAM COLLEGE OF ENGINEERING**

**ANNAUNIVERSITY:CHENNAI600025**

## **ABSTRACT**

The presence of hazardous gas leakage in Industries, also, stored gases contain gas which exhibits ideal characteristic is use. For that sake, an alarm unit is used to vibrate an alarm which is buzzer. Buzzer gives an audible sign of the presence of gas volume. These sensors are widely used to detect essence of propane, iso-butane and even smoke. The sensor has an advantage to combine a sensitivity response time. If the gas sensor senses gas leak, sensor output goes to active low (logic-0) condition. Arduino UNO is used in the project; low signals are overlooked by the Arduino and gas leakage is noticed by the Arduino. The Arduino UNO turns on the LCD and buzzer. It even turns on the GSM modem after that, it continues to send messages SMS to mobile numbers specifically mentioned in the program of the source code for alerting danger to the people.

# **LITERATURE REVIEW**

## **Survey1:**

**Pal-Stefan Murvay, Ioan Silea (2012)**

### **'Journal of Loss Prevention in the Process Industries'**

The main purpose of this paper is to identify the state-of-the-art in leak detection and localization methods. Additionally we evaluate the capabilities of these techniques in order to identify the advantages and disadvantages of using each leak detection solution.

## **Survey2:**

**Srinivasan, Leela, Jeyabharathi, Kirthik, Rajasree; (2014)**

### **'Adapted approach for Species Classification'**

In this research paper they told about gas leakage detection and control. In this paper, the gas leakage resulting into fatal inferno has become a serious problem in household and other areas where household gas is handled and used. It alerts the subscriber through the alarm and the status display besides turning off the gas supply valve as a primary safety measure. This simplicity results in a high instruction turn-out and spectacular real-time interrupt response from a tiny and cost-efficient processor core. The microcontroller provides the data to the coil valve to shut its knob. The coil valve consists of a disc that's in touch with the spring. Once the gas leaks the disc comes in touch with the spring so it stops the flow of gas. Finally the gas area unit thrown out the disc moves so the gas flows. At that point the buzzer starts direful thereby to alert the neighbors. A Buzzer or electronic device is a signal device, typically electronic, generally used in cars, manage appliances such as microwave kitchen appliance or game shows.

### **Survey3:**

**Prof.M.Amsaveni, A.Anurupa, R.S.AnuPreetha,  
C.Malarvizhi,M.Gunasekaran;(2015)**

#### **“GSMbasedLPGleakagedetectionandcontrollingsystem”**

They proposed their methodology that the system takes an automatic control action after the detection of 0.001% of Gas leakage. This automatic control action provides a mechanical handle for closing the valve. We are increasing the security for human by means of a relay which will shut down the electric power to the house. Also by using GSM, we are sending an alert message to the users and a buzzer is provided for alerting the neighbors about the leakage.

### **Survey4:**

**VSuma,RamyaRShekar,  
KumarAAkshay(2019)'GasLeakageDetectionBase  
donIOT'**

The aim of this paper is to present a new system automatically books a cylinder when the gas is about to empty by sending a notification to the gas agency using wifi using Internet of Things approach.

### **Survey5:**

**AdilAhmad,ShaikShaheeda  
DepartmentofInformationScienceandEngineering,BengaluruGasLeakageD  
etectionBasedSystem(ICEA2017).**

The author has observed gas leakage and LPG levels where gas leakage occurs automatically. The authors suggest that gas leakage is performed by various gas sensors. Whose author has worked on gas leaks and mentions that we can take care if a found using a sensor and gas booking can be done automatically when a small amount of gas is taken enclosed.

### **Survey6:**

**MohdAbidPGstudent**

**Design and Embedded system, VTU PG centre kalaburagi, India  
IJETERvolume6,issue4,April(2018).**

Through this paper important parameters are used to find the level of gas in the container. The good purpose of this project is to get notification of gas leak to user when gas leakage is started. Arduino was originally created as a tool for fast sampling and activities for students with no knowledge for electronics. This paper uses a microcontroller, buzzer and a gas sensor to detect gas leakage system. When a gas leak is detected by a gas sensor, the microcontroller turns on the buzzer in critical condition. The author suggests that this message or instruction may be displayed using an LCD display for LPG monitoring.

### **Survey7:**

**Kulothungan. S, Gukan. A ,**

**Arunprabu.K.B Student, IFET College of Engineering.**

**IJEDR2019.**

The proposed system detects LPG leaks and alerts customers. The alarm starts when the system notices and increases in LPG leakage concentration by sending an alarm and sending a message to a specific mobile phone. The device assures safety and prevents explosions. A microcontroller-based system based on a gas sensor (MQ6) has been developed in the proposed system to detect LPG leakage. The unit is also integrated with an alarm unit to detect a signal a leak.

## REFERENCES

1. Pal-Stefan Murvay, Ioan Silea  
'Journal of Loss Prevention in the Process Industries'-2012
2. Srinivasan, Leela, Jeyabharathi, Kirthika, Rajasree  
“GAS LEAKAGE DETECTION AND CONTROL” Scientific Journal of Impact Factor (SJIF): 3.134 March-2014.
3. Prof. M. Amsaveni, A. Anurupa, R. S. Anu Preetha, C. Malarvizhi, M. Gunasekaran  
“Gsm based LPG leakage detection and controlling system” the International Journal of Engineering and Science (IJES) ISSN (e): 2319 – 1813 ISSN (p): 2319 – 1805 Pages 112-116 March-2015'
4. V Suma, Ramya R Shekar, Kumar A Akshay  
'Gas Leakage Detection Based on IOT'-2019
5. Adil Ahmad, Shaik Shaheeda.  
Bengaluru Gas Leakage Detection Based System (ICEA 2017).
6. Mohd Abid PG student Dept of VLSI Design and Embedded system.  
VTU PG centre kalaburagi, India IJETER volume 6, issue 4, April (2018).
7. Kulothungan. S, Gukan. A , Arunprabu. K. B Associate  
Professor. Student, IFET College of Engineering. IJEDR 2019