

SPRINT DELIVERY – 4

Team ID	PNT2022TMID24443
Project Name	Smart Farmer – IOT Enabled Smart Farming Application

5.5 Receiving commands from IBM cloud using Python program

```
import time import
```

```
sys
```

```
import ibmiotf.application
```

```
import ibmiotf.device import
```

```
random
```

```
#Provide your IBM Watson Device
```

```
organization = "uojvy9"
```

```
deviceType= "NodeMCU"
```

```
deviceid="12345 "
```

```
authMethod="token"
```

```
authToken="12345678"
```

```
# Initialize GPIO
```

```
def myCommandCallback(cmd):
```

```
print("Command received: %s" % cmd.data['command'])
```

```
status=cmd.data['command']
```

```
if status=="motoron":
```

```
    print ("motor is on")
```

```
elif status == "motoroff":
```

```

        print("motor is off")

else :

    print ("please send proper command")


try:

    deviceOptions = {"org": organization, "type": deviceType, "id": deviceId,
"auth-method": authMethod, "auth-token": authToken}
    deviceCli = ibmiotf.device.Client(deviceOptions)

    #.....

except Exception as e:

    print("Caught exception connecting device: %s" %
str(e))sys.exit()

# Connect and send a datapoint "hello" with value "world" into the cloud as an
event of type "greeting" 10 times deviceCli.connect()


while True:

    #Get Sensor Data from
    DHT11
    temp=random.randint(90,110)
    Humid=random.randint(60,100)
    Mois=random. Randint(20,120)

    data = { 'temp' : temp, 'Humid': Humid ,
'Mois': Mois}

    #print data      def
myOnPublishCallback(
):

    print ("Published Temperature = %s C" % temp, "Humidity = %s %% "
%Humid, "Moisture =%s deg c" % Mois "to IBM Watson")

```

```

        success = deviceCli.publishEvent("IoTSensor", "json", data,
qos=0,on_publish=myOnPublishCallback)        if not success:
        print("Not connected to IoTF")

```

```

time.sleep(10)

```

```

deviceCli.commandCallback = myCommandCallback #

```

Disconnect the device and application from the cloud

```

deviceCli.disconnect()

```

```

import time
import sys
import ibmiotf.application
import ibmiotf.device
import random


organization = "uojvvy9"
deviceType="NodeMCU"
deviceId="12345"
authMethod="token"
authToken="12345678"

def myCommandCallback(cmd):
    print("Message received from IBM IoT Platform: %s" % cmd.data['command'])
    m=cmd.data['command']
    if(m=="motoron"):
        print("Motor is on")
    elif(m=="motorkoff"):
        print("Motor is off")
    else:
        print("plese send proper command ")
try:
    deviceOptions = {"org": organization, "type": deviceType, "id": deviceId,
"auth-method": authMethod, "auth-token": authToken} deviceCli = ibmiotf.device.Client(deviceOptions)
#.....

except Exception as e:
    print("Caught exception connecting device: %s" % str(e))sys.exit()
# Connect and send a datapoint "hello" with value "world" into the cloud as an event of type "greeting" 10 times deviceCli.connect()

while True:
    #Get Sensor Data from DHT11

```




```

Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py =====
2022-11-07 20:01:24,074  ibmiotf.device.Client      INFO      Connected successfu
lly: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motorkoff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson

```

6. Flow Chart




7. Observations & Results

```
Python 3.7.0 Shell
File Edit Shell Debug Options Window Help
Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py =====
2022-11-07 20:01:24,074 ibmiotf.device.Client INFO Connected successfully
lly: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motoroff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson
```



Farming Measure Data



Switchboard

MOTOR SWITCH ON

MOTOR SWITCH OFF

8. Advantages & Disadvantages Advantages:

- Farms can be monitored and controlled remotely.
- Increase in convenience to farmers.
- Less labor cost.
- Better standards of living.

Disadvantages:

- Lack of internet/connectivity issues.
- Added cost of internet and internet gateway infrastructure.
- Farmers wanted to adapt the use of Mobile App.

9. Conclusion

Thus the objective of the project to implement an IOT system in order to help farmers to control and monitor their farms has been implemented successfully.