Assignment Date	29 September 2022
Student Name	Prakalya.RS
Student Roll Number	211519205112
Maximum Marks	2 Marks

Question-1:

Create form of type input text, email, password, radio button, text area, drop down and navigate to successor page and display files of form in table (CSS, HTML)

Solution:

```
<html>
<head>
<title>Form</title>
<script type="text/javascript">
function displayDetails()
{
var name = document.getElementById("name").value;
var email = document.getElementById("email").value;
var gender = document.getElementById("gender").value;
var year = document.getElementById("year").value;
var pl = document.getElementById("pl").value;
document.writeln("<html><body>");
document.writeln("<table border='1'><tr>");

document.writeln("<th>Name</th><th>Email</th><th>Gender</th><th>Program
mingLanguage</th><th>Year</th>");
document.writeln("</tr>");

document.writeln("<tr><td>"+name+"</td><td>"+email+"</td><td>"+gender+"</t
d><td>"+pl+"</td><td>"+year+"</td>");
document.writeln("</tr></table>");
document.writeln("</body></html>");
}
</script>
</head>
<body>
<form method="post" onsubmit="displayDetails()">
<label for="name">Name:</label>
  <input type="text" id="name" name="name" placeholder="Enter
name"/><br/><br/>
<label for="email">Email:</label>
  <input type="email" id="email" name="email" placeholder="Enter
email"/><br/><br/>
```

```html
  <label for="pwd">Password:</label>
    <input type="password" id="pwd" name="pwd" placeholder="Enter password"/><br/><br/>
  <label for="address">Address:</label>
    <textarea id="address" name="address" rows="4" cols="50"></textarea><br/><br/>
  <label for="gender">Gender: </label>
    <input type="radio" id="gender" name="gender" value="male">Male</input>

    <input type="radio" id="gender" name="gender" value="female">Female</input><br/><br/>
  <label for="pl">Programming languages: </label>
    <input type="checkbox" id="pl" name="pl" value="java">Java</input>
          <input type="checkbox" id="pl" name="pl" value="c">C</input>
          <input type="checkbox" id="pl" name="pl" value="python">Python</input>
          <input type="checkbox" id="pl" name="pl" value="c++">C++</input><br/><br/>
  <label for="year">Year:</label>
    <select name="year" id="year">
          <option value="first">I</option>
          <option value="first">II</option>
          <option value="first">III</option>
          <option value="first">IV</option>
          </select><br/><br/>
  <label for="submit">Submit:</label>
    <input type="submit" value="submit"/><br/><br/></form></body>
</html>
```

OUTPUT:

Name: [Enter name]

Email: [Enter email]

Password: [Enter password]

Address: [   ]

Gender: ○ Male ○ Female

Programming languages: ☐ Java ☐ C ☐ Python ☐ C++

Year: [I ▾]

Submit: [submit]

Question-2:

For the CSS create external style sheet for above task (separate css file and link that in html)

Solution:

```html
<html>
<head>
<title>Form</title>
<script type="text/javascript">
function displayDetails()
{
var name = document.getElementById("name").value;
var email = document.getElementById("email").value;
var gender = document.getElementById("gender").value;
var year = document.getElementById("year").value;
var pl = document.getElementById("pl").value;
document.writeln("<html><body>");
document.writeln("<table border='1'><tr>");
document.writeln("<th>Name</th><th>Email</th><th>Gender</th><th>ProgrammingLanguage</th><th>Year</th>");
document.writeln("</tr>");
document.writeln("<tr><td>"+name+"</td><td>"+email+"</td><td>"+gender+"</td><td>"+pl+"</td><td>"+year+"</td>");
document.writeln("</tr></table>");
document.writeln("</body></html>"); }
</script>
<link rel="stylesheet" href="style.css" type="text/css" /></head>
<body>
<form method="post" onsubmit="displayDetails()">
 <label for="name">Name:</label>
   <input type="text" id="name" name="name" placeholder="Enter name"/><br/><br/>
  <label for="email">Email:</label>
   <input type="email" id="email" name="email" placeholder="Enter email"/><br/><br/>
 <label for="pwd">Password:</label>
   <input type="password" id="pwd" name="pwd" placeholder="Enter password"/><br/><br/>
 <label for="address">Address:</label>
    <textarea id="address" name="address" rows="4" cols="50"></textarea><br/><br/>
```

```html
    <label for="gender">Gender: </label>
        <input type="radio" id="gender" name="gender" value="male">Male</input>
        <input type="radio" id="gender" name="gender" value="female">Female</input><br/><br/>
    <label for="pl">Programming languages: </label>
        <input type="checkbox" id="pl" name="pl" value="java">Java</input>
            <input type="checkbox" id="pl" name="pl" value="c">C</input>
            <input type="checkbox" id="pl" name="pl" value="python">Python</input>
            <input type="checkbox" id="pl" name="pl" value="c++">C++</input><br/><br/>
    <label for="year">Year:</label>
        <select name="year" id="year">
            <option value="first">I</option>
            <option value="first">II</option>
            <option value="first">III</option>
            <option value="first">IV</option></select><br/><br/>
    <label for="submit">Submit:</label>
        <input type="submit" value="submit"/><br/><br/></form></body></html>
```

style.css
```css
body {
  background-color:pink;
  border-style: solid;}
table, th, td {
  border:1px solid;
}
```

OUTPUT:

Question-3:

Create sample program for Flask HTTP methods (list or map and perform operations of PUT, GET, DELETE and POST)

Solution:

```python
from flask import Flask,request,json
app=Flask(__name__)
cars={"1":"Lamborghini", "2":"Ferrari" , "3":"Porsche" , "4":"Landrover" , "5":"Bugatti",
"6":"Mercedes" ,"7":"Rolls-Royce" , "8":"BMW"}
@app.route('/data' ,methods=['GET','POST'])
def api():
    if request.method=='GET':
        return cars
    if request.method=='POST':
        data=request.json
        cars.update(data)
        return 'data got inserted'
@app.route("/data/<id>",methods=['PUT'])
def update(id):
    data=request.form['items']
    cars[str(id)]=data
    return 'data updated'
@app.route("/data/<id>",methods=["DELETE"])
def deleteoperation(id):
    cars.pop(str(id))
    return 'data deleted'
if__name__=='__main__':
    app.run(debug=True)
```

Output:

from flask import Flask,request,json app=Flask(__name__) cars={"1":"Lamborghini", "2":"Ferrari" , "3":"Porsche" , "4":"Landrover" , "5":"Bugatti", "6":"Mercedes" ,"7":"Rolls-Royce" , "8":"BMW"} @app.route('/data' ,methods= ['GET','POST']) def api(): if request.method=='GET': return cars if request.method=='POST': data=request.json cars.update(data) return 'data got inserted' @app.route("/data/",methods=['PUT']) def update(id): data=request.form['items'] cars[str(id)]=data return 'data updated' @app.route("/data/",methods=["DELETE"]) def deleteoperation(id): cars.pop(str(id)) return 'data deleted' if__name__=='__main__': app.run(debug=True)