```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#include "DHT.h"// Library for dht11
#define DHTPIN 15 // what pin we're connected to
#define DHTTYPE DHT22 // define type of sensor DHT 11
#define BUZZER PIN 2
int BUZZER CHANNEL = 0;
DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr of dht connected
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
//----credentials of IBM Accounts-----
#define ORG "Iryrya"//IBM ORGANITION ID
#define DEVICE TYPE "Temp"//Device type mentioned in ibm watson IOT Platform
#define DEVICE ID "T1"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "123456789" //Token
String data3:
float Temperature;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and
format in which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT command type
AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN:
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the predefined client id by
passing parameter like server id, portand wificredential
void setup()// configureing the ESP32
 Serial.begin(115200);
 dht.begin();
 pinMode(BUZZER PIN,OUTPUT);
 ledcAttachPin(BUZZER PIN, BUZZER CHANNEL);
 delay(10);
 Serial.println();
```

```
wificonnect();
 mqttconnect();
}
void loop()// Recursive Function
 Temperature = dht.readTemperature();
 Serial.print("temperature:");
 Serial.println(Temperature);
 PublishData(Temperature);
 delay(1000);
 if (!client.loop()) {
  mqttconnect();
}
}
/*.....*/
void PublishData(float temp) {
 mqttconnect();//function call for connecting to ibm
   creating the String in in form JSon to update the data to ibm cloud
 String payload = "{\"Temperature\":";
 payload += temp;
 payload += "}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c str())) {
  Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will print publish
ok in Serial monitor or else it will print publish failed
 } else {
  Serial.println("Publish failed");
 }
```

```
void mqttconnect() {
 if (!client.connected()) {
  Serial.print("Reconnecting client to ");
  Serial.println(server);
  while (!!!client.connect(clientId, authMethod, token)) {
    Serial.print(".");
    delay(500);
   initManagedDevice();
   Serial.println();
 }
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
 while (WiFi.status() != WL CONNECTED) {
  delay(500);
  Serial.print(".");
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
}
void initManagedDevice() {
 if (client.subscribe(subscribetopic)) {
  Serial.println((subscribetopic));
  Serial.println("subscribe to cmd OK");
 } else {
  Serial.println("subscribe to cmd FAILED");
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
```

```
for (int i = 0; i < payloadLength; i++) {
  //Serial.print((char)payload[i]);
  data3 += (char)payload[i];
 }
 Serial.println("data: "+ data3);
 if(data3=="lighton")
 {
Serial.println(data3);
digitalWrite(BUZZER_PIN,HIGH);
ledcWriteNote(BUZZER_CHANNEL, (note_t)NOTE_D, 8);
 }
 else
 {
Serial.println(data3);
digitalWrite(BUZZER_PIN,LOW);
ledcWriteNote(BUZZER_CHANNEL, (note_t)NOTE_D, 0);
 }
data3="";
}
```