

```

import keras
from keras.datasets import fashion_mnist
from keras.layers import Dense, Activation, Flatten, Conv2D, MaxPooling2D
from keras.models import Sequential
from keras.utils import to_categorical
import numpy as np
import matplotlib.pyplot as plt

(train_X, train_Y), (test_X, test_Y) = fashion_mnist.load_data()

train_X = train_X.reshape(-1, 28, 28, 1)
test_X = test_X.reshape(-1, 28, 28, 1)

train_X = train_X.astype('float32')
test_X = test_X.astype('float32')
train_X = train_X / 255
test_X = test_X / 255

train_Y_one_hot = to_categorical(train_Y)
test_Y_one_hot = to_categorical(test_Y)

model = Sequential()

model.add(Conv2D(64, (3, 3), input_shape=(28, 28, 1)))
model.add(Activation('relu'))
model.add(MaxPooling2D(pool_size=(2, 2)))

model.add(Conv2D(64, (3, 3)))
model.add(Activation('relu'))
model.add(MaxPooling2D(pool_size=(2, 2)))

model.add(Flatten())
model.add(Dense(64))

model.add(Dense(10))
model.add(Activation('softmax'))

model.compile(loss=keras.losses.categorical_crossentropy,
optimizer=keras.optimizers.Adam(), metrics=['accuracy'])

model.fit(train_X, train_Y_one_hot, batch_size=64, epochs=5)

test_loss, test_acc = model.evaluate(test_X, test_Y_one_hot)
print('Test loss', test_loss)
print('Test accuracy', test_acc)

predictions = model.predict(test_X)
print(np.argmax(np.round(predictions[0])))

plt.imshow(test_X[0].reshape(28, 28), cmap = plt.cm.binary)
plt.show()

```