

### ASSIGNMENT 3

Assignment Date	19 September 2022
Student Name	SUBRAMANI B
Student Roll Number	715319106306
Maximum Marks	2 Marks

## Artificial intelligence

### A startlingly effective assistant

I was given early “preview” access to Copilot about a year ago, and I’ve been using it on and off. It takes some practice to learn exactly how to frame your requests in English so the Copilot AI gives the most useful code output, but it can be startlingly effective.

However, we’re still a *long* way from “Hey Siri, make me a million dollar iPhone app”. It’s still necessary to use my software design skills to figure out what the different bits of code should do in my app.

To understand the level Copilot is working at, imagine writing an essay. You can’t just throw the essay question at it and expect it to produce a useful, well-argued piece. But if you figure out the argument and maybe write the topic sentence for each paragraph, it will often do a pretty good job at filling in the rest of each paragraph automatically.

Depending on the type of coding I’m doing, this can sometimes be a huge time- and brainpower-saver.

Out[1]:

In [2]:

d.head()

	school	sex	age	addresses	family size	status	married	Fedu	Mjob	Fjob	...	internet	romantic	family	frequency	gout	Dalc	Walc	health	abuses	parents
0	GP	F	18	U	GT3	A	4	4	at_home	teacher	...	no	no	4	3	4	1	1	3	4	0
1	GP	F	17	U	GT3	T	1	1	at_home	other	...	yes	no	5	3	3	1	1	3	2	0
2	GP	F	15	U	LE3	T	1	1	at_home	other	...	yes	no	4	3	2	2	3	3	6	1
3	GP	F	15	U	GT3	T	4	2	health	services	...	yes	yes	3	2	2	1	1	5	0	1

	age	Medu	Fedu	travel_time	study_time	failures	famrel	fretime	goout	Dalc	..	activities_no	activities_yes	numser_y_no	numser_y_yes	higherno	higheryes	internet_no	internet_yes	romantic_no	romantic_yes
0	$\frac{1}{8}$	4	4	2	2	0	4	3	4	1	..	1	0	0	1	0	1	1	0	1	0
1	$\frac{1}{7}$	1	1	1	2	0	5	3	3	1	..	1	0	1	0	0	1	0	1	1	0
2	$\frac{1}{5}$	1	1	1	2	0	4	3	2	2	..	1	0	0	1	0	1	0	1	1	0
3	$\frac{1}{5}$	4	2	1	3	0	3	2	2	1	..	0	1	0	1	0	1	0	1	0	1

	a	g	e	M	F	tr	st	f	f	fr	g	D	.	act	act	nu	nu	hi	hi	int	int	ro	ro
	e	d	e	av	u	ai	a	e	o	a	.	.	.	ivi	ivit	rs	rs	gh	gh	er	er	ma	ma
	u	u	e	el	dy	l	m	r	o	e	t	c	.	s_	_y	y_	y_	_n	_y	t_	t_	an	an
				ti	ti	u	r	e		i			.	no	es	no	s	_o	_es	no	ye	tic	ti
				e	e	s	e			e			.								s	_n	c_
													.									o	yes
4	1	3	3	1	2	0	4	3	2	1	.	.	.	1	0	0	1	0	1	1	0	1	0
6											.	.	.										

5 rows × 57 columns

In [4]:

```
# shuffle rows
d = d.sample(frac=1)
# split training and testing data
d_train = d[:500]
d_test = d[500:]

d_train_att = d_train.drop(['pass'], axis=1)
d_train_pass = d_train['pass']

d_test_att = d_test.drop(['pass'], axis=1)
d_test_pass = d_test['pass']

d_att = d.drop(['pass'], axis=1)
d_pass = d['pass']

# number of passing students in whole dataset:
import numpy as np
print("Passing: %d out of %d (%.2f%%)" % (np.sum(d_pass), len(d_pass), 100*float(np.sum(d_pass)) /
len(d_pass)))
Passing: 328 out of 649 (50.54%)
```

In [5]:

```
# fit a decision tree
from sklearn import tree
t = tree.DecisionTreeClassifier(criterion="entropy", max_depth=5)
t = t.fit(d_train_att, d_train_pass)
```

In [6]:

```
# visualize tree
import graphviz
```

```
dot_data = tree.export_graphviz(t, out_file=None, label="all", impurity=False, proportion=True,
                                feature_names=list(d_train_att), class_names=["fail", "pass"],
                                filled=True, rounded=True)
graph = graphviz.Source(dot_data)
graph
```

Out[6]:

```
b'\n'
```

In [7]:

```
# save tree
tree.export_graphviz(t, out_file="student-performance.dot", label="all", impurity=False,
                    proportion=True,
                    feature_names=list(d_train_att), class_names=["fail", "pass"],
                    filled=True, rounded=True)
```

In [8]:

```
t.score(d_test_att, d_test_pass)
```

Out[8]:

```
0.59731543624161076
```

In [9]:

```
from sklearn.model_selection import cross_val_score
scores = cross_val_score(t, d_att, d_pass, cv=5)
# show average score and +/- two standard deviations away (covering 95% of scores)
print("Accuracy: %0.2f (+/- %0.2f)" % (scores.mean(), scores.std() * 2))

Accuracy: 0.67 (+/- 0.06)
```

In [10]:

```
for max_depth in range(1, 20):
    t = tree.DecisionTreeClassifier(criterion="entropy", max_depth=max_depth)
    scores = cross_val_score(t, d_att, d_pass, cv=5)
    print("Max depth: %d, Accuracy: %0.2f (+/- %0.2f)" % (max_depth, scores.mean(), scores.std() * 2))
```

```
Max depth: 1, Accuracy: 0.64 (+/- 0.05)
Max depth: 2, Accuracy: 0.69 (+/- 0.08)
Max depth: 3, Accuracy: 0.69 (+/- 0.09)
Max depth: 4, Accuracy: 0.66 (+/- 0.10)
Max depth: 5, Accuracy: 0.67 (+/- 0.06)
Max depth: 6, Accuracy: 0.64 (+/- 0.08)
Max depth: 7, Accuracy: 0.67 (+/- 0.02)
Max depth: 8, Accuracy: 0.67 (+/- 0.07)
Max depth: 9, Accuracy: 0.67 (+/- 0.06)
Max depth: 10, Accuracy: 0.63 (+/- 0.12)
Max depth: 11, Accuracy: 0.65 (+/- 0.07)
Max depth: 12, Accuracy: 0.63 (+/- 0.07)
Max depth: 13, Accuracy: 0.63 (+/- 0.07)
Max depth: 14, Accuracy: 0.63 (+/- 0.08)
Max depth: 15, Accuracy: 0.64 (+/- 0.06)
Max depth: 16, Accuracy: 0.62 (+/- 0.05)
Max depth: 17, Accuracy: 0.64 (+/- 0.09)
Max depth: 18, Accuracy: 0.63 (+/- 0.08)
```

Max depth: 19, Accuracy: 0.63 (+/- 0.06)

In [11]:

```
depth_acc = np.empty((19,3), float)
i = 0
for max_depth in range(1, 20):
    t = tree.DecisionTreeClassifier(criterion="entropy", max_depth=max_depth)
    scores = cross_val_score(t, d_att, d_pass, cv=5)
    depth_acc[i,0] = max_depth
    depth_acc[i,1] = scores.mean()
    depth_acc[i,2] = scores.std() * 2
    i += 1
```

depth\_acc

Out[11]:

```
array([[ 1.    , 0.63790456, 0.04848398],
       [ 2.    , 0.68559869, 0.07148267],
       [ 3.    , 0.68710174, 0.0865951 ],
       [ 4.    , 0.6669467 , 0.10726248],
       [ 5.    , 0.66261518, 0.05307124],
       [ 6.    , 0.65018859, 0.07040891],
       [ 7.    , 0.66564494, 0.02029519],
       [ 8.    , 0.67474598, 0.05984916],
       [ 9.    , 0.6640118 , 0.03746891],
       [10.    , 0.6346137 , 0.09657669],
       [11.    , 0.6484015 , 0.10475147],
       [12.    , 0.64545485, 0.05529647],
       [13.    , 0.64544256, 0.08167465],
       [14.    , 0.6346614 , 0.07458128],
       [15.    , 0.63463773, 0.08162646],
       [16.    , 0.62853141, 0.05926906],
       [17.    , 0.63622335, 0.05390067],
       [18.    , 0.62548936, 0.06050112],
       [19.    , 0.63004547, 0.07022296]])
```

In [12]:

```
import matplotlib.pyplot as plt
fig, ax = plt.subplots()
ax.errorbar(depth_acc[:,0], depth_acc[:,1], yerr=depth_acc[:,2])
plt.show()
```

In [ ]