INTERNETOFTHINGS

GAS LEAKAGE MONITORINGANDALERTINGSYSTEMFOR INDUSTRIES

IBMProject–TeamID:PNT2022TMID46919

TeamLeader

sivaneskumar-821819104303

TeamMembers

Anuja.g 821819104301

BACHELOROFENGINEERING

In

COMPUTER SCIENCE

SMR EAST COAST

COLLEGE OF ENGINEERING AND

TECHNOLOGY

ANNAUNIVERSITY:CHENNAI 600025

ABSTRACT

Thepresenceofhazardousgasleakageinindustries,also,storedgasescontainergas which exhibits ideal characteristic is use. For that sake, an alarm unit is usedtovibrateanalarmwhichisbuzzer.Buzzergivesanaudiblesignofthepresenceofg asvolume.Thesensorsarewidelyused to detect essence ofpropane, iso-butane and even smoke. The sensor has an advantage to combine asensitivity response time. If the gas sensor senses gas leak, sensor output goes toactive low (logic-0) condition. Arduino UNO is used in the project; low signalsare overlooked by the Arduino and gas leakage is been noticed by the Arduino.The Arduino UNO turns on the LCD and buzzer. It even turns on the GSMmodemafterthat,itcontinuestosendmessagesSMStomobilenumberspecifical ly mentioned in the program of the source code for alerting danger tothepeople.

LITERATUREREVIEW

Survey1:

Pal-StefanMurvay,IoanSilea(2012)

'JournalofLossPreventioninthe ProcessIndustries'

The main purpose of this paper is to identify the state-of-the-art in leak detection andlocalization methods. Additionally we evaluate the capabilities of these techniques in order toidentify the advantages and disadvantages of using each leak detection solution.

Survey2:

Srinivasan,Leela,Jeyabharathi,Kirthik,Rajasree;(2014)‘ AdaptedapproachforSpeciesClassification’

In this research paper they told about gas leakage detection and control. In this paper,the gas leakage resulting into fatal inferno has become a serious problem in household andotherareaswherehouseholdgasishandledandused. It alerts the subscriber through thealarm and the status display besides turning off the gas supply valve as a primary safetymeasure.Thissimplicityresultsinahighinstructionturnoutandspectacularrealtimeinterrupt response from a tiny and cost-efficient processor core. The microcontroller providesthe data to the coil valve to shut its knob. The coil valve consists of a disc that's in touch withthe spring. Once the gas leaks the disc comes in touch with the spring so it stops the flow ofgas. Finally the gases area unit thrown out the disc moves so the gas flows. At that point thebuzzer starts direful thereby to alert the neighbors. A Buzzer or electronic device is a signaldevice,typicallyelectronic,generallyused in cars, manage appliances.such as microwavekitchen appliance or game shows.

Survey3:

Prof.M.Amsaveni, A.Anurupa, R.S.AnuPreetha,

C.Malarvizhi,M.Gunasekaran;(2015)

“GSMbasedLPGleakagedetectionandcontrollingsystem”

They proposed their methodology that the system takes an automatic control actionafter the detection of 0.001% of Gas leakage. This automatic control action provides amechanicalhandleforclosingthevalve.Weareincreasingthesecurityforhumanbymeansof a relay which will shut down the electric power to the house. Also by using GSM, we aresending an alert message to the users and a buzzer is provided for alerting the neighbors about the leakage.

Survey4:

VSuma,RamyaRShekar,

KumarAAkshay(2019)'GasLeakageDetectionBase

donIOT'

The aim of this paper is to present a new system automatically books a cylinder whenthe gas is about to empty is by sending a notification to the gas agency using wifi usingInternet ofThings approach.

Survey5:

AdilAhmad,ShaikShaheeda

DepartmentofInformationScienceandEngineering,BengaluruGasLeakageD etectionBasedSystem(ICEA2017).

TheauthorhasobservedgasleakageandLPGlevelswheregasleakageoccursautomatically. The authors suggests that gas leakage is performed by various gas sensors.Whose author has worked on gas leaks and mentions thatwe can take care if a found using asensor and gas booking can be done automatically when a small amount of gas istakenclosed.

Survey6:

MohdAbidPGstudent

Design and Embedded system, VTU PG centre kalaburagi, India IJETERvolume6,issue4,April(2018).

Through this paper importantparameters are used to find the level of gas in thecontainer. The good purpose of this project is to get notification of gasleak to user when gasleakage is started. Arduino was originally created as a tool for fast sampling and activities forstudents with no knowledge for electronics. This paper uses a microcontroller, buzzer and agas sensor to detect gas leakage system. When a gas leak is detected by a gas sensor ,themicrocontroller turn on the buzzer in critical condition.The author suggest that this messageor instruction may be displayed using an LCD display for LPG monitoring.

Survey7:

Kulothungan. S, Gukan. A , Arunprabu.K.BStudent,IFETCollegeofEngineering.

IJEDR2019.

The proposed system detects LPG leaks and alerts customers. The alarm starts whenthe system notice andincreases in LPG leakage concentration by sending an alarm andsendingamessagetospecificmobilephone.Thedeviceassuressafetyandpreventsexplosions. A microcontroller based system based on gas sensor(MQ6) has been developed inproposed system to detect LPG leakage.The unit is also integrated with an alarm unit todetect signal a leak.

REFERENCES

1. Pal-StefanMurvay,IoanSilea
   'JournalofLossPreventionintheProcessIndustries'-2012
2. Srinivasan,Leela,Jeyabharathi,Kirthika,Rajasree
   "GASLEAKAGEDETECTIONANDCONTROL"ScientificJournalofImpactFactor(SJIF):3.134March-2014.
3. Prof.M.Amsaveni,A.Anurupa,R.S.AnuPreetha,C.Malarvizhi,M.Gunasekaran
   "Gsm based LPG leakage detection and controlling system" the International Journalof Engineering and Science (IJES) ISSN (e): 2319 – 1813 ISSN (p): 2319 – 1805 Pages112-116March-2015'
4. VSuma, Ramya R Shekar, KumarAAkshay
   'GasLeakageDetectionBasedonIOT'-2019
5. AdilAhmad,ShaikShaheeda.
   BengaluruGasLeakageDetectionBasedSystem(ICEA2017).
6. MohdAbid PGstudent Dept ofVLSI Design andEmbedded system.
   VTUPGcentrekalaburagi,IndiaIJETERvolume6,issue4,April(2018).
7. Kulothungan. S, Gukan. A , Arunprabu.K.B Associate
   Professor.Student,IFETCollegeofEngineering.IJEDR20
   19