

NAME : HARIRAJ S

REG NO : 210619205014

COLLEGE: JEPPIAAR INSTITUTE OF TECHNOLOGY

```
#include  
<Servo.h>
```

```
int output1Value = 0;  
int sen1Value = 0;  
int sen2Value = 0;  
int const gas_sensor = A1;  
int const LDR = A0;  
int limit = 400;  
  
long readUltrasonicDistance(int triggerPin, int echoPin)  
{  
    pinMode(triggerPin, OUTPUT); // Clear the trigger  
    digitalWrite(triggerPin, LOW);  
    delayMicroseconds(2);  
    // Sets the trigger pin to HIGH state for 10 microseconds  
    digitalWrite(triggerPin, HIGH);  
    delayMicroseconds(10);  
    digitalWrite(triggerPin, LOW);  
    pinMode(echoPin, INPUT);  
    // Reads the echo pin, and returns the sound wave travel time in microseconds  
    return pulseIn(echoPin, HIGH);  
}  
  
Servo servo_7;  
  
void setup()  
{  
    Serial.begin(9600); //initialize serial communication  
    pinMode(A0, INPUT); //LDR  
    pinMode(A1, INPUT); //gas sensor  
    pinMode(13, OUTPUT); //connected to relay  
    servo_7.attach(7, 500, 2500); //servo motor
```

```

pinMode(8,OUTPUT);          //signal to piezo buzzer
pinMode(9, INPUT);          //signal to PIR
pinMode(10, OUTPUT);         //signal to npn as switch
pinMode(4, OUTPUT);          //Red LED
pinMode(3, OUTPUT);          //Green LED

}

void loop()
{

    //-----light intensity control-----//
    //-----
    int val1 = analogRead(LDR);
    if (val1 > 500)
    {
        digitalWrite(13, LOW);
        Serial.print("Bulb ON = ");
        Serial.print(val1);
    }
    else
    {
        digitalWrite(13, HIGH);
        Serial.print("Bulb OFF = ");
        Serial.print(val1);
    }

    //-----
    //----- light & fan control-----//
    //-----
    sen2Value = digitalRead(9);
    if (sen2Value == 0)
    {
        digitalWrite(10, LOW); //npn as switch OFF
        digitalWrite(4, HIGH); // Red LED ON, indicating no motion
        digitalWrite(3, LOW); //Green LED OFF, since no Motion detected
        Serial.print("    || NO Motion Detected    ");
    }
}

```

```

if (sen2Value == 1)
{
    digitalWrite(10, HIGH);//npn as switch ON
    delay(3000);
    digitalWrite(4, LOW); // RED LED OFF
    digitalWrite(3, HIGH);//GREEN LED ON , indicating motion detected
    Serial.print("    || Motion Detected!    ");
}
delay(300);

//-----
// ----- Gas Sensor -----//
//-----

int val = analogRead(gas_sensor);    //read sensor value
    Serial.print("|| Gas Sensor Value = ");
    Serial.print(val);                //Printing in serial monitor
//val = map(val, 300, 750, 0, 100);
if (val > limit)
{
    tone(8, 650);
}
delay(300);
noTone(8);

//-----
//----- servo motor -----//
//-----

sen1Value = 0.01723 * readUltrasonicDistance(6, 6);

if (sen1Value < 100)
{
    servo_7.write(90);
    Serial.print("    || Door Open! ; Distance = ");
    Serial.print(sen1Value);
    Serial.print("\n");

}
else
{
    servo_7.write(0);
    Serial.print("    || Door Closed! ; Distance = ");

```

```
    Serial.print(sen1Value);  
    Serial.print("\n");  
}  
delay(10); // Delay a little bit to improve simulation performance  
}
```