

Assignment Date	25 October 2022
Student Name	K.Madheshwaran
Student Roll Number	811519106077
Maximum Marks	2 Marks

ASSIGNMENT-4

Problem Statement:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send "alert" to IBM cloud and display in device recent events.

Source Code:

```
#include <WiFi.h>
#include <PubSubClient.h>
void callback(char* subscribetopic,byte* payload, unsigned int payloadLength);
#define ORG "p4s6t5"
#define DEVICE_TYPE "Ultrasonic_Sensor_ESP32"
#define DEVICE_ID "1923"
#define TOKEN "12345678"
String data3;
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/distance/fmt/json";
char subscribeTopic[] = "iot-2/cmd/test/fmt/String";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientID[] = "d:"ORG":DEVICE_TYPE":DEVICE_ID;
WiFiClient wifiClient;
PubSubClient client(server,1883,callback,wifiClient);
#define ECHO_PIN 12
#define TRIG_PIN 13
#define led 2
void setup() {
// put your setup code here, to run once:
Serial.begin(115200);
pinMode(led, OUTPUT);
pinMode(TRIG_PIN, OUTPUT);
pinMode(ECHO_PIN, INPUT);
wificonnect();
mqttconnect();
}
```

```

float readDistanceCM() {
digitalWrite(TRIG_PIN, LOW); // Clear the trigger
delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH); // Sets the trigger pin to HIGH state for 10
microseconds
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
int duration=pulseIn(ECHO_PIN, HIGH);
//Serial.println(duration);
//duration = pulseIn(ECHO_PIN, HIGH);
return duration*0.017;
//Serial.println(duration);
}
void loop() {
float distance = readDistanceCM();
//Serial.println(distance);
bool isNearby = distance < 100;
digitalWrite(led, isNearby);
Serial.print("Measured distance: ");
Serial.println(distance);
if(distance<100){
PublishData2(distance);
}else{
PublishData1(distance);
}
//PublishData(distance);
delay(1000);
if(!client.loop()){
mqttconnect();
}
//delay(2000);
}
void PublishData1(float dist){
mqttconnect();
String payload= "{\"distance\":\"";
payload += dist;
payload+="}";
Serial.print("Sending payload:");
Serial.println(payload);
if(client.publish(publishTopic, (char*)payload.c_str())){
Serial.println("publish ok");
} else{
Serial.println("publish failed");
}
}
}

```

```

void PublishData2(float dist){
  mqttconnect();
  String payload= "{\"ALERT\":";
  payload += dist;
  payload+="}";
  Serial.print("Sending payload:");
  Serial.println(payload);
  if(client.publish(publishTopic,(char*)payload.c_str())){
    Serial.println("publish ok");
  } else{
    Serial.println("publish failed");
  }
}

void mqttconnect(){
  if(!client.connected()){
    Serial.print("Reconnecting to ");
    Serial.println(server);
    while(!!!client.connect(clientID, authMethod, token)){
      Serial.print(".");
      delay(500);
    }
    initManagedDevice();
    Serial.println();
  }
}

void wificonnect(){
  Serial.println();
  Serial.print("Connecting to");
  WiFi.begin("Wokwi-GUEST","",6);
  while(WiFi.status()!=WL_CONNECTED){
    delay(500);
    Serial.print(".");
  }
  Serial.println("");
  Serial.println("WIFI CONNECTED");
  Serial.println("IP address:");
  Serial.println(WiFi.localIP());
}

void initManagedDevice(){
  if(client.subscribe(subscribeTopic)){
    Serial.println((subscribeTopic));
    Serial.println("subscribe to cmd ok");
  }else{
    Serial.println("subscribe to cmd failed");
  }
}

```

```

void callback(char* subscribeTopic, byte* payload, unsigned int
payloadLength){
  Serial.print("callback invoked for topic:");
  Serial.println(subscribeTopic);
  for(int i=0; i<payloadLength; i++){
    data3 += (char)payload[i];
  }
  Serial.println("data:" + data3);
  if(data3=="lighton"){
    Serial.println(data3);
    digitalWrite(led,HIGH);
  }else{
    Serial.println(data3);
    digitalWrite(led,LOW);
  }
  data3="";
}

```

Wokwi Link:

<https://wokwi.com/projects/346334151941554770>

Normal and Alert case:

The screenshot displays the Wokwi IDE interface. On the left, the code for 'esp32-blink.ino' is shown, which includes the necessary libraries, defines the sensor and device details, and implements the logic for reading distance and publishing it. The right side shows a simulation of the hardware setup, including the ESP32, the HC-SR04 ultrasonic sensor, and a red LED. Below the simulation, the serial output log shows the successful execution of the code, including distance measurements and payload publishing.

WOKWI

esp32-blink.ino

```

1 #include <wifi.h>
2 #include <PubSubClient.h>
3 void callback(char* subscribetopic,byte* payload,unsigned int payloadLength);
4 #define ORG "p4s6t5"
5 #define DEVICE_TYPE "Ultrasonic_Sensor_ESP32"
6 #define DEVICE_ID "1923"
7 #define TOKEN "12345678"
8 String data3;
9 char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
10 char publishTopic[] = "iot-2/evt/distance/fmt/json";
11 char subscribetopic[] = "iot-2/cmd/test/fmt/string";
12 char authMethod[] = "use-token-auth";
13 char token[] = TOKEN;
14 char clientId[] = "d:ORG:"DEVICE_TYPE:"DEVICE_ID";
15 WiFiClient wificlient;
16 PubSubClient client(server,1883,callback,wificlient);
17 #define ECHO_PIN 12
18 #define TRIG_PIN 13
19 #define led 2
20 void setup() {
21 // put your setup code here, to run once:
22 Serial.begin(115200);
23 pinMode(led, OUTPUT);
24 pinMode(TRIG_PIN, OUTPUT);
25 pinMode(ECHO_PIN, INPUT);
26 wificlient.connect();
27 mqttconnect();
28 }
29 float readDistanceCM() {
30 digitalWrite(TRIG_PIN, LOW); // Clear the trigger
31 delayMicroseconds(2);
32 digitalWrite(TRIG_PIN, HIGH); // Sets the trigger pin to HIGH state for 10 microseconds
33 delayMicroseconds(10);
34 digitalWrite(TRIG_PIN, LOW);
35 int duration=pulseIn(ECHO_PIN, HIGH);

```

Simulation

Editing Ultrasonic Distance Sensor

Distance: 54cm

publish ok
Measured distance: 53.99
Sending payload:{"ALERT":53.99}
publish ok
Measured distance: 53.99
Sending payload:{"ALERT":53.99}
publish ok

IBM Cloud Storage

IBM Watson IoT Platform

2019504577@smartinternz.com
ID: p4s6t5

Browse Action Device Types Interfaces

Add Device

Search by Device ID

Device Simulator

Device ID	Status	Device Type	Class ID	Date Added	Descriptive Location
1923	Disconnected	Ultrasonic_Sensor_ESP32	Device	Oct 23, 2022 10:24 PM	

Identity	Device Information	Recent Events	State	Logs
The recent events listed show the live stream of data that is coming and going from this device.				
Event	Value	Format	Last Received	
distance	{"distance":326.98}	json	a few seconds ago	
distance	{"distance":326.98}	json	a few seconds ago	
distance	{"distance":326.98}	json	a few seconds ago	
distance	{"ALERT":53.99}	json	a few seconds ago	
distance	{"ALERT":53.96}	json	a few seconds ago	