Creating a Node-Red Web Application to view data in Separate Numerical form

Date	07 November 2022
Team ID	PNT2022TMID01909
Project Name	Project - Gas Leakage Monitoring and Alerting System for Industries.

- In IBM cloud dashboard, click on Cloud Foundry apps



- A new window appears where we need to NODE-RED SELDZ app created before.



- Click on Visit App URL in Node RED SELDZ service dashboard.



Click on your Node-RED flow editor where you will be redirected to the Node-RED flow editor.




WhatsApp
IBM
IoT-B2-2M4E (Morning Session)-
SmartHomeAutomationusingIBM
Node-RED
127.0.0.1:1880/#flow/b47948623bf1c79f
Node-RED
Deploy
filter nodes
Flow 1
common
inject
debug
complete
catch
status
link in
link call
link out
comment
function
function
switch
change
range
info
Search flows
Flows
Flow 1
Subflows
Global Configuration Nodes
Flow 1
Flow
"b47948623bf1c79f"
Move the selected nodes using the
and keys. Hold to nudge
them further
Activate Windows
Go to Settings to activate Windows.
Type here to search
25°C Cloudy
ENG
20:33
03-11-2022

- To install IBM nodes in Node-red flow editor click on manage palette in the menu option which is on the top-right of the screen.



- In install section search for ibmiot and install the ibm nodes to flow editor.



Search for IBM nodes in the filter nodes section



- To Retrieve the data from the IBM IoT platform by using Node-RED IBM IoT Input node and double click on the IBM IoT input node



Select API Key from Authentication in properties.

- In API Key paste API Key, API Token and server name and update it



- Also update your input type as event, Device type, Device ID, command and format in the propertiees section and click on Done

- **To generate API Key go to IBM IoT platform**
- In Apps Section -> Click onGenerate API Key



- Click on Deploy option to check the connection status. If the status is disconnected check for IBM IoT properties and try again.



- Place the debug node in the flow editor and click on deploy to see the temperature and humidity value in the debug tab



- Install the dashboard node from the manage pallet to create a UI to display temperature and humidity values in the Dashboard



- Drag and place the function node ang gauge node in the flow editor to separate the temperature and humidity value



- Double click on function and update the details as follow, ○ Type msg.payload=msg.payload.Temperature in one function.
- Type msg.payload=msg.payload.Humidity in another function
- Type msg.payload=msg.payload.HazardousGas
- Type msg.payload=msg.payload.d.Pressure
- To separate the humidity and temperature values from payload and click deploy

-



Select gauge function and these nodes to temperature, pressure, hazardous gas and humidity



- Edit temperature, hazardous gas, pressure and humidity nodes and deploy it.



- After editing the nodes, deploy it



RESULT:

Thus, the Node-Red Web Application is created successfully.