

# **INTERNET OF THINGS**

## **GAS LEAKAGE MONITORING AND ALERTING SYSTEM**

Team members

Team Lead : SYED IBRAHIM R

TEAM MEMBER1 : GUNENDRA PRASANTH S

TEAM MEMBER2 : HARISHANKAR N

TEAM MEMBER 3 : ESHWAR S H

Of

BACHELOR OF

ELECTRONICS AND COMMUNICATION ENGINEERING

IN

BANNARI AMMAN INSTITUTE OF TECHNOLOGY, SATHYAMANGALAM  
LITERATURE SURVEY

### **Survey 1:**

**A. Mahalingam, r. T. Naayagi, n. E. Mastorakis;** they introduce design and implementation of an economic gas leakage detector. They gave the formulation of many problems in previous gas leakage detectors. They told that several standards have been formulated for the design of a gas leakage detection system such as IEEE, BS 5730, and IEC. For this work, the recommended UK safety standards have been

adopted. The proposed alarm system is mainly meant to detect LPG leakage, which is most commonly used in residential and commercial premises. The system detects not only the presence of gas (gas leak), but also the amount of leakage in the air, and accordingly raises an appropriate audio visual alarm. The objective of the system is to detect LPG gases such as propane and butane. The allowed UK level for butane is 600 ppm above which it is considered to be of high level and poses a danger. The proposed system ensures a continuous monitoring of the gas levels. If the gas level increases above the normal threshold level of 400 ppm butane (LPG), the system starts to issue early warning alarms at 100ms interval, which implies low level gas leakage.

### **Survey 2:**

**Prof. M.Amsaveni, A.Anurupa, R.S.Anu Preetha, C.Malarvizhi, M.Gunasekaran;** their research paper on “GSM based LPG leakage detection and controlling system” the leakage of LPG gas is detected by the MQ-6 gas sensor. Its analog output is given to the microcontroller. It consists of predefined instruction set. Based on this, the exhaust fan is switched on. So, the concentration of gas inside the room gets decreased. Then, the stepper motor is rotated thus closing the knob of the cylinder. Because of this process, the leakage of gas is stopped. The relay is switched to off the power supply of the house. The buzzer produces an alarm to indicate the gas leakage. Then, the user is alerted by SMS through the GSM module. They proposed their methodology that the system takes an automatic control action after the detection of 0.001% of LPG leakage. This automatic control action provides a mechanical handle for closing the valve.

### **Survey 3:**

**Pal-Stefan Murvaya, Ioan Sileaa, 2008,** they told in their survey on gas leak detection and localization techniques various ways to detect the gas leakage. They introduce some old or new technique to detect the gas. The proposed techniques in this paper are nontechnical methods, hardware based methods which include acoustic methods, optical methods and active methods. In their survey they told a wide variety of leak detecting techniques is available for gas pipelines. Some techniques have been improved since their first proposal and some new ones were designed as a result of advances in sensor manufacturing and computing power.

However, each detection method comes with its advantages and disadvantages. Leak detection techniques in each category share some advantages and disadvantages. For example, all external techniques which involve detection done from outside the pipeline by visual observation or portable detectors are able to detect very small leaks and the leak location, but the detection time is very long. Methods based on the mathematical model of the pipe have good results at high flow rates while at low flow rates a mass balance based detection system would be more suitable. This disadvantage is prone to disappear for some of these techniques due to forthcoming technological advancements.

#### **Survey 4:**

**Chandana R , Nandini R , Dr. T P Surekha**, have proposed a system that along with monitoring and detection of gas leakage, real time data is made available through real time feed over internet They have used Xively IOT platform to provide real time sensor data over the internet.

#### **Survey 5:**

**Ch. Manohar Raju and N. Sushma Rani, 2008**, they introduce an android based automatic gas detection and indication robot. They proposed prototype depicts a mini mobile robot which is capable to detect gas leakage in hazardous places. Whenever there is an occurrence of gas leakage in a particular place the robot immediately read and sends the data to android mobile through wireless communication like Bluetooth. We develop an android application for android based smartphones which can receive data from robot directly through Bluetooth. The application warns with an indication whenever there is an occurrence of gas leakage and we can also control the robot movements via Bluetooth by using text commands as well as voice commands. The previous mobile robots are based on heterogeneous technologies like GSM, GPS, internet based etc., **Survey 6:**

**P.Meenakshi Vidya, S.Abinaya, G.Geetha Rajeswari, N.Guna**, Automatic LPG detection and hazard controlling published in April 2014 proposed the leakage detection and real time gas monitoring system. In this system, the gas leakage is detected and controlled by means of exhaust fan. The level of LPG in cylinder is also continuously monitored