

ASSIGNMENT-4

DISTANCE DETECTION USING ULTRASONIC SENSOR

| | |
|---------------------|------------------|
| Date | 08 November 2022 |
| Team ID | PNT2022TMID10960 |
| Name | M.ANDAL |
| Student Roll Number | 811519106009 |
| Maximum Marks | 2 Marks |

Question1 :

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send "alert" to ibm cloud and display in device recent events.

CODE :

```

1  #include <WiFi.h> //library for wifi
2  #include <PubSubClient.h> //library for MQTT
3
4
5  void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
6
7 //-----credentials of IBM Accounts-----
8
9  #define ORG "4hne0jp" //IBM ORGANITION ID
10 #define DEVICE_TYPE "ULTRASONIC" //Device type mentioned in ibm watson IOT Platform
11 #define DEVICE_ID "DISTANCEDETECT" //Device ID mentioned in ibm watson IOT Platform
12 #define TOKEN "wuo5s7PR)ZSegVk&Rx" //Token
13 String data3;
14 float dist;
15
16
17 //----- Customise the above values -----
18 char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // Server Name
19 char publishtopic[] = "iot-2/evt/data/fmt/json"; // topic name and type of event perform and format in which data to be send
20 char subscribetopic[] = "iot-2/cmd/test/fmt/string"; // cmd REPRESENT command type AND COMMAND IS TEST OF FORMAT STRING
21 char authMethod[] = "use-token-auth"; // authentication method
22 char token[] = TOKEN;
23 char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID; //client id
24
25
26 //-----
27 WiFiClient wifiClient; // creating the instance for wifiClient
28 PubSubClient client(server, 1883, callback, wifiClient); //calling the predefined client id by passing parameter like server id, port and wifi credential
29
30 int LED = 4;
31 int trig = 5;
32 int echo = 18;
33 void setup()
34 {
35   Serial.begin(115200);

```

```
esp32-blink.ino • diagram.json • libraries.txt • Library Manager ▾
36 pinMode(trig,OUTPUT);
37 pinMode(echo,INPUT);
38 pinMode(LED, OUTPUT);
39 delay(10);
40 wifiConnect();
41 mqttConnect();
42 }
43 void loop()// Recursive Function
44 {
45
46 digitalWrite(trig,LOW);
47 digitalWrite(trig,HIGH);
48 delayMicroseconds(10);
49 digitalWrite(trig,LOW);
50 float dur = pulseIn(echo,HIGH);
51 float dist = (dur * 0.0343)/2;
52 Serial.print ("Distancein cm");
53 Serial.println(dist);
54
55
56 PublishData(dist);
57 delay(1000);
58 if (!client.loop()) {
59   mqttConnect();
60 }
61 }
62
63
64
65 /*.....retrieving to Cloud.....*/
66
67 void PublishData(float dist) {
68   mqttConnect(); //function call for connecting to ibm
69   /*
70   || creating the String in form JSON to update the data to ibm cloud
```

```

70     , // creating the String in in form JSON to update the data to ibm cloud
71     */
72     String object;
73     if (dist <100)
74     {
75         digitalWrite(LED,HIGH);
76         Serial.println("object is near");
77         object = "Near";
78     }
79     else
80     {
81         digitalWrite(LED,LOW);
82         Serial.println("no object found");
83         object = "No";
84     }
85
86     String payload = "{\"distance\":";
87     payload += dist;
88     payload += "," "\"object\":\"";
89     payload += object;
90     payload += "}";
91
92
93     Serial.print("Sending payload: ");
94     Serial.println(payload);
95
96
97
98

```

```

esp32-blink.ino • diagram.json • libraries.txt • Library Manager ▾
98
99     if (client.publish(publishTopic, (char*) payload.c_str())) {
100        Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will print publish ok in Serial monitor or else it will print publish failed
101    } else {
102        Serial.println("Publish failed");
103    }
104
105 }
106 void mqttconnect() {
107     if (!client.connected()) {
108         Serial.print("Reconnecting client to ");
109         Serial.println(server);
110         while (!client.connect(clientId, authMethod, token)) {
111             Serial.print(".");
112             delay(500);
113         }
114
115         initManagedDevice();
116         Serial.println();
117     }
118 }
119 void wificonnect() //function defination for wificonnect
120 {
121     Serial.println();
122     Serial.print("Connecting to ");
123
124     WiFi.begin("Wokwi-GUEST", "", 6); //passing the wifi credentials to establish the connection
125     while (WiFi.status() != WL_CONNECTED) {
126         delay(500);
127         Serial.print(".");
128     }
129     Serial.println("");
130     Serial.println("Wifi connected");
131     Serial.println("IP address: ");
132     Serial.println(WiFi.localIP());

```

```
esp32-blink.ino • diagram.json • libraries.txt • Library Manager ▾
123
124     WiFi.begin("Wokwi-GUEST", "", 6); //passing the wifi credentials to establish the connection
125     while (WiFi.status() != WL_CONNECTED) {
126         delay(500);
127         Serial.print(".");
128     }
129     Serial.println("");
130     Serial.println("WiFi connected");
131     Serial.println("IP address: ");
132     Serial.println(WiFi.localIP());
133 }
134
135 void initManagedDevice() {
136     if (client.subscribe(subscribetopic)) {
137         Serial.println((subscribetopic));
138         Serial.println("subscribe to cmd OK");
139     } else {
140         Serial.println("subscribe to cmd FAILED");
141     }
142 }
143
144 void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
145
146     Serial.print("callback invoked for topic: ");
147     Serial.println(subscribetopic);
148     for (int i = 0; i < payloadLength; i++) {
149         //Serial.print((char)payload[i]);
150         data3 += (char)payload[i];
151     }
152
153 //    Serial.println("data: " + data3);
154 //    if(data3=="Near")
155 //    {
156 //        Serial.println(data3);
157 //        // do something here
158 //    }
```

```
esp32-blink.ino • diagram.json • libraries.txt • Library Manager ▾  
142 }  
143  
144 void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)  
145 {  
146  
147     Serial.print("callback invoked for topic: ");  
148     Serial.println(subscribetopic);  
149     for (int i = 0; i < payloadLength; i++) {  
150         //Serial.print((char)payload[i]);  
151         data3 += (char)payload[i];  
152     }  
153  
154     //    Serial.println("data: " + data3);  
155     //    if(data3=="Near")  
156     //    {  
157     //        Serial.println(data3);  
158     //        digitalWrite(LED,HIGH);  
159     //    }  
160     //  
161     //    else  
162     //    {  
163     //        Serial.println(data3);  
164     //        digitalWrite(LED,LOW);  
165     //    }  
166     //  
167     data3="";  
168  
169  
170 }  
171 }
```

OUTPUT:

```

esp32-blink.ino ● diagram.json ● libraries.bd ● Library Manager
1 #include <WiFi.h> //Library for wifi
2 #include <PubSubClient.h> //Library for MQTT
3
4
5 void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
6
7 //-----credentials of IBM Accounts-----
8
9 #define ORG "4hn0jp"//IBM ORGANIZATION ID
10 #define DEVICE_TYPE "ULTRASON"//Device type mentioned in ibm watson IOT Platform
11 #define DEVICE_ID "DISTANCEDECTCT"//Device ID mentioned in ibm watson IOT Platform
12 #define TOKEN "wuo5s7PRjZsegVk&Rx"//Token
13 String data3;
14 float dist;
15
16
17 //----- Customise the above values -----
18 char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
19 char publishTopic[] = "iot-2/evt/data/fmt/json"; // topic name and type of event perform and form
20 char subscribeTopic[] = "iot-2/cmd/test/fmt/String"; // cmd REPRESENT command type AND COMMAND I
21 char authMethod[] = "use-token-auth"; // authentication method
22 char token[] = TOKEN;
23 char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
24
25
26 //-----
27 WiFiClient wifiClient; // creating the instance for wifiClient
28 PubSubClient client(server, 1883, callback ,wifiClient); //calling the predefined client id by
29
30 int LED = 4;
31 int trig = 5;
32 int echo = 18;
33 void setup()
34 {
35   Serial.begin(115200);

```

Simulation
00:18.152 98%


HC-SR04
ESP32
no object found
Sending payload: {"distance":141.21,"object":"No"}
Publish ok
Distancein cm141.21
no object found
Sending payload: {"distance":141.21,"object":"No"}
Publish ok

Data send to the IBM cloud device when the object is far

| Event | Value | Format | Last Received |
|-------|-----------------------------------|--------|-------------------|
| Data | {"distance":141.21,"object":"No"} | json | a few seconds ago |
| Data | {"distance":141.21,"object":"No"} | json | a few seconds ago |
| Data | {"distance":141.21,"object":"No"} | json | a few seconds ago |
| Data | {"distance":141.18,"object":"No"} | json | a few seconds ago |
| Data | {"distance":141.2,"object":"No"} | json | a few seconds ago |

Items per page 50 | 1-2 of 2 items 1 of 1 page < 1 >

when object is near to the ultrasonic sensor



Data sent to the IBM Cloud Device when the object is near

| Event | Value | Format | Last Received |
|-------|------------------------------------|--------|-------------------|
| Data | {"distance":79.66,"object":"Near"} | json | a few seconds ago |
| Data | {"distance":79.64,"object":"Near"} | json | a few seconds ago |
| Data | {"distance":79.66,"object":"Near"} | json | a few seconds ago |
| Data | {"distance":79.64,"object":"Near"} | json | a few seconds ago |
| Data | {"distance":79.66,"object":"Near"} | json | a few seconds ago |