SPRINT - 2

Date	16/11/2022
Team ID	PNT2022TMID10965
Project Name	Real-Time Water Quality
	Monitoring And Control System

CODING:

```
#include <ESP8266WiFi.h>
#include <PubSubClient.h>
WiFiClient wifiClient;

//Enter your network credentials below in ssid and password const char* ssid = " ";
const char* password = " ";

//Provide your IBM IOT Platform credentials
#define ORG ""
#define DEVICE_TYPE ""
#define DEVICE_ID ""
#define TOKEN ""
```

```
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/Data/fmt/json";
char topic[] = "iot-2/cmd/home/fmt/String"; // cmd REPRESENT command type AND COMMAND IS
TEST OF FORMAT STRING
char authMethod[] = "use-token-auth"; char
token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
void callback(char* topic, byte* payload, unsigned int payloadLength); PubSubClient
client(server, 1883, callback, wifiClient);
int publishInterval = 5000; // 30 seconds long
lastPublishMillis;
String data;
void setup()
 Serial.begin(9600);
 pinMode(D0, OUTPUT);
 wifiConnect(); mqttConnect();
void loop() {
 if (millis() - lastPublishMillis > publishInterval)
 {
  publishData();
  lastPublishMillis = millis(); }
```

```
if (!client.loop()) { mqttConnect();
 }
}
void wifiConnect() {
 Serial.print("Connecting to "); Serial.print(ssid);
 WiFi.begin(ssid,
                         password);
                                           while
                 != WL_CONNECTED)
 (WiFi.status()
 delay(500);
  Serial.print(".");
 Serial.print("nWiFi connected, IP address: "); Serial.println(WiFi.localIP());
}
void mqttConnect() {
 if (!client.connected()) {
  Serial.print("Reconnecting MQTT client to "); Serial.println(server); while
  (!client.connect(clientId, authMethod, token)) {
  Serial.print(".");
   delay(500);
  }
  initManagedDevice();
  Serial.println();
```

```
}
}
void initManagedDevice() {
 if (client.subscribe(topic)) {
  // Serial.println(client.subscribe(topic));
  Serial.println("subscribe to cmd OK");
 } else {
  Serial.println("subscribe to cmd FAILED");
}
void callback(char* topic, byte* payload, unsigned int payloadLength) {
 Serial.print("callback invoked for topic: ");
 Serial.println(topic);
 for (int i = 0; i < payloadLength; i++) {
  //Serial.print((char)payload[i]);
  data += (char)payload[i];
 }
 Serial.println("Data: " + data );
                      "lon")
      (data
 digitalWrite(D0, HIGH);
```

```
else if (data == "loff") { digitalWrite(D0,
  LOW);
 }
 data = "";
}
void publishData()
{
 int a = 10;
 Serial.print("Sample Value: ");
 Serial.println(a);
 String payload = \{\'''d\'': \{\'''data\'':"; payload\}
 += a;
 payload += "}}";
 Serial.print("\n");
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
  Serial.println("Publish OK");
 } else {
  Serial.println("Publish FAILED");
 }
```

}