

## ASSIGNMENT-4

### DISTANCE DETECTION USING ULTRASONIC SENSOR

Date	30 October 2022
Team ID	PNT2022TMID11082
Name	SOWNDARYA G
Student Roll Number	811519106141
Maximum Marks	2 Marks

#### Question1 :

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send "alert" to ibm cloud and display in device recent events.

#### WOKWI LINK :

<https://wokwi.com/projects/305566932847821378> CODE :

```

1 #include <WiFi.h> //library for wifi
2 #include <PubSubClient.h> //library for MQTT
3
4
5 void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
6
7 //-----credentials of IBM Accounts-----
8
9 #define ORG "4hn@jp" //IBM ORGANITION ID
10 #define DEVICE_TYPE "ULTRASON" //Device type mentioned in ibm watson IOT Platform
11 #define DEVICE_ID "DISTANCEDETECT" //Device ID mentioned in ibm watson IOT Platform
12 #define TOKEN "wuo5s7PR)ZSegVkkR&x" //Token
13 String data3;
14 float dist;
15
16
17 //----- Customise the above values -----
18 char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // Server Name
19 char publishTopic[] = "iot-2/evt>Data/fmt/json"; // topic name and type of event perform and format in which data to be send
20 char subscribeTopic[] = "iot-2/cmd/test/fmt/String"; // cmd REPRESENT command type AND COMMAND IS TEST OF FORMAT STRING
21 char authMethod[] = "use-token-auth"; // authentication method
22 char token[] = TOKEN;
23 char clientId[] = "d;" ORG ";" DEVICE_TYPE ":" DEVICE_ID; //client id
24
25
26 //-----
27 WiFiClient wifiClient; // creating the instance for wifiClient
28 PubSubClient client(server, 1883, callback, wifiClient); //calling the predefined client id by passing parameter like server id, port and wifi credential
29
30 int LED = 4;
31 int trig = 5;
32 int echo = 18;
33 void setup()
34 {
35 Serial.begin(115200);

```

```
esp32-blink.ino e    diagram    .json ●    libraries.txt ●    Library Manager ▾
36  pinMode(trig,OUTPUT);
37  pinMode(echo,INPUT);
38  pinMode(LED, OUTPUT);
39  delay(10);
40  wificonnect();
41  mqttconnect();
42 }
43 void loop()// Recursive Function
44 {
45
46  digitalWrite(trig,LOW);
47  digitalWrite(trig,HIGH);
48  delayMicroseconds(10);
49  digitalWrite(trig,LOW);
50  float dur = pulseIn(echo,HIGH);
51  float dist = (dur * 0.0343)/2;
52  Serial.print ("Distancein cm");
53  Serial.println(dist);
54
55
56  PublishData(dist);
57  delay(1000);
58  if (!client.loop()) {
59    mqttconnect();
60  }
61 }
62
63
64
65 /*.....retrieving to Cloud.....*/
66
67 void PublishData(float dist) {
68  mqttconnect(); //function call for connecting to ibm
69  /*
70   | | creating the String in in form JSON to update the data to ibm cloud
```

```

70     // creating the String in in form JSON to update the data to ibm cloud
71     /*
72     String object;
73     if (dist <100)
74     {
75         digitalWrite(LED,HIGH);
76         Serial.println("object is near");
77         object = "Near";
78     }
79     else
80     {
81         digitalWrite(LED,LOW);
82         Serial.println("no object found");
83         object = "No";
84     }
85
86     String payload = "{\"distance\":\"";
87     payload += dist;
88     payload += "," "object\":\"\"";
89     payload += object;
90     payload += "}";
91
92
93     Serial.print("Sending payload: ");
94     Serial.println(payload);
95
96
97
98

```

```

esp32-blink.ino • diagram.json • libraries.txt • Library Manager ▾
98
99     if (client.publish(publishTopic, (char*) payload.c_str())) {
100        Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will print publish ok in Serial monitor or else it will print publish failed
101    } else {
102        Serial.println("Publish failed");
103    }
104
105 }
106 void mqttconnect() {
107     if (!client.connected()) {
108         Serial.print("Reconnecting client to ");
109         Serial.println(server);
110         while (!client.connect(clientId, authMethod, token)) {
111             Serial.print(".");
112             delay(500);
113         }
114
115         initManagedDevice();
116         Serial.println();
117     }
118 }
119 void wificonnect() //function defination for wificonnect
120 {
121     Serial.println();
122     Serial.print("Connecting to ");
123
124     WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
125     while (WiFi.status() != WL_CONNECTED) {
126         delay(500);
127         Serial.print(".");
128     }
129     Serial.println("");
130     Serial.println("WiFi connected");
131     Serial.println("IP address: ");
132     Serial.println(WiFi.localIP());

```

```
esp32-blink.ino • diagram.json • libraries.txt • Library Manager ▾
123
124     WiFi.begin("Wokwi-GUEST", "", 6); //passing the wifi credentials to establish the connection
125     while (WiFi.status() != WL_CONNECTED) {
126         delay(500);
127         Serial.print(".");
128     }
129     Serial.println("");
130     Serial.println("WiFi connected");
131     Serial.println("IP address: ");
132     Serial.println(WiFi.localIP());
133 }
134
135 void initManagedDevice() {
136     if (client.subscribe(subscribetopic)) {
137         Serial.println((subscribetopic));
138         Serial.println("subscribe to cmd OK");
139     } else {
140         Serial.println("subscribe to cmd FAILED");
141     }
142 }
143
144 void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
145
146     Serial.print("callback invoked for topic: ");
147     Serial.println(subscribetopic);
148     for (int i = 0; i < payloadLength; i++) {
149         //Serial.print((char)payload[i]);
150         data3 += (char)payload[i];
151     }
152
153 //    Serial.println("data: " + data3);
154 //    if(data3=="Near")
155 //    {
156 //        Serial.println(data3);
157 //    }
158 //    // do something with data3
159 }
```

```
esp32-blink.ino • diagram.json • libraries.txt • Library Manager ▾
142 }
143
144 void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
145 {
146
147     Serial.print("callback invoked for topic: ");
148     Serial.println(subscribetopic);
149     for (int i = 0; i < payloadLength; i++) {
150         //Serial.print((char)payload[i]);
151         data3 += (char)payload[i];
152     }
153
154     //    Serial.println("data: " + data3);
155     //    if(data3=="Near")
156     //    {
157     //        Serial.println(data3);
158     //        digitalWrite(LED,HIGH);
159
160     //    }
161
162     //    else
163     //    {
164     //        Serial.println(data3);
165     //        digitalWrite(LED,LOW);
166
167     //    }
168     data3="";
169
170
171 }
```

## OUTPUT:

```

esp32-blink.ino ● diagram.json ● libraries.bd ● Library Manager
1 #include <WiFi.h>/library for wifi
2 #include <PubSubClient.h>/library for MQTT
3
4
5 void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
6 //-----credentials of IBM Accounts-----
7
8 #define ORG "4hn0jp"/IBM ORGANIZATION ID
9 #define DEVICE_TYPE "ULTRASONIC"/Device type mentioned in ibm watson IOT Platform
10 #define DEVICE_ID "DISTANCEDECTC"/Device ID mentioned in ibm watson IOT Platform
11 #define TOKEN "wuo5s7PRz5egvk&Rx"/Token
12
13 String data3;
14 float dist;
15
16
17 //----- Customise the above values -----
18 char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // Server Name
19 char publishTopic[] = "iot-2/evt/data/fmt/json"; // topic name and type of event perform and form
20 char subscribeTopic[] = "iot-2/cmd/test/fmt/string"; // cmd REPRESENT command type AND COMMAND I
21 char authMethod[] = "use-token-auth"; // authentication method
22 char token[] = TOKEN;
23 char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
24
25
26
27 WiFiClient wifiClient; // creating the instance for wifiClient
28 PubSubClient client(server, 1883, callback ,wifiClient); //calling the predefined client id by
29
30 int LED = 4;
31 int trig = 5;
32 int echo = 18;
33 void setup()
34 {
35   Serial.begin(115200);

```

Simulation window showing the circuit and publish logs:

- no object found
- Sending payload: {"distance":141.21,"object":"No"}
- Publish ok
- Distance in cm141.21
- no object found
- Sending payload: {"distance":141.21,"object":"No"}
- Publish ok

Data send to the IBM cloud device when the object is far

Event	Value	Format	Last Received
Data	{"distance":141.21,"object":"No"}	json	a few seconds ago
Data	{"distance":141.21,"object":"No"}	json	a few seconds ago
Data	{"distance":141.21,"object":"No"}	json	a few seconds ago
Data	{"distance":141.18,"object":"No"}	json	a few seconds ago
Data	{"distance":141.2,"object":"No"}	json	a few seconds ago

when object is near to the ultrasonic sensor

Data sent to the IBM Cloud Device when the object is near

The screenshot shows the IBM Cloud Device interface. On the left is a sidebar with icons for Home, Devices, Actions, Metrics, Events, Logs, and Help. The main area has tabs for Browse, Action, Device Types, and Interfaces. A blue header bar displays the device name "DISTANCEDETECT", its status as "Disconnected", the interface "ULTRASON", the device type "Device", the date and time "Oct 20, 2022 9:46 AM", and an "Add Device" button. Below the header is a navigation bar with tabs for Identity, Device Information, Recent Events (which is selected), State, and Logs. A message states: "The recent events listed show the live stream of data that is coming from this device." A table lists five recent events:

Event	Value	Format	Last Received
Data	{"distance":79.66,"object":"Near"}	json	a few seconds ago
Data	{"distance":79.64,"object":"Near"}	json	a few seconds ago
Data	{"distance":79.66,"object":"Near"}	json	a few seconds ago
Data	{"distance":79.64,"object":"Near"}	json	a few seconds ago

At the bottom, there are pagination controls: "Items per page: 50" with a dropdown, "1–2 of 2 items", "1 of 1 page", and navigation arrows.

<https://wokwi.com/projects/305566932847821378>