ASSIGNMENT-4

Date	29 Oct 2022		
Student roll no	912619104014		
Student name	R.NIROSHIKA		
Project Name	Real-Time Communication System Powered by AI		
	for Specially Abled		
Maximum mark	2 mark		

 $1.\ Download\ the\ dataset:\ \underline{https://www.kaggle.com/code/kredy10/simple-lstm-for-text-classification/**data}**$

```
[ ] import numpy as np
  import pandas as pd
  import matplotlib.pyplot as plt
  import seaborn as sns
  import keras
  from sklearn.model_selection import train_test_split
  from sklearn.preprocessing import LabelEncoder
  from keras.models import Model
  from keras.awors import Model
  from keras.layers import RMSprop
  from keras.optimizers import RMSprop
  from keras.preprocessing.text import Tokenizer
  from keras.preprocessing import sequence
  from keras.utils import to_categorical, pad_sequences
  from keras.callbacks import EarlyStopping
  %matplotlib inline
```

2. Import Required libararies

[] df = pd.read_csv('/content/spam.csv',delimiter=',',encoding='latin-1')
 df.head()

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy Available only	NaN	NaN	NaN
1	ham	Ok lar Joking wif u oni	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina	NaN	NaN	NaN
3	ham	U dun say so early hor U c already then say	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro	NaN	NaN	NaN

3. Read dataset and pre-processing

```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
[ ] df.shape
    (5572, 2)
[\ ] #plot the ham and spam messages to understand the distribution
    df['v1'].value_counts().plot(kind='bar')
    plt.xlabel('Label')
    plt.title('Number of ham and spam messages')
    Text(0.5, 1.0, 'Number of ham and spam messages')
                Number of ham and spam messages
      4000
      3000
      2000
      1000
                             Label
 [ ] X = dt.v2
      Y = df.v1
      #label encoding for Y
      le = LabelEncoder()
      Y = le.fit_transform(Y)
      Y = Y.reshape(-1,1)
 #split into train and test sets
      X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.20)
 [ ] max_words = 1000
      max_len = 150
      tok = Tokenizer(num_words=max_words)
      tok.fit_on_texts(X_train)
      sequences = tok.texts_to_sequences(X_train)
      sequences_matrix = keras.utils.pad_sequences(sequences,maxlen=max_len)
```

4. Add Layers(LSTM, Dense-(Hidden Layers), Output)

```
inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
```

5. Create Model

```
[ ] model = Model(inputs=inputs,outputs=layer)
```

6. Compile the Model

```
[ ] model.summary()
    model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
   Model: "model"
    Layer (type)
                           Output Shape
                                                  Param #
    _____
    inputs (InputLayer)
                           [(None, 150)]
    embedding (Embedding)
                                                50000
                          (None, 150, 50)
    1stm (LSTM)
                           (None, 64)
                                                 29440
                                                 16640
    FC1 (Dense)
                           (None, 256)
    activation (Activation)
                           (None, 256)
    dropout (Dropout)
                           (None, 256)
                                                 257
    out_layer (Dense)
                           (None, 1)
    activation_1 (Activation) (None, 1)
    Total params: 96,337
    Trainable params: 96,337
    Non-trainable params: 0
```

7.Fit the Model

8. Save the Model

```
[ ] model.save('spam_lstm_model.h5')
```

9.Test the Model

```
[ ] #processing test data
    test_sequences = tok.texts_to_sequences(X_test)
    test_sequences_matrix = keras.utils.pad_sequences(test_sequences,maxlen=max_len)

[ ] #evaluation of our model
    accr = model.evaluate(test_sequences_matrix,Y_test)
    print('Test set\n Loss: {:0.3f}\n Accuracy: {:0.3f}'.format(accr[0],accr[1]))

35/35 [=========] - 1s 25ms/step - loss: 0.0627 - accuracy: 0.9839
Test set
    Loss: 0.063
    Accuracy: 0.984
```