Assignment_3

November 17, 2022

Assignment Date	01 October 2022
Student Name Student Roll Number Maximum Marks	Prajeen R G 2019504560 2 Marks

1 Build CNN Model for Classification Of Flowers

```
[24]: import tensorflow as tf
from tensorflow.keras import layers
from tensorflow.keras.models import Sequential
import numpy as np
```

```
[25]: batch_size = 32
img_height = 180
img_width = 180

data_dir = "../input/flowers-ibmntp/flowers"
```

1.0.1 Image augmentation

```
[26]: data_augmentation = Sequential(
    [
        layers.RandomFlip("horizontal",input_shape=(img_height, img_width, 3)),
        layers.RandomRotation(0.1),
        layers.RandomZoom(0.1),
        ]
    )
```

1.0.2 Split dataset into training and testing sets

```
[27]: train_ds = tf.keras.utils.image_dataset_from_directory(
    data_dir,
    validation_split=0.2,
    subset="training",
    seed=123,
```

```
image_size=(img_height, img_width),
batch_size=batch_size)
```

Found 4317 files belonging to 5 classes. Using 3454 files for training.


Found 4317 files belonging to 5 classes. Using 863 files for validation.

```
[29]: class_names = train_ds.class_names print(class_names)
```

['daisy', 'dandelion', 'rose', 'sunflower', 'tulip']

```
[30]: import matplotlib.pyplot as plt

plt.figure(figsize=(10, 10))
for images, labels in train_ds.take(1):
    for i in range(9):
        ax = plt.subplot(3, 3, i + 1)
        plt.imshow(images[i].numpy().astype("uint8"))
        plt.title(class_names[labels[i]])
        plt.axis("off")
```



```
[31]: normalization_layer = layers.Rescaling(1./255)
```

```
[32]: normalized_ds = train_ds.map(lambda x, y: (normalization_layer(x), y))
  image_batch, labels_batch = next(iter(normalized_ds))
  first_image = image_batch[0]
  # Notice the pixel values are now in `[0,1]`.
  print(np.min(first_image), np.max(first_image))
```

0.0 0.97046

1.0.3 Create the model and adding layers

```
[33]: num_classes = len(class_names)

model = Sequential([
    data_augmentation,
    layers.Rescaling(1./255, input_shape=(img_height, img_width, 3)),
    layers.Conv2D(16, 3, padding='same', activation='relu'),
    layers.MaxPooling2D(),
    layers.Conv2D(32, 3, padding='same', activation='relu'),
    layers.MaxPooling2D(),
    layers.Conv2D(64, 3, padding='same', activation='relu'),
    layers.MaxPooling2D(),
    layers.Flatten(),
    layers.Dense(128, activation='relu'),
    layers.Dense(num_classes)
])
```

1.0.4 Compile the model

[35]: model.summary()

Model: "sequential_2"

Layer (type)	Output	Shape	Param #
sequential_1 (Sequential)	(None,	180, 180, 3)	0
rescaling_3 (Rescaling)	(None,	180, 180, 3)	0
conv2d_3 (Conv2D)	(None,	180, 180, 16)	448
max_pooling2d_3 (MaxPooling2	(None,	90, 90, 16)	0
conv2d_4 (Conv2D)	(None,	90, 90, 32)	4640
max_pooling2d_4 (MaxPooling2	(None,	45, 45, 32)	0
conv2d_5 (Conv2D)	(None,	45, 45, 64)	18496
max_pooling2d_5 (MaxPooling2	(None,	22, 22, 64)	0

1.0.5 Fit the model

```
[36]: epochs=10
history = model.fit(
    train_ds,
    validation_data=val_ds,
    epochs=epochs
)
```

```
Epoch 1/10
108/108 [============= ] - 12s 98ms/step - loss: 1.3587 -
accuracy: 0.4311 - val_loss: 1.1208 - val_accuracy: 0.5481
Epoch 2/10
108/108 [============ ] - 8s 63ms/step - loss: 1.0440 -
accuracy: 0.5926 - val_loss: 1.0209 - val_accuracy: 0.6083
Epoch 3/10
accuracy: 0.6283 - val_loss: 0.9353 - val_accuracy: 0.6431
Epoch 4/10
108/108 [============ ] - 8s 66ms/step - loss: 0.8782 -
accuracy: 0.6726 - val_loss: 0.8580 - val_accuracy: 0.6582
Epoch 5/10
108/108 [============= ] - 7s 61ms/step - loss: 0.8522 -
accuracy: 0.6699 - val_loss: 0.9512 - val_accuracy: 0.6211
Epoch 6/10
108/108 [============ ] - 7s 61ms/step - loss: 0.8144 -
accuracy: 0.6957 - val_loss: 0.8153 - val_accuracy: 0.6651
Epoch 7/10
108/108 [============= ] - 7s 58ms/step - loss: 0.7433 -
accuracy: 0.7215 - val_loss: 0.7417 - val_accuracy: 0.7115
Epoch 8/10
accuracy: 0.7336 - val_loss: 0.7869 - val_accuracy: 0.6813
Epoch 9/10
108/108 [============= ] - 7s 62ms/step - loss: 0.6884 -
accuracy: 0.7360 - val loss: 0.7605 - val accuracy: 0.7080
Epoch 10/10
```

```
[37]: | acc = history.history['accuracy']
      val_acc = history.history['val_accuracy']
      loss = history.history['loss']
      val_loss = history.history['val_loss']
      epochs_range = range(epochs)
      plt.figure(figsize=(8, 8))
      plt.subplot(1, 2, 1)
      plt.plot(epochs_range, acc, label='Training Accuracy')
      plt.plot(epochs_range, val_acc, label='Validation Accuracy')
      plt.legend(loc='lower right')
      plt.title('Training and Validation Accuracy')
      plt.subplot(1, 2, 2)
      plt.plot(epochs_range, loss, label='Training Loss')
      plt.plot(epochs_range, val_loss, label='Validation Loss')
      plt.legend(loc='upper right')
      plt.title('Training and Validation Loss')
      plt.show()
```



1.0.6 Save the model

```
[38]: model.save("flowers.m5")
```

1.0.7 Testing the model

```
img_array = tf.keras.utils.img_to_array(img)
img_array = tf.expand_dims(img_array, 0) # Create a batch

predictions = model.predict(img_array)
score = tf.nn.softmax(predictions[0])

print(
    "This image most likely belongs to {} with a {:.2f} percent confidence."
    .format(class_names[np.argmax(score)], 100 * np.max(score))
)
```