## **Assignment -4**

#### Wokwi and IBM cloud connection

Student Name	VASANTHARAJ M
Student Roll Number	6113191041112
Maximum Marks	2 Marks

# **Question-1:**

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100cms send "alert" to IBM cloud and display in device recent events (Upload document with wokwi share link and images of IBM cloud).

### **Solution:**

**Wokwi link:** https://wokwi.com/projects/347467009158546002

### Code:

#include <WiFi.h>//library for wifi #include <PubSubClient.h>//library for MQtt

void callback(char\* subscribetopic, byte\* payload, unsigned int payloadLength);

#define ORG "hbgvif"//IBM ORGANITION ID

#define DEVICE\_TYPE "Board"//Device type mentioned in ibm watson IOT Platform #define DEVICE\_ID "1234"//Device ID mentioned in ibm watson IOT Platform #define TOKEN "12345678" //Token String data3;

```
//------ Customise the above values -------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and format in
which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT command type AND
COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
```

```
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback, wifiClient); //calling the predefined client id by passing
parameter like server id, portand wificredential
#define echoPin 10
#define trigPin 11
float duration;
float distance;
void setup() {
 pinMode(trigPin, OUTPUT);
 pinMode(echoPin, INPUT);
 Serial.begin(9600);
void loop() {
 // Clears the trigPin condition
 digitalWrite(trigPin, LOW);
 delayMicroseconds(2);
 // Sets the trigPin HIGH (ACTIVE) for 10 microseconds
 digitalWrite(trigPin, HIGH);
 delayMicroseconds(10);
 digitalWrite(trigPin, LOW);
 // Reads the echoPin, returns the sound wave travel time in microseconds
 duration = pulseIn(echoPin, HIGH);
 // Calculating the distance
 distance = duration * 0.034/2; // Speed of sound wave divided by 2 (go and back)
 // Displays the distance on the Serial Monitor
 Serial.print("Distance: ");
 Serial.print(distance);
 Serial.println(" cm");
 if(distance<100)
  Serial.println("Alert:Object is between 100cm");
/*.....retrieving to Cloud.....*/
void PublishData(float distance) {
```

```
mqttconnect();//function call for connecting to ibm
   creating the String in in form JSon to update the data to ibm cloud
 String payload = "{\"distance\":";
 payload += distance;
 payload += "}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
  Serial.println("Publish ok");// if it successfully upload data on the cloud then it will print publish ok in
Serial monitor or else it will print publish failed
 } else {
  Serial.println("Publish failed");
}
void mqttconnect() {
 if (!client.connected()) {
  Serial.print("Reconnecting client to ");
  Serial.println(server);
  while (!!!client.connect(clientId, authMethod, token)) {
   Serial.print(".");
   delay(500);
   initManagedDevice();
   Serial.println();
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
 while (WiFi.status() != WL_CONNECTED) {
  delay(500);
  Serial.print(".");
```

```
Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
void initManagedDevice() {
 if (client.subscribe(subscribetopic)) {
  Serial.println((subscribetopic));
  Serial.println("subscribe to cmd OK");
 } else {
  Serial.println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
 for (int i = 0; i < payloadLength; i++) {
  //Serial.print((char)payload[i]);
  data3 += (char)payload[i];
 Serial.println("data: "+ data3);
data3="";
```

