1.Import requried library

```
import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input,
Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras_preprocessing import sequence
from keras.utils import to_categorical
from keras.models import load_model
```

```
import csv
import tensorflow as tf
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from tensorflow.keras.preprocessing.text import Tokenizer
from tensorflow.keras.preprocessing.sequence import pad_sequences
import nltk
nltk.download('stopwords')
from nltk.corpus import stopwords
STOPWORDS = set(stopwords.words('english'))
```

```
[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data]   Unzipping corpora/stopwords.zip.
```

2.Read dataset and do preprocessing

```
import pandas as pd
import numpy as np
import seaborn as sns
import matplotlib.pyplot as plt
%matplotlib inline
```

```
df =
pd.read_csv('/content/drive/MyDrive/spam.csv',delimiter=',',encoding='
latin-1')
df.head()
```

```
     v1                                                 v2 Unnamed: 2
\
0   ham  Go until jurong point, crazy.. Available only ...        NaN

1   ham                      Ok lar... Joking wif u oni...        NaN

2  spam  Free entry in 2 a wkly comp to win FA Cup fina...        NaN
```

```
3   ham  U dun say so early hor... U c already then say...         NaN

4   ham  Nah I don't think he goes to usf, he lives aro...         NaN


  Unnamed: 3 Unnamed: 4
0        NaN        NaN
1        NaN        NaN
2        NaN        NaN
3        NaN        NaN
4        NaN        NaN
```

```
df.drop(['Unnamed: 2','Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
```

#dropping unwanted columns

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 2 columns):
 #   Column  Non-Null Count  Dtype
---  ------  --------------  -----
 0   v1      5572 non-null   object
 1   v2      5572 non-null   object
dtypes: object(2)
memory usage: 87.2+ KB
```

#Count of Spam and Ham values

```
df.groupby(['v1']).size()
```

```
v1
ham     4825
spam     747
dtype: int64
```

#Label Encoding target column

```
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

 # Test and train spilit

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

 # Tokenisation function

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = sequence.pad_sequences(sequences,maxlen=max_len)
```

3.Create Model

4.Add layers (LSTM ,Dense-(Hidden Layers),Ouput)

```
#creating LSTM model
inputs = Input(name='InputLayer',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FullyConnectedLayer1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='OutputLayer')(layer)
layer = Activation('sigmoid')(layer)
```

5. Compile the model

```
model = Model(inputs=inputs,outputs=layer)
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=[
'accuracy'])
```

```
Model: "model"
_________________________________________________________________
 Layer (type)                Output Shape              Param #
=================================================================
 InputLayer (InputLayer)     [(None, 150)]             0

 embedding (Embedding)       (None, 150, 50)           50000

 lstm (LSTM)                 (None, 64)                29440

 FullyConnectedLayer1 (Dense  (None, 256)              16640
 )

 activation (Activation)     (None, 256)               0

 dropout (Dropout)           (None, 256)               0

 OutputLayer (Dense)         (None, 1)                 257

 activation_1 (Activation)   (None, 1)                 0

=================================================================
Total params: 96,337
Trainable params: 96,337
Non-trainable params: 0
_________________________________________________________________
```

6.Fit the model

```
model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,
          validation_split=0.2)
```

```
Epoch 1/10
30/30 [==============================] - 8s 263ms/step - loss: 0.0035
- accuracy: 0.9995 - val_loss: 0.1122 - val_accuracy: 0.9863
Epoch 2/10
30/30 [==============================] - 13s 454ms/step - loss: 0.0026
- accuracy: 0.9995 - val_loss: 0.1018 - val_accuracy: 0.9873
Epoch 3/10
30/30 [==============================] - 14s 468ms/step - loss: 0.0026
- accuracy: 0.9992 - val_loss: 0.0911 - val_accuracy: 0.9852
Epoch 4/10
30/30 [==============================] - 15s 493ms/step - loss: 0.0023
- accuracy: 0.9995 - val_loss: 0.1240 - val_accuracy: 0.9852
Epoch 5/10
30/30 [==============================] - 10s 349ms/step - loss: 0.0015
- accuracy: 0.9995 - val_loss: 0.1336 - val_accuracy: 0.9863
Epoch 6/10
30/30 [==============================] - 7s 249ms/step - loss: 0.0026
- accuracy: 0.9992 - val_loss: 0.1339 - val_accuracy: 0.9873
Epoch 7/10
30/30 [==============================] - 9s 289ms/step - loss:
3.0076e-04 - accuracy: 0.9997 - val_loss: 0.1313 - val_accuracy:
0.9873
Epoch 8/10
30/30 [==============================] - 8s 255ms/step - loss:
4.5712e-04 - accuracy: 0.9997 - val_loss: 0.1547 - val_accuracy:
0.9873
Epoch 9/10
30/30 [==============================] - 8s 253ms/step - loss:
1.8049e-04 - accuracy: 1.0000 - val_loss: 0.1490 - val_accuracy:
0.9863
Epoch 10/10
30/30 [==============================] - 11s 366ms/step - loss:
4.6702e-05 - accuracy: 1.0000 - val_loss: 0.1521 - val_accuracy:
0.9873

<keras.callbacks.History at 0x7f284144c9d0>
```

7.Save the model

```
model.save("model_1")
```

```
WARNING:absl:Function `_wrapped_model` contains input name(s)
InputLayer with unsupported characters which will be renamed to
inputlayer in the SavedModel.
WARNING:absl:Found untraced functions such as
lstm_cell_layer_call_fn,
lstm_cell_layer_call_and_return_conditional_losses while saving
(showing 2 of 2). These functions will not be directly callable
after loading.
```

8.Test the Model

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix =
sequence.pad_sequences(test_sequences,maxlen=max_len)
```

```
accuracy =
model.evaluate(test_sequences_matrix,Y_test)
print('Accuracy: {:0.3f}'.format(accuracy[1]))
```

```
27/27 [==============================] - 1s 49ms/step - loss: 0.2340
-
accuracy: 0.9809
Accuracy: 0.981
```

```
y_pred = model.predict(test_sequences_matrix)
print(y_pred[25:40].round(3))
```

```
27/27 [==============================] - 1s 23ms/step
[[0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
 [0.]
```

```
 [0.]]


print(Y_test[25:40

])[[0]
 [0]
 [0]
 [0]
 [0]
 [0]
 [0]
 [0]
 [0]
 [0]
 [0]
 [0]
 [0]
 [0]
 [0]]
```