Databases

Database name | Create Database | { } JSON

Your Databases

Name	Size	# of Docs	Partitioned	Actions
sample	1.2 KB	1	No	

Log Out

Showing 1–1 of 1 databases. Databases per page 20 « 1 »

IBM | Cloud Products Solutions Pricing Docs Support Explore more Console

Cloudant

Overview
- Introduction
- Authentication
  - Security scheme
  - Authentication with external configuration
  - Programmatic authentication
- Event tracking
- Error handling
- Logging

Methods
- Server
- Databases
- Documents
- Design Documents
- Views

SDK using the `IBMCloudEnv` tool to obtain the configuration information from bound services. The `IBMCloudEnv` tool is available for Go, Java (Spring), Node.js, and Python.

Curl Java Node Python Go

```
service.set_service_url('{url}')
```

SDK managing session cookie.

```
from ibmcloudant.cloudant_v1 import CloudantV1
from ibmcloudant import CouchDbSessionAuthenticator

authenticator = CouchDbSessionAuthenticator('{username}',
'{password}')

service = CloudantV1(authenticator=authenticator)

service.set_service_url('{url}')
```

Basic authentication.

```
from ibmcloudant.cloudant_v1 import CloudantV1
from ibmcloudant import CouchDbSessionAuthenticator
from ibm_cloud_sdk_core.authenticators import
BasicAuthenticator

authenticator = BasicAuthenticator('{username}',
'{password}')

service = CloudantV1(authenticator=authenticator)

service.set_service_url('{url}')
```

FEEDBACK

IBM Cloud | Search resources and offerings... | Catalog Docs Support Manage Nagadeep Nem...

Resource list /

Cloud Object Storage-sk Active Add tags

Transfers Details Actions...

- Getting started
- Buckets
- Integrations New!
- Endpoints
- Service credentials
- Connections
- Usage details
- Plan

Endpoints

Endpoints are used with your credentials (Bucket name, API Key, SDK) to tell your service where to look for your bucket. Choose an endpoint URL that is located in the same region as your service or application. Learn more

Select resiliency: Cross Region

Select location: ap-geo

	public	Private	Direct
ap-geo	s3.ap.cloud-object-storage.appdomain.cloud	s3.private.ap.cloud-object-storage.appdomain.cloud	s3.direct.ap.cloud-object-storage.appdomain.cloud
Tokyo	s3.tok.ap.cloud-object-storage.appdomain.cloud	s3.private.tok.ap.cloud-object-storage.appdomain.cloud	s3.direct.tok.ap.cloud-object-storage.appdomain.cloud
Seoul	s3.seo.ap.cloud-object-storage.appdomain.cloud	s3.private.seo.ap.cloud-object-storage.appdomain.cloud	s3.direct.seo.ap.cloud-object-storage.appdomain.cloud
Hong Kong	s3.hkg.ap.cloud-object-storage.appdomain.cloud	s3.private.hkg.ap.cloud-object-storage.appdomain.cloud	s3.direct.hkg.ap.cloud-object-storage.appdomain.cloud

Legacy Endpoints

FEEDBACK