Delivery of Sprint-2

DATE	4 November 2022
TEAM ID	PNT2022TMID05196
PROJECT NAME	SMART WASTE MANAGEMENT FOR METROPOLITAN CITIES-IOT

Code for Data Transfer from Sensors

```
#include <WiFi.h>                                   // library for wifi
#include <PubSubClient.h>                           // library for MQTT
#include <LiquidCrystal_I2C.h>
LiquidCrystal_I2C lcd(0x27, 20, 4);

//---------------------- credentials of IBM Accounts ------------------------------

#define ORG "9gbe4w"                                // IBM organisation id
#define DEVICE_TYPE "SWMSMC"                        // Device type mentioned in ibm watson iot platform
#define DEVICE_ID "ibmproject"                      // Device ID mentioned in ibm watson iot platform #define
TOKEN "sUNA41tG6-Pq)0rk5X"                  // Token

//---------------------- customise above values ----------------------------------------------------

char server[] = ORG ".messaging.internetofthings.ibmcloud.com";      // server name char
publishTopic[] = "iot-2/evt/data/fmt/json";
char topic[] = "iot-2/cmd/led/fmt/String";                          // cmd Represent type and command is test format of strings
char authMethod[] = "use-token-auth";                               // authentication method char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;           //Client id

//-------------------------------------------------------------------------------------------------------------------

WiFiClient wifiClient;                                      // creating instance for wificlient
PubSubClient client(server, 1883, wifiClient);

#define ECHO_PIN 12 #define
TRIG_PIN 13
float dist;

void setup()
{
 Serial.begin(115200);
pinMode(LED_BUILTIN,   OUTPUT);
pinMode(TRIG_PIN,       OUTPUT);
pinMode(ECHO_PIN, INPUT);
 //pir pin
 pinMode(4, INPUT);

 //ledpins
pinMode(23, OUTPUT);
pinMode(2, OUTPUT);
pinMode(4, OUTPUT);
 pinMode(15, OUTPUT);


 lcd.init();
lcd.backlight();
lcd.setCursor(1, 0);
```

```
lcd.print("");
wifiConnect();
 mqttConnect();
}

float readcmCM()
{
 digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);   int
duration = pulseIn(ECHO_PIN, HIGH);
 return duration * 0.034 / 2;
}

void loop()
 {

 lcd.clear();

 publishData();
delay(500);
 if (!client.loop())
  {
    mqttConnect();                                                    // function call to connect to IBM
}
}

/* ------------------------------------------------------------retrieving to cloud----------------------------------------------------*/

void wifiConnect()
{
 Serial.print("Connecting to ");
 Serial.print("Wifi");
 WiFi.begin("Wokwi-GUEST", "", 6);
 while (WiFi.status() != WL_CONNECTED)
  {
    delay(500);
Serial.print(".");
  }
 Serial.print("WiFi connected, IP address: ");
 Serial.println(WiFi.localIP());
}
void mqttConnect()
 {
  if (!client.connected())
   {
     Serial.print("Reconnecting MQTT client to ");
Serial.println(server);       while (!client.connect(clientId,
authMethod, token))
       {
         Serial.print(".");
         delay(500);
       }
      initManagedDevice();
      Serial.println();
    }
 }
void initManagedDevice()
 {
  if (client.subscribe(topic))
```

```
    {
      Serial.println("IBM subscribe to cmd OK");
    }
else
{
Serial.p
rintln("s
ubscrib
e to
cmd
FAILED"
);
    }
 }
void publishData()
{
 float cm = readcmCM();

 if(digitalRead(34))                                          //PIR motion detection
{
   Serial.println("Motion Detected");
Serial.println("Lid          Opened");
digitalWrite(15, HIGH);

}
 else
 {
   digitalWrite(15, LOW);
 }

 if(digitalRead(34)== true)
 {
  if(cm <= 100)                                              //Bin level detection
  {
   digitalWrite(2, HIGH);
   Serial.println("High Alert!!!,Trash bin is about to be full");
   Serial.println("Lid Closed");
lcd.print("Full! Don't use");
delay(2000);
   lcd.clear();
digitalWrite(4, LOW);
digitalWrite(23, LOW);
  }
  else if(cm > 150 && cm < 250)
  {
   digitalWrite(4, HIGH);
   Serial.println("Warning!!,Trash is about to cross 50% of bin level");
digitalWrite(2, LOW);    digitalWrite(23, LOW);
  }
  else if(cm > 250 && cm <=400)
  {
   digitalWrite(23,          HIGH);
Serial.println("Bin  is  available");
digitalWrite(2,LOW);
   digitalWrite(4, LOW);
  }
   delay(10000);
   Serial.println("Lid Closed");
 }
 else
 {
  Serial.println("No motion detected");
```

```
}



 if(cm <= 100)
{
digitalWrite(21,HIGH);
String payload = "{\"High Alert!!\":\"";
payload += cm; payload
+= "left\" }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str()))        // if data is uploaded to cloud successfully,prints publish ok or prints publish failed
{
Serial.println("Publish OK");
}
}
if(cm <= 250)
{
digitalWrite(22,HIGH);
String payload = "{\"Warning!!\":\"";
payload += dist; payload += "left\"
}";
Serial.print("\n");
Serial.print("Sending distance: "); Serial.println(cm);
if(client.publish(publishTopic, (char*) payload.c_str()))
{
Serial.println("Publish OK");
}
else
{
Serial.println("Publish FAILED");
}
}

 float inches = (cm / 2.54);                                                                    //print on LCD
lcd.setCursor(0,0);  lcd.print("Inches");  lcd.setCursor(4,0);  lcd.setCursor(12,0);  lcd.print("cm");
lcd.setCursor(1,1);  lcd.print(inches, 1);  lcd.setCursor(11,1);  lcd.print(cm, 1);
lcd.setCursor(14,1);  delay(1000);  lcd.clear();
}
```

Connection Diagram