

ASSIGNMENT- 4

Register Number	921319104190
Date	15 th October ,2022
Student Name	SOWMIYA K
Maximum Marks	2 Marks

#Import required libraries

```
import pandas as pd
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input,
Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
```

#Read dataset and do pre-processing

```
df = pd.read_csv(
    'sample_data/spam.csv',
    delimiter = ',', encoding =
    'latin-1'
)
df.drop(
    ['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],
    axis = 1, inplace
    = True
)
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1, 1)
X_train, X_test, Y_train, Y_test = train_test_split(X,
    Y,
    test_size = 0.15
)
```

```

max_words = 1000
max_len = 150
tok = Tokenizer(num_words = max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences, maxlen = max_len)

```

#Add Layers (LSTM, Dense-(Hidden Layers), Output)

```
def RNN():
```

```

    inputs = Input(name = 'inputs', shape = [max_len])
    layer = Embedding(max_words, 50, input_length = max_len)(inputs)

```

```

    layer = LSTM(64)(layer)
    layer = Dense(256,name = 'FC1')(layer)
    layer = Activation('relu')(layer)
    layer = Dropout(0.5)(layer)
    layer = Dense(1,name = 'out_layer')(layer)
    layer = Activation('sigmoid')(layer)
    model = Model(inputs = inputs, outputs = layer)
    return model

```

```
#Create model =
```

```
RNN() #Compile
```

```
the model
```

```

model.compile(loss = 'binary_crossentropy', optimizer = RMSprop(),metrics =
['accuracy'])

```

#Fit the model

```

model.fit(
    sequences_matrix,
    Y_train, batch_size
    = 128,epochs=10,
    validation_split = 0.2,
    callbacks=[EarlyStopping(monitor = 'val_loss', min_delta =0.0001)])

```

```
Epoch 1/10
```

```
30/30 [=====] - 12s 296ms/step - loss: 0.3357
```

```
- accuracy: 0.8672 - val_loss: 0.1516 - val_accuracy: 0.9757Epoch
```

```
2/10
```

```
30/30 [=====] - 8s 272ms/step - loss: 0.0924  
- accuracy: 0.9762 - val_loss: 0.0530 - val_accuracy: 0.9873
```

```
<keras.callbacks.History at 0x7fdb374d5250>
```

```
#Save the model
```

```
model.save('./spam.h5')
```

```
#Test the model
```

```
test_sequences = tok.texts_to_sequences(X_test) test_sequences_matrix =  
pad_sequences(test_sequences, maxlen=max_len)  
accr = model.evaluate(test_sequences_matrix, Y_test)print("Test  
set\n Loss: {:.3f}\n Accuracy:  
{:.3f}'.format(accr[0],accr[1]))
```

```
27/27 [=====] - 1s 26ms/step - loss: 0.0550 -  
accuracy: 0.9880
```

Test set Loss:

0.055

Accuracy: 0.9

