PROJECT DEVELOPMENT PHASE
SPRINT- 4

Date	17 NOVEMBER 2022
Team ID	PNT2022TMID42437
Project Name	Project - Hazardous Area Monitoring for Industrial Plant powered by IoT
Maximum Marks	4 Marks

CODE :

```
#include <WiFi.h>
#include <PubSubClient.h>
#include <DHT.h>
WiFiClient wifiClient;
String data3;
#define DHTTYPE DHT11
#define DHTPIN 4
#define MQTPIN 34
DHT dht(DHTPIN, DHTTYPE);

#define ORG "v6wg8x"
#define DEVICE_TYPE "projectFinal"
#define DEVICE_ID "FinalDeliverable"
#define TOKEN "A1ymH))p*JB&iMWNpY"
#define speed 0.034
```

```
void callback(char* topic, byte* playload, unsigned int payloadLength);

char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/Data/fmt/json"; char topic[] =
"iot-2/cmd/test/fmt/String"; char authMethod[] = "use-token-
auth"; char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
PubSubClient client(server, 1883, callback , wifiClient); void
publishData();

String command;
String data = "";

long duration; float
dist;



void setup()
{
  Serial.begin(115200);
dht.begin();   wifiConnect();
mqttConnect();
}

void loop() {
publishData();
delay(500);

  if (!client.loop()) {
mqttConnect();
  }
}
```

```
void wifiConnect() {
  Serial.print("Connecting to "); Serial.print("Wifi");
WiFi.begin("JerroldWi-Fi","75779901");   while
(WiFi.status() != WL_CONNECTED) {     delay(500);
Serial.print(".");
  }
  Serial.print("WiFi connected, IP address: "); Serial.println(WiFi.localIP());
}

void mqttConnect() {   if
(!client.connected()) {
    Serial.print("Reconnecting MQTT client to "); Serial.println(server);
while (!client.connect(clientId, authMethod, token)) {
Serial.print(".");       delay(500);
    }
    initManagedDevice();
    Serial.println();
  }
}

void initManagedDevice() {
if (client.subscribe(topic)) {
    Serial.println("IBM subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
  }
}

void publishData()
{
  int sensorValue = analogRead(MQTPIN); //MQT 135 connected to GPIO 34 (Analog
ADC1_CH6)
  Serial.print("AirQua=");
  Serial.print(sensorValue, DEC);
```

```
  Serial.println(" PPM");   float humid =
dht.readHumidity();   float temp =
dht.readTemperature(true);   String
payload = "{\"Humidity\":";   payload +=
humid;   payload += "}";
  if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish OK");
  }
  payload = "{\"Temperature\":";
payload += temp;   payload +=
"}";
  if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish OK");
  }
  payload = "{\"AirQuality\":";
payload += String(sensorValue);
payload += "}";
  if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish OK");
  }
}
void callback(char* subscribeTopic, byte* payload, unsigned int payloadLength) {
  Serial.print("callback invoked for topic:");
Serial.println(subscribeTopic);   for (int i =
0; i < payloadLength; i++) {     dist +=
(char)payload[i];
  }
  Serial.println("data:" + data3);
if (data3 == "lighton") {
    Serial.println(data3);
  }
  data3 = "";
}
```