Assignment-4

Assignment Date	8 November 2022
Student Name	Vasuki.M
Student Roll Number	513119106095

QUESTION:

Write code and connections in wokwi for ultrasonic sensor. Whenever the distance is less than 100 cms send "alert" to IBM cloud and display in the device recent events.

Output:

```
PROGRAM:
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
//----credentials of IBM Accounts-----
#define ORG "tvfy4f"//IBM ORGANITION ID
#define DEVICE_TYPE "raspberrypi"//Device type mentioned in ibm watson IOT
Platform
#define DEVICE_ID "131928"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "12345678" //Token
String data3;
float dist;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/vasu/fmt/json";// topic name and type of event
perform and format in which data to be send
char subscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command
type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback , wifiClient); //calling the predefined
client id by passing parameter like server id, portand wificredential
int LED = 14;
int trig = 13;
int echo = 18;
void setup()
Serial.begin(115200);
```

```
pinMode(trig,OUTPUT);
pinMode(echo,INPUT);
pinMode(LED, OUTPUT);
delay(10);
wificonnect();
mqttconnect();
void loop()// Recursive Function
{
 digitalWrite(trig,LOW);
 digitalWrite(trig,HIGH);
 delayMicroseconds(10);
 digitalWrite(trig,LOW);
 float dur = pulseIn(echo,HIGH);
 float dist = (dur * 0.0343)/2;
 Serial.print ("Distancein cm");
 Serial.println(dist);
 PublishData(dist);
 delay(1000);
 if (!client.loop()) {
   mqttconnect();
 }
}
/*....retrieving to
void PublishData(float dist) {
 mqttconnect();//function call for connecting to ibm
  /*
    creating the String in in form JSon to update the data to ibm cloud
  */
 String object;
  if (dist <100)</pre>
    digitalWrite(LED,HIGH);
   Serial.println("object is near");
   object = "Near";
  }
 else
   digitalWrite(LED, LOW);
   Serial.println("no object found");
   object = "No";
  }
 String payload = "{\"distance\":";
 payload += dist;
  payload += "," "\"object\":\"";
```

```
payload += object;
  payload += "\"}";
  Serial.print("Sending payload: ");
  Serial.println(payload);
  if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish ok");// if it sucessfully upload data on the cloud
then it will print publish ok in Serial monitor or else it will print publish
failed
  } else {
    Serial.println("Publish failed");
  }
}
void mqttconnect() {
  if (!client.connected()) {
    Serial.print("Reconnecting client to ");
    Serial.println(server);
    while (!!!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
      delay(500);
    }
     initManagedDevice();
     Serial.println();
  }
void wificonnect() //function defination for wificonnect
{
  Serial.println();
  Serial.print("Connecting to ");
  WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
the connection
  while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
}
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
    Serial.println((subscribetopic));
```

```
Serial.println("subscribe to cmd OK");
    } else {
        Serial.println("subscribe to cmd FAILED");
    }
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
   Serial.print("callback invoked for topic: ");
   Serial.println(subscribetopic);
   for (int i = 0; i < payloadLength; i++) {</pre>
        //Serial.print((char)payload[i]);
        data3 += (char)payload[i];
   }
             Serial.println("data: "+ data3);
// if(data3=="Near")
// Serial.println(data3);
// digitalWrite(LED,HIGH);
//
      }
//
       else
//
          {
// Serial.println(data3);
// digitalWrite(LED,LOW);
// }
data3="";
}
₩ sketch.ino - Wokwi Arduino and 🗆 🗙 🕇
                                                                                                                                                ∨ - □ ×
                                                                                                                                            🖻 🖈 🗆 🥝 :
 ← → C • wokwi.com/projects/347515229109748308
 M Gmail • YouTube 🔣 Maps 🎂 News 🞧 IBM-Project-16184
₩OKWî 📄 SAVE 🔻 🥕 SHARE 💙 sketch.ino 🖍
                                                                                                                                                      Docs 🤼
  sketch.ino diagram.json libraries.txt Library Manager ▼
1 #include <WiFi.h>//library for wifi
                                                                                                                                                  Ō00:32.187 ⊘102%
        #include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
                                                                                   void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
        float dist;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/vasu/fmt/json";// topic name and type of event perform a
char subscribetopic[] = "iot-2/emd/test/fmt/string";// cmd REPRESENT command type AND CO
char authWethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientid[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ITYPE "!"
        WiFiclient wificlient; // creating the instance for wificlient
PubSubClient client(server,1883, callback ,wificlient); //calling the predefined client i
                                                                                 Sending payload: {"distance":40.30,"object":"Near"}
        int LED = 14;
int trig = 13;
int echo = 18;
void setup()
                                                                                 Publish ok
                                                                                 Distancein cm40.30
                                                                                 object is near
                                                                                 Sending payload: {"distance":40.30,"object":"Near"}
        {
Serial.begin(115200);
pinMode(trig,OUTPUT);
pinMode(echo.INPUT);
                                                                                 Publish ok
                                                                                                                                                      V 0
```



